

Asphalt Milling Machine | SAFE WORK METHOD STATEMENT (SWMS)

TASK OR ACTIVITY: Asphalt Milling Machine

Business Name:	ABN:	SWMS#
Business Address:		
Contact Person:	Phone:	Email:

THIS SAFE WORK METHOD STATEMENT IS APPROVED BY THE PCBU OF THIS PROJECT

Under the Work Health and Safety Regulation (WHS Regulation), a person conducting a business or undertaking (PCBU) is required to ensure that a safe work method statement (SWMS) is prepared before the proposed work starts.

Full Name:		
Signature:	Title:	Date:
Details of the person(s) responsible for ensuring implementation, monitoring compliance of the SWMS as well as reviews and modifications of the SWMS.		
Full Name:	Title:	Phone:

ALL PERSONNEL PARTICIPATING IN ANY ACTIVITY ON THIS SWMS MUST HAVE THE FOLLOWING COMMUNICATED | **NAME OF ALL RELEVANT PERSONNEL WHO HAVE BEEN CONSULTED AND COMMUNICATED TO IN THE DEVELOPMENT AND APPROVAL OF THIS SWMS**

Safety meetings or toolbox talks will be scheduled in accordance with legislative requirements to first identify any site hazards, then to communicate those hazards and then to further take steps to either eliminate or control each hazard.

If an incident or a near miss occurs, all work must stop immediately. Depending on the severity of the incident, a meeting will be called with all workers to amend the SWMS if required. The meeting may also be an educational opportunity.

Any changes made to the SWMS after an incident or a near miss must be approved by the Person Conducting Business or Undertaking and communicated to all relevant personnel.

The SWMS must be kept and be available for inspection at least until the work is completed. Where a SWMS is revised, all versions should be kept. If a notifiable incident occurs in relation to which the SWMS relates, then the SWMS must be kept for at least two years from the occurrence of the notifiable incident.

CLIENT OR PRINCIPAL CONTRACTOR DETAILS	
Client:	SCOPE OF WORKS
Project Name:	
Project Address:	
Project Manager:	
Contact Phone:	
Date SWMS supplied to Project Manager:	

ANY HIGH-RISK CONSTRUCTION WORK BEING CARRIED OUT	
<input type="checkbox"/> involves a risk of a person falling more than 2 meters	<input type="checkbox"/> is carried out on or near pressurised gas mains or piping
<input type="checkbox"/> is carried out on a telecommunication tower	<input type="checkbox"/> is carried out on or near chemical, fuel or refrigerant lines
<input type="checkbox"/> involves demolition of an element of a structure that is load-bearing	<input type="checkbox"/> is carried out on or near energised electrical installations or services
<input type="checkbox"/> involves demolition of an element related to the physical integrity of a structure	<input type="checkbox"/> is carried out in an area that may have a contaminated or flammable atmosphere
<input type="checkbox"/> involves, or is likely to involve, disturbing asbestos	<input type="checkbox"/> involves tilt-up or precast concrete
<input type="checkbox"/> involves structural alteration or repair that requires temporary support to prevent collapse	<input type="checkbox"/> is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor
<input type="checkbox"/> is carried out in or near a confined space	<input type="checkbox"/> is carried out in an area of a workplace where there is any movement of powered mobile plant
<input type="checkbox"/> is carried out in/near a shaft or trench deeper than 2m or tunnel involving use of explosives	<input type="checkbox"/> is carried out in areas with artificial extremes of temperature.
<input type="checkbox"/> is carried out in or near water or other liquid that involves a risk of drowning.	<input type="checkbox"/> involves diving work.

ANY HIGH-RISK MACHINERY OR EQUIPMENT NEARBY

RISK MATRIX									
LIKELIHOOD	INSIGNIFICANT	MINOR	MODERATE	MAJOR	CATASTROPHIC	SCORE	ACTION	HEIRARCHY OF CONTROLS	
ALMOST CERTAIN	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4 ACUTE			Elimination Remove the hazard.	
LIKELY	2 MODERATE	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4A ACUTE	DO NOT PROCEED	Substitution Replace the hazard.	
POSSIBLE	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	4 ACUTE	3H HIGH	Review before work starts.	Isolation Isolate People from the hazard	
UNLIKELY	1 LOW	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	2M MODERATE	Ensure control measures in place.	Engineering Isolate the hazard.	
RARE	1 LOW	1 LOW	2 MODERATE	3 HIGH	3 HIGH	1L LOW	Monitor and keep records	Administrative Change the work.	
								PPE	

Notes on Hierarchy of Controls: Elimination methods are the most effective and preferred when controlling a hazard. Substitution is the second most effective method of controlling a hazard. Engineering by isolation is the third most effective, while Administrative Controls by changing the work is the fourth most effective method. PPE (Personal Protective Equipment) is the least effective method.

PERSONAL PROTECTIVE EQUIPMENT (PPE)											
Select the appropriate PPE above suitable for the equipment used or the job task being performed (if applicable).											
FOOT PROTECTION	HAND PROTECTION	HEAD PROTECTION	HEARING PROTECTION	EYE PROTECTION	RESPIRATORY PROTECTION	FACE PROTECTION	HIGH-VIS CLOTHING	PROTECTIVE CLOTHING	FALL PROTECTION	SUN PROTECTION	HAIR/JEWELLERY SECURED
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Other PPE Required:											
Permit or Licenses Requirements						Mandatory Qualifications and Training					

JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
1. Preparation	Trip hazards, Noise levels	2M	<ul style="list-style-type: none"> - Conduct a pre-start safety briefing to ensure all workers are aware of the specific hazards and procedures involved with using an asphalt milling machine. - Perform a comprehensive risk assessment to identify potential trip hazards in the work area, including uneven surfaces, loose materials, or tools left on the ground. - Clearly mark identified trip hazards with high-visibility paint or signage, and if feasible, remove the hazard altogether to mitigate the risk. - Ensure that walkways and pathways around the work area are kept clear at all times, implementing temporary barriers or tapes to guide pedestrian traffic away from the work zone. - Provide all personnel with personal protective equipment (PPE) appropriate for the job, including safety boots with slip-resistant and puncture-resistant soles to prevent tripping and falling injuries. - Offer ear protection, such as earmuffs or earplugs to every worker and visitor in the vicinity to safeguard against the high noise levels associated with milling machines. - Carry out regular maintenance and inspection of the asphalt milling machine to confirm it is in safe working condition, focusing on parts that may contribute to excessive noise generation. - Limit exposure time to noise by rotating tasks among workers, giving them breaks from the loud environment, or by scheduling noisy operations during periods of less frequent activity. - Implement engineering controls where possible, such as acoustic enclosures or barriers, to reduce noise emissions from the equipment. - Schedule mandatory hearing tests for employees to ensure early detection of noise-induced hearing loss and to reinforce the importance of hearing conservation practices. - Enforce a strict policy to keep non-essential personnel away from the equipment during operation to minimize the number of individuals exposed to trip hazards and noise. - Incorporate anti-vibration mounts or pads beneath milling machinery to dampen vibration and lessen both movement and noise output. - Provide thorough training for all operators and nearby workers about safe operating procedures, emergency stop mechanisms, and effective communication signals or methods while the milling machine is in operation. 	1L
2. Equipment Inspection	Mechanical failure, Electric shocks	3H	<ul style="list-style-type: none"> - Ensure all machinery is subject to a pre-operational check each day before use to identify any defects or maintenance issues that could lead to mechanical failure. Use a standardised checklist that covers all major components of the asphalt milling machine to ensure consistency. - Implement a regular maintenance schedule, in alignment with the manufacturer's recommendations, and keep detailed records to prevent mechanical failures due to wear and tear over time. - Verify that all operators are trained to recognise the signs of electrical faults and understand the emergency shutdown procedures to promptly deal with electric shocks and minimize injury risk. 	1L

JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			<ul style="list-style-type: none"> - Incorporate residual current devices (RCDs) into the electrical circuit to provide an additional layer of protection against electric shock, ensuring these are tested regularly for functionality. - Mandate the use of personal protective equipment (PPE), such as rubber-insulated gloves and non-conductive safety footwear, for operators to minimise the risk of electric shocks. - Conduct tool inspection to identify cracked housings, damaged insulation, or exposed wires, and take defective tools out of service immediately until repairs are made by a qualified technician to prevent electric shocks. - Designate only qualified electricians to perform repair work on the electrical components of the asphalt milling machine to reduce the likelihood of electric shocks caused by improper handling. - Apply lockout/tagout (LOTO) procedures during inspection, maintenance, or any situation where unexpected energisation could cause electric shock or mechanical movement that may result in injury. - Establish and maintain clear labels and warning signs highlighting electric shock risks and important operating guidelines for operators to see easily. - Provide workers with comprehensive training and instructions on safe operating procedures, including how to properly inspect the asphalt milling machine to avoid both mechanical failures and electric shock incidents. Regularly refresh this training to ensure ongoing compliance and understanding. <p>Each control measure should be documented within the Safe Work Method Statement (SWMS) to ensure that every step is accountably adhered to. It's crucial to not just put these controls in place but also to actively monitor their adherence to maintain a safe working environment.</p>	
3. Start of Milling Process	Flying debris, Dust inhalation	2M	<p>See, here is a list of detailed control measures for the work step: 3. Start of Milling Process with the identified hazards of Flying debris and Dust inhalation:</p> <ul style="list-style-type: none"> - Ensure all machinery operators and nearby workers are provided with appropriate personal protective equipment (PPE), including safety goggles or face shields to protect against flying debris, and P2-rated dust masks or respiratory protective equipment (RPE) to prevent dust inhalation. - Fit the asphalt milling machine with well-maintained and effective dust suppression systems such as water spray nozzles or extraction units to minimise airborne dust particles. - Conduct a pre-start inspection of the milling machine to check for any mechanical defects that might cause malfunction or increase the risk of flying debris. - Set up exclusion zones around the milling area where only essential personnel can enter, to keep other workers safe from the risk of flying debris. - Provide appropriate training and competency assessments for all operators on the safe use and emergency shut-down procedures of the milling machine. - Conduct a thorough risk assessment and method statement specific to the particular job before starting the milling process, ensuring all potential risk of flying debris and dust inhalation are identified and controlled. - Install physical barriers or guarding around the milling drum to contain debris and reduce the risk of material ejection. 	1L

JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			<ul style="list-style-type: none"> - Develop and implement safe work methods or standard operating procedures (SOPs) – such as correct milling pattern and sequence – that aim to reduce the velocity and volume of debris being ejected. - Ensure regular housekeeping and removal of debris in the work area to prevent accumulation which could become a projectile hazard or contribute to dust generation. - Utilise vacuum attachments when available and ensure they are connected and functioning properly to capture dust at the point of origin. - Assess weather conditions, particularly wind speed and direction, before commencement of work to avoid dust being blown towards workers or into the public spaces. - Rotate tasks amongst crew members to limit individual exposure time to high-dust areas and flying debris. - Ensure clear communication is maintained among all workers to promptly identify and address unsafe conditions related to debris and dust. <p>Always remember to comply with the workplace health and safety legislation applicable to your location in Australia and the guidelines set by the Safe Work Australia. Regularly review and update these control measures in response to changes in the work environment or feedback from workers.</p>	
4. Operation of Milling Machine	Crashes and Collisions, ...	3H	<p>[REDACTED]</p> <p>[REDACTED]</p> <p>[REDACTED]</p> <p>[REDACTED]</p> <p>[REDACTED]</p> <p>[REDACTED]</p> <p>[REDACTED]</p> <p>[REDACTED]</p> <p>[REDACTED]</p> <p>[REDACTED]</p>	1L

JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			[REDACTED]	
5. Constant Monitoring	Falls from height, Loss of visibility		[REDACTED]	2M
6. Maintenance Activities	Proximity to moving parts, Chemical exposure	3H	[REDACTED]	1L

SAMPLE

JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			[REDACTED]	
8.Stop Milling Process	Unexpected machine start, Hot surfaces	3H	[REDACTED]	2M

SAMPLE

JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			[REDACTED]	
9.Clean Up	Slips on spilt material, Improper disposal	3H	[REDACTED]	1L

SAMPLE

JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			[REDACTED]	
10. Disassembly of Machine	Crush injuries, Pinch points		[REDACTED]	1L
11. Shut Down	Energy release, Burns	3H	[REDACTED]	1L

SAMPLE

JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			[REDACTED]	
13.Reporting Hazards	Communication breakdowns, Incorrect information	2M	[REDACTED]	1L

SAMPLE

JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			[REDACTED]	
14.Evaluation of Work	Overexertion, Job dissatisfaction	3H	[REDACTED]	1L

SAMPLE

JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			[REDACTED]	
15.Process Review	Non-compliance, Process inefficiency	2M	[REDACTED]	1L

SAMPLE

JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			[REDACTED]	
16.Final Inspection	Missed defects, Complacency endangerment	3H	[REDACTED]	2M

SAMPLE

JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			[REDACTED]	
			[REDACTED]	
			[REDACTED]	
			[REDACTED]	

SAMPLE

EMERGENCY RESPONSE – CALL 000 FOR EMERGENCIES

Ensure to have an Emergency Management Plan in place as well as adequate numbers of trained first aid staff with easy access to fully stocked first aid kits, rescue equipment, material safety data sheets, adequate access to emergency communication equipment and fire-fighting equipment suitable for all classes of fire and ignition sources.

LEGISLATIVE REFERENCES

RELEVANT LEGISLATION AND CODES OF PRACTICE. DELETE THE LEGISLATIVE REFERENCES FOR ANY STATE THAT ARE NOT APPLICABLE

Queensland & Australian Capital Territory

Work Health and Safety Act 2011
 Work Health and Safety Regulations 2011
 Legislation QLD: <https://www.worksafe.qld.gov.au/laws-and-compliance/work-health-and-safety-laws>
 Codes of Practice QLD: <https://www.worksafe.qld.gov.au/laws-and-compliance/codes-of-practice>
 Legislation ACT: <https://www.worksafe.act.gov.au/laws-and-compliance/acts-and-regulations>
 Codes of Practice ACT: <https://www.worksafe.act.gov.au/laws-and-compliance/codes-of-practice>

Victoria

Occupational Health and Safety Act 2004
 Occupational Health and Safety Regulations 2017
 Legislation VIC: <https://www.worksafe.vic.gov.au/occupational-health-and-safety-act-and-regulations>
 Codes of Practice VIC: <https://www.worksafe.vic.gov.au/compliance-codes-and-codes-practice>

New South Wales

Work Health and Safety Act 2011
 Work Health and Safety Regulations 2025
 Legislation NSW: <https://www.safework.nsw.gov.au/legal-obligations/legislation>
 Codes of Practice NSW: <https://www.safework.nsw.gov.au/resource-library/list-codes-of-practice>

Western Australia

Work Health and Safety Act 2020
 Work Health and Safety Regulations 2022
 Legislation Western Australia: <https://www.commerce.wa.gov.au/worksafe/legislation>
 Codes of Practice WA: <https://www.commerce.wa.gov.au/worksafe/codes-practice>

Northern Territory

Work Health and Safety (National Uniform Legislation) Act 2011
 Work Health and Safety (National Uniform Legislation) Regulation 2011
 Legislation NT: <https://worksafe.nt.gov.au/laws-and-compliance/workplace-safety-laws>
 Codes of Practice NT: <https://worksafe.nt.gov.au/laws-and-compliance/codes-of-practice>

Safe Work Australia Links

Law and Regulation (All States): <https://www.safeworkaustralia.gov.au/law-and-regulation>
 Model Codes of Practice: <https://www.safeworkaustralia.gov.au/resources-publications/model-codes-of-practice>

South Australia

Work Health and Safety Act 2012 (SA)
 Work Health and Safety Regulations 2012 (SA)
 Legislation for SA: <https://www.safework.sa.gov.au/resources/legislation>
 Codes of Practice for SA: <https://www.safework.sa.gov.au/workplaces/codes-of-practice#COPs>

Model Codes of Practice

- Managing noise and preventing hearing loss at work
- Confined spaces
- Labelling of workplace hazardous chemicals
- Managing risks of hazardous chemicals in the workplace
- Welding processes
- First aid in the workplace
- Managing the risk of falls at workplaces
- Hazardous manual tasks
- Managing the risk of falls in housing construction
- Managing electrical risks in the workplace
- Demolition work
- Excavation work
- Work health and safety consultation, cooperation and coordination
- Managing the work environment and facilities
- How to manage work health and safety risks
- Managing risks of plant in the workplace
- Construction work

Tasmania

Work Health and Safety Act 2012
 Work Health and Safety (Transitional and Consequential Provisions) Act 2012
 Work Health and Safety Regulations 2012
 Work Health and Safety (Transitional) Regulations 2012
 Legislation for TAS: <https://worksafe.tas.gov.au/topics/laws-and-compliance/acts-and-regulations>
 Codes of Practice for TAS: <https://worksafe.tas.gov.au/topics/laws-and-compliance/codes-of-practice>

Details of permits, licenses or access required by regulatory bodies (add or delete as required):

- Permits from local council
- Authorisation to commence work
- Any required documents.

SIGNATORIES OF THE SAFE WORK METHOD STATEMENT

The signed and dated personnel listed below have cooperated in the consultation and development of this Safe Work Method Statement which has been approved by the Person/s Conducting a Business or Undertaking (PCBU). In signing this Safe Work Method Statement each individual acknowledges and confirms that they have read this SWMS in full, having raised any questions for items on this Safe Work Method Statement that require clarification, and confirms that they are competent, skilled and knowledgeable for the task assigned to them. Every person acknowledges that they have received the relevant training and qualifications where required, before carrying out any work contained in this Safe Work Method Statement. By signing this Safe Work Method Statement each individual agrees to work safely, to follow any safe work instructions which are provided, and agrees to use all Personal Protective Equipment where appropriate.

Worker Name	Signature	Date

SAFE WORK METHOD STATEMENT MONITORING AND REVIEW

The SWMS must be reviewed regularly to make sure it remains effective and must be reviewed (and revised if necessary) if relevant control measures are revised. The review must be carried out in consultation with workers (including contractors and sub-contractors) who may be affected by the operation of the SWMS and their health and safety representatives who represent that work group at the workplace.

When the SWMS has been revised the PCBU must ensure that all persons involved with the work are advised that a revision has been made and how they can access the revised SWMS, including all persons who will need to change a work procedure or system as a result of the review are advised of the changes in a way that will enable them to implement their duties consistently with the revised SWMS. All workers that will be involved in the work must be provided with the relevant information and instruction that will assist them to understand and implement the revised SWMS.

The SWMS must be monitored regularly for the effectiveness of ensuring hazard controls are effective in reducing the risk of incidents, keeping the workplace safe for all personnel. The person responsible for monitoring the effectiveness of the Safe Work Method Statement should employ a multi-faceted approach which includes but is not limited to:

1. Spot Checks.
2. Consultation with workers, contractors and sub-contractors.
3. Internal audits on a continual basis.

An approach of continuous improvement, promptly recording inconsistencies or deficiencies, followed up by immediate corrective action and consultation with all relevant personnel ensures that the PCBU is consistently developing ever-improving systems of safe work principles.

REVIEW NUMBER	1	2	3	4	5	6	7
NAME							
INITIALS							
DATE							

SAFE WORK METHOD STATEMENT REVIEW CHECKLIST

This Safe Work Method Statement Review Checklist is to be followed and used upon initial development of the SWMS to help ensure that all steps have been adequately taken before work commences. Think of this document as an internal audit review checklist before commencing work, and may form part of a Toolbox Talk (safety meeting) and may be used as an opportunity for education and training.

ITEMS WHICH MUST BE INCLUDED IN THE SWMS	COMPLETED	COMMENTS
The company details have been entered, including the project name and address.	<input checked="" type="checkbox"/>	
All relevant personnel consulted during the development of the SWMS.	<input checked="" type="checkbox"/>	
Name, signature, position and date signed of the person approving the SWMS.	<input type="checkbox"/>	
Specific personnel and qualifications, experience is noted in the SWMS.	<input type="checkbox"/>	
Provides a step-by-step process of tasks required to carry out the activity or task.	<input checked="" type="checkbox"/>	
Adequate risk assessment of any identified hazards has been completed.	<input checked="" type="checkbox"/>	
Foreseeable hazards are identified and documented for each step.	<input checked="" type="checkbox"/>	
Any hazards listed in any site risk assessments have been added to the SWMS.	<input checked="" type="checkbox"/>	
SWMS initial risk (IR) column as well as residual risk (RR) column completed.	<input checked="" type="checkbox"/>	
Check control measures added to the SWMS are the most effective selected.	<input checked="" type="checkbox"/>	
Responsible person is assigned and listed on the SWMS for the implementation of control measures.	<input checked="" type="checkbox"/>	
Permit or licenses requirements specified, such as Hot Work, Electrical Work, Work at Heights etc.	<input checked="" type="checkbox"/>	
SWMS identifies plant and equipment to be used.	<input checked="" type="checkbox"/>	
Details of inspection checks required for any equipment listed are noted on the SWMS.	<input checked="" type="checkbox"/>	
Describes any mandatory qualifications, experience, training or skills required to perform the work.	<input checked="" type="checkbox"/>	
Applicable personal protective equipment is selected on the SWMS.	<input checked="" type="checkbox"/>	
Reflects and documents any legislative references and/or Australian Standards.	<input checked="" type="checkbox"/>	
Identifies any hazardous substances used with specific control measures in line with any SDS.	<input checked="" type="checkbox"/>	
REVIEWED BY		DATE REVIEWED
SIGNATURE		DATE COMPLETED