



Battery Safety   S	SAFE WORK METHOD STA	TEMENT (SWMS)	
Т	ASK OR ACTIVITY: Battery Safe	ty	
Business Name:		ABN:	SWMS#
Business Address:			
Contact Person:	Phone:	E jil:	
THIS SAFE WORK METHOD	STATEMENT IS APPRO' D BY	THE PCL OF THE ROJECT	
Under the Work Health and Safety Regulation (WHS Regulation), a person conduct the proposed work starts.	eting a business or under a (PC 1) is	required to en that a safe work method s	statement (SWMS) is prepared before
Full Name:			
Signature:	NY	Title:	Date:
Details of the person(s) responsible for ensuring implementation, monitoring	opliance the VMS a well as review	s and modifications of the SWMS.	
Full Name:		Title:	Phone:
ALL PERSONNEL PARTICIPATING IN ANY ACTIVITY ON THIS S /MS M' HAVE THE FOLLOWING COMMUNICATED	NA, 2 OF ALL RELEVANT PERSONNE EVELOPMENT AND APPROVAL OF	EL WHO HAVE BEEN CONSULTED AND CO THIS SWMS	OMMUNICATED TO IN THE
Safety meetings or toolbox talks will be sched and in account with gislative requirements to first identify any site hazards, and then to further take steps to either eliminate or continuous each hazard.			
If an incident or a near miss occurs, all work must sto, an alately. Depending on the severity of the incident, a meeting will be called with all workers to amend the SWMS if required. The meeting may also be an educational opportunity.			
Any changes made to the SWMS after an incident or a near miss must be approved by the Person Conducting Business or Undertaking and communicated to all relevant personnel.			
The SWMS must be kept and be available for inspection at least until the work is completed. Where a SWMS is revised, all versions should be kept. If a notifiable incident occurs in relation to which the SWMS relates, then the SWMS must be kept for at least two years from the occurrence of the notifiable incident.			

Version 2.5 Authorised by Review # Date of Issue: Review Date: 1





CLIENT OR PRINCIPAL	CONTRACTOR DETAILS
Client:	SCOPE OF WORKS
Project Name:	
Project Address:	
Project Manager:	
Contact Phone:	
Date SWMS supplied to Project Manager:	
ANY HIGH BIOK CONSTRUCTOR	NAME OF THE POLIT
ANY HIGH-RISK CONSTRUCTOR	N WC & BEIN C ARIED OUT
☐ involves a risk of a person falling more than 2 meters	is carried out on or near pressurised gas mains or piping
☐ is carried out on a telecommunication tower	carried out on or near chemical, fuel or refrigerant lines
☐ involves demolition of an element of a structure that is load-bearing	$\square$ is carried out on or near energised electrical installations or services
☐ involves demolition of an element related to the physical integral of a functure	☐ is carried out in an area that may have a contaminated or flammable atmosphere
☐ involves, or is likely to involve, disturbing asb	☐ involves tilt-up or precast concrete
☐ involves structural alteration or repair that —quires term — v sup —rt to prevent collapse	☐ is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor
☐ is carried out in or near a confined space	☐ is carried out in an area of a workplace where there is any movement of powered mobile plant
☐ is carried out in/near a shaft or trench deeper that. tunnel involving use of explosives	☐ is carried out in areas with artificial extremes of temperature.
$\square$ is carried out in or near water or other liquid that involves a risk of drowning.	☐ involves diving work.
ANY HIGH-RISK MACHINER	Y OR EQUIPMENT NEARBY

Version 2.5 Authorised by Review # Date of Issue: Review Date: 2



RISK MATRIX										
LIKELIHOOD	INSIGNIFICANT	MINOR	MODERATE	MAJOR	CATASTROPHIC	SCORE	ACTION	HEI	RARCHY OF CONTROLS	
ALMOST CERTAIN	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4 ACUTE	SCORE	ACTION		Elimination Remove the hazard.	
LIKELY	2 MODERATE	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4A ACUTE	DO NOT PROCE		Substitution	
POSSIBLE	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	4 ACUTE	3H HIGH	Review before work starts.		Replace the hazard.	
UNLIKELY	1 LOW	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	2M MODERATE	Ensure control measures in place.	Isolate	e People from the hazard	
RARE	1 LOW	1 LOW	2 MODERATE	3 HIGH	3 HIGH	1L LOW	nitor and		Engineering Isolate the hazard.	
is the second m	rchy of Controls: ost effective metho nging the work is th	d of controlling a	hazard. Enginee	ering by isolati	on is the in ost e	en 'ive, while	rd. Substitution Administrative effective		Administrative Change the work.  PPE	

				PERS		TIVE EQUIPM					
		Select the app	ropriate PPŁ	abo v uitab	cor the equi	pment used or	the job task	being perforr	ned (if applica	ıble).	
FOOT PROTECTION	HAND PROTECTION	HEAD PROTECTION	HEARING ETION	P ECTION	PROTECTION	FACE PROTECTION	HIGH-VIS CLOTHING	PROTECTIVE CLOTHING	FALL PROTECTION	SUN PROTECTION	HAIR/JEWELLERY SECURED
Other PPE R	equired:										
	Pe	ermit or Licen	ses Requirem	ents		Mandatory Qualifications and Training					



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
1. Preparation	Falls from heights, Manual handling injuries	2M	- Conduct a thorough risk assessment before commencing work to identify potential hazards and establish appropriate control measures.  - Ensure that workers are properly trained in it is a calculating techniques and are aware of the correct procedures for lifting, carrying and moving battle is.  - Provide appropriate personal protective equipment PPF or workers, such as gloves, safety footwear, and back support belt of secessics.  - Establish clean acclusion ones as and the workers at to prevent unauthorised access and reduce the risk of falls fit theights.  - Utility mechanical aids such as trolley, or hoists, whenever possible to assist with the movement and handley of battles or minimise manual handling risks.  - Implementation of the provided walkways and ensure these are kept free of obstructions to minimise trip hazards an ensuring in a sale working environment.  Implementation as a working environment.  Implementation pregular inspection and maintenance schedules for equipment used in battery handling, such ladders, scaffolding, and harnesses, to ensure their safe operation and reliability.  - Bucourage open communication between team members, allowing workers to report any concerns regarding falls from heights or manual handling injuries promptly without fear of reprisal.  - Maintain accurate records of all workplace incidents involving falls or manual handling injuries, analysing trends and implementing corrective actions to continuously improve workplace health and safety practices.  - Regularly review and revise the SWMS to ensure relevance and effectiveness, incorporating new technologies, best practices, or legislative changes as necessary to optimise battery safety in the workplace.	1L
2. Battery Transportation	Battery leaks, Heavy lifting injury	ЗН	<ul> <li>Ensure that all batteries are appropriately packaged in accordance with the manufacturer's recommendations and relevant safety standards, including materials to absorb any potential leaks or spills.</li> <li>Securely fasten battery packages in the transport vehicle to prevent movement during transit, minimising the risk of damage, leakage or spillage.</li> <li>Train personnel involved in battery transportation on the proper handling techniques, including lifting heavy batteries using correct body mechanics to reduce the risk of injury.</li> <li>Use mechanical lifting aids such as forklifts, carts, or trolleys to handle larger, heavier batteries, minimising the risk of manual injuries during loading and unloading.</li> </ul>	2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			<ul> <li>Provide necessary personal protective equipment (PPE) to workers, including gloves, safety goggles, and appropriate footwear to protect against potential exposure to hazardous materials or heavy lifting injuries.</li> </ul>	
			- Clearly label all battery packages with indications of the hazard posed by their contents, ensuring relevant handling precautions are community and to transport personnel.	
			- Regularly inspect delivery vehicles for signs of leaker adamage before transporting batteries, addressing any issues promptly to maintain a manage before transporting batteries,	
			- Maintain communication are not transport person all throughout the journey, with regular check-ins to ensure timely notification and a ponse to any potential in the last that may occur during transportation.	
			- Prepare a continuous, and for a conding to emergencies during battery transportation, such as leaks or spills, including guideling for confinment, of the pup, and disposal of hazardous materials.	
			- Limit the time atteries a stored in port vehicle, particularly in extreme temperatures, to reduce the right batter leaken other temperature-related hazards.	
			- Implying no-sitying policies and enforce prohibition of open flames near battery transportation areas to minitise the possitify of ignition of leaked battery fluids or gases.	
			- Ensure ranse it personnel are knowledgeable about the appropriate weight restrictions and capacities their lode or ansportation to avoid overloading and creating additional risks during battery transports on.	
			Routine valuate and refine transportation procedures to identify areas for improvement and tinuously enhance the overall safety of battery transportation operations.	
			- Consider conducting internal audits or engaging third-party inspectors to review battery transportation practices, ensuring compliance with workplace health and safety regulations and identifying any potential areas for improvement.	
			- Proper training: Ensure that all workers handling and inspecting the batteries are adequately trained on safe battery handling procedures, potential hazards, and emergency response.	
			- Personal Protective Equipment (PPE): Provide suitable PPE such as gloves, safety glasses, and face shields to prevent exposure to battery acid and minimise the risk of electrical shock.	
			- Insulated tools: Use non-conductive or insulated tools when working with or around batteries to reduce the risk of electrical shock.	
3. Battery Inspection	Exposure to battery acid, Electrical shock	3H	- Regular inspections: Conduct periodic inspections of batteries for leakage, corrosion, and damage to ensure early detection of issues and prompt corrective actions.	1L
			- Battery isolation: When possible, isolate the power supply or disconnect the battery terminals before inspection, reducing the chance of electrical discharge during the process.	
			- Safety signage: In addition to proper labeling of batteries, display clear and visible warning signs about electrical hazards and battery acid in the work area.	
			- Ventilation: Ensure good ventilation in the battery storage and inspection areas to avoid the buildup of potentially hazardous gases.	



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			- Securely store batteries: All batteries should be securely stored in designated areas, preventing any accidental damages or spillages during inspection.	
			- Spill containment: Have spill containment material readily available in case of a battery acid leak or spill, enabling quick and effective clean-up.	
			- Emergency eye-wash station: Install an exergency eye-mash station near the work area for immediate access in case of accidental exposure to ball access in case of accidental exposure to ball access in case of accident	
			- First-aid kit: Maintain a fully stocked first-aid knows site, ensuring it includes appropriate treatment supplies for chemical burns and electrical injuries	
			- Safe disposal practices: Prom, and dispose of dama, reaking batteries according to local regulations and guidelines to risk exposure to hazar your substances.	
			- Communication plan: De lop an applement a clear communication plan for workers to raise concerns about battery atted haze as and required sistance if needed.	
			- Control regular transfer and updates: Periodically review and update the SWMS to include new guide and update the structures, and lessons learned from previous incidents. This ensures that control measures and update and effective in managing risks associated with battery inspection tasks.	
4. Ventilation Setup	Inadequate airflow, Overhating	2M		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
5. PPE Donning	Equipment malfunction, Incorrect us e	2M		114



8

JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
6. Battery Removal	Accidental discharg	a BH		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
. Neutralization Process	Chemical burns, A d spillage	4A		3H
				I
				ı



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
8. Terminal Cleaning	Electrical short cir. It, Fire hazard	ЗН		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
9. Level Checking	Overfilling, Spillage			



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
10. Battery Charging	Overcharging, Explosion risk	4A		2M
11. Personal Hygiene	Cross-contamination, Skin irritation	2M		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
12. Storage Area Check	Mishandling, Equipment collapse	2M		<b>1</b> L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
		Non		
	5			



#### **EMERGENCY RESPONSE - CALL 000 FOR EMERGENCIES**

Ensure to have an Emergency Management Plan in place as well as adequate numbers of trained first aid staff with easy access to fully stocked first aid kits, rescue equipment, material safety data sheets, adequate access to emergency communication equipment and fire-fighting equipment suitable for all classes of fire and ignition sources.

#### LEGISLATIVE REFERENCES

RELEVANT LEGISLATION AND CODES OF PRACTICE. DELETE THE LEGISLATIVE REFERENCES. ANY STATE OF AT ARE NOT APPLICABLE.

#### **Queensland & Australian Capital Territory**

Work Health and Safety Act 2011

Work Health and Safety Regulations 2011

Legislation QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/work-health-and-safety-laws Codes of Practice QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/codes-of-practice

Legislation ACT: https://www.worksafe.act.gov.au/laws-and-compliance/acts-and-regulations

Codes of Practice ACT: https://www.worksafe.act.gov.au/laws-and-compliance/codes-of-practice

#### **New South Wales**

Work Health and Safety Act 2011

Work Health and Safety Regulations 2017

Legislation NSW: https://www.safework.nsw.gov.au/legal-obligations/legislative

Codes of Practice NSW: https://www.safework.nsw.gov.au/resource-library/lis codes-oi ractive

#### **Northern Territory**

Work Health and Safety (National Uniform Legislation) Act 2011

Work Health and Safety (National Uniform Legislation) Regulation 201

Legislation NT: https://worksafe.nt.gov.au/laws-and-compliance/wo\_place-

Codes of Practice NT: https://worksafe.nt.gov.au/f

#### South Australia

Work Health and Safety Act 2012 (SA)

Work Health and Safety Regulations 2012 (SA)

Legislation for SA: https://www.safework.sa.gov.au/resources/le\_lation

Codes of Practice for SA: <a href="https://www.safework.sa.gov.au/wor">https://www.safework.sa.gov.au/wor</a> aces/codes-of-practice#COPs

#### Tasmania

Work Health and Safety Act 2012

Work Health and Safety (Transitional and Consequential Provisions) Act 2012

Work Health and Safety Regulations 2012

Work Health and Safety (Transitional) Regulations 2012

Legislation for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/acts-and-regulations

Codes of Practice for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/codes-of-practice

Details of permits, licenses or access required by regulatory bodies (add or delete as required):

- Permits from local council
- Authorisation to commence work
- Any required documents.

#### Victoria

Occupational Health al. Safety Act

Occupational Health and affety gulations 2017

Legis on VIC: https://www.wksafe.vic.gov.au/occupational-health-and-safety-act-and-

gulat

des on actice VI autros://www.worksafe.vic.gov.au/compliance-codes-and-codes-practice

#### Western Australia

Work Health and Safety Act 2020

Work Health and Safety Regulations 2022

Legislation Western Australia: https://www.commerce.wa.gov.au/worksafe/legislation

Codes of Practice WA: https://www.commerce.wa.gov.au/worksafe/codes-practice

#### Safe Work Australia Links

Law and Regulation (All States): https://www.safeworkaustralia.gov.au/law-and-regulation Model Codes of Practice: https://www.safeworkaustralia.gov.au/resources-publications/model-codes-of-practice

#### **Model Codes of Practice**

- Managing noise and preventing hearing loss at work
- Confined spaces
- Labelling of workplace hazardous chemicals
- Managing risks of hazardous chemicals in the workplace
- Welding processes
- First aid in the workplace
- Managing the risk of falls at workplaces
- Hazardous manual tasks
- Managing the risk of falls in housing construction
- Managing electrical risks in the workplace
- Demolition work
- Excavation work
- Work health and safety consultation, cooperation and coordination
- Managing the work environment and facilities
- How to manage work health and safety risks
- Managing risks of plant in the workplace
- Construction work





#### SIGNATORIES OF THE SAFE WORK METHOD STATEMENT

The signed and dated personnel listed below have cooperated in the consultation and development of this Safe Work Method Statement which has been approved by the Person/s Conducting a Business or Undertaking (PCBU). In signing this Safe Work Method Statement each individual acknowledges and confirms that they have read this SWMS in full, having raised any questions for items on this Safe Work Method Statement that require clarification, and confirms that they are competent, skilled and knowledgeable for the task assigned to them. Every person acknowledges that they have received the relevant training and qualifications where required, before carrying out any work contained in this Safe Work Method Statement. By signing this Safe Work Method Statement each individual agrees to work safely, to follow any safe work instructions which are provided, and agrees to use all Personal Protective Equipment where appropriate.

Worker Name	Signature	Date

#### SAFE WORK IN THE STATEMENT MONITORING AND REVIEW

The SWMS must be reviewed regularly to make sure it remains a fective of must be reviewed (and revised if necessary) if relevant control measures are revised. The view process should be carried out in consultation with workers (including contractors of the SWMS and their health and safety representatives who represented that work group at the workplace.

When the SWMS has been revised the PCBU mast ensure that advised that a revision has been made and how they can access the revised SWMS, including all persons who will need to change a work procedure or system as a rest of the review are advised of the changes in a way that will enable them to implement their duties and the involved in the work must be provided with the relevant information and instruction that will assist them to understand and implement the revised SWMS.

The SWMS must be monitored regularly for the effectiveness of ensuring hazard controls are effective in reducing the risk of incidents, keeping the workplace safe for all personnel. The person responsible for monitoring the effectiveness of the Safe Work Method Statement should employ a multi-faceted approach which includes but is not limited to:

- Spot Checks.
- 2. Consultation with workers, contractors and sub-contractors.
- 3. Internal audits on a continual basis.

An approach of continuous improvement, promptly recording inconsistencies or deficiencies, followed up by immediate corrective action and consultation with all relevant personnel ensures that the PCBU is consistently developing ever-improving systems of safe work principles.

REVIEW NUMBER	1	2	3	4	5	6	7
NAME							
INITIALS							
DATE							

Version 2.5 Authorised by Review # Date of Issue: Review Date: 16





### SAFE WORK METHOD STATEMENT REVIEW CHECKLIST

This Safe Work Method Statement Review Checklist is to be followed and used upon initial development of the SWMS to help ensure that all steps have been adequately taken before work commences. Think of this document as an internal audit review checklist before commencing work, and may form part of a Toolbox Talk (safety meeting) and may be used as an opportunity for education and training.

ITEMS WHICH MUST BE INCLUDED IN THE SWMS	COMPLETED	COMMENTS
The company details have been entered, including the project name and address.		
All relevant personnel consulted during the development of the SWMS.		
Name, signature, position and date signed of the person approving the SWMS.		
Specific personnel and qualifications, experience is noted in the SWMS.	7	
Provides a step-by-step process of tasks required to carry out the activity or task.		
Adequate risk assessment of any identified hazards has been completed.		
Foreseeable hazards are identified and documented for each step.		
Any hazards listed in any site risk assessments have been added to the SWMS		
SWMS initial risk (IR) column as well as residual risk (RR) column ppleted.		
Check control measures added to the SWMS are the most effective selectives		
Responsible person is assigned and listed on the property the improvement of measures.		
Permit or licenses requirements specified, sur as Hot Work, Electric Work, Work at Heights etc.		
SWMS identifies plant and equipment to be us		
Details of inspection checks required for any equipment listed noted on the SWMS.		
Describes any mandatory qualifications, experience, and g or skills required to perform the work.		
Applicable personal protective equipment is selected on the SWMS.		
Reflects and documents any legislative references and/or Australian Standards.		
dentifies any hazardous substances used with specific control measures in line with any SDS.		
REVIEWED BY	DATE REVIEWED	
SIGNATURE	DATE COMPLETE	D