



| Demolition SA | FE WORK METHOD STAT | EMENT (SWMS) | |
|--|--|--|-------------------------------------|
| | TASK OR ACTIVITY: Demolition | | |
| Business Name: | | ABN: | SWMS# |
| Business Address: | | | |
| Contact Person: | Phone: | E jil: | |
| | | | |
| THIS SAFE WORK METHOD | STATEMENT IS APPROVED BY | THE PC. OF THE ROJECT | |
| Under the Work Health and Safety Regulation (WHS Regulation), a person conduct the proposed work starts. | cting a business or under the (PC 1) is | required to en that a safe work method s | statement (SWMS) is prepared before |
| Full Name: | | | |
| Signature: | | Title: | Date: |
| Details of the person(s) responsible for ensuring implementation, monitoring a | opliance the VMS a well as review | s and modifications of the SWMS. | |
| Full Name: | | Title: | Phone: |
| ALL PERSONNEL PARTICIPATING IN ANY ACTIVITY ON THIS & VMS IN HAVE THE FOLLOWING COMMUNICATED | NA. 2 OF ALL RELEVANT PERSONNI EVELOPMENT AND APPROVAL OF | EL WHO HAVE BEEN CONSULTED AND COTHIS SWMS | OMMUNICATED TO IN THE |
| Safety meetings or toolbox talks will be sched and in account with a gislative requirements to first identify any site hazards, and then to further take steps to either eliminate or continuous hazard. | | | |
| If an incident or a near miss occurs, all work must ste, anately. Depending on the severity of the incident, a meeting will be called with all workers to amend the SWMS if required. The meeting may also be an educational opportunity. | | | |
| Any changes made to the SWMS after an incident or a near miss must be approved by the Person Conducting Business or Undertaking and communicated to all relevant personnel. | | | |
| The SWMS must be kept and be available for inspection at least until the work is completed. Where a SWMS is revised, all versions should be kept. If a notifiable incident occurs in relation to which the SWMS relates, then the SWMS must be kept for at least two years from the occurrence of the notifiable incident. | | | |





| CLIENT OR PRINCIPAL | CONTRACTOR DETAILS |
|--|---|
| Client: | SCOPE OF WORKS |
| Project Name: | |
| Project Address: | |
| Project Manager: | |
| Contact Phone: | |
| Date SWMS supplied to Project Manager: | |
| ANY HIGH BIOK CONSTRUCTOR | NAME OF THE POLIT |
| ANY HIGH-RISK CONSTRUCTOR | N WC & BEIN C ARIED OUT |
| ☐ involves a risk of a person falling more than 2 meters | is carried out on or near pressurised gas mains or piping |
| ☐ is carried out on a telecommunication tower | carried out on or near chemical, fuel or refrigerant lines |
| ☐ involves demolition of an element of a structure that is load-bearing | \square is carried out on or near energised electrical installations or services |
| ☐ involves demolition of an element related to the physical integral of a functure | ☐ is carried out in an area that may have a contaminated or flammable atmosphere |
| ☐ involves, or is likely to involve, disturbing asb | ☐ involves tilt-up or precast concrete |
| ☐ involves structural alteration or repair that —quires term — v sup —rt to prevent collapse | ☐ is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor |
| ☐ is carried out in or near a confined space | ☐ is carried out in an area of a workplace where there is any movement of powered mobile plant |
| ☐ is carried out in/near a shaft or trench deeper that. tunnel involving use of explosives | ☐ is carried out in areas with artificial extremes of temperature. |
| \square is carried out in or near water or other liquid that involves a risk of drowning. | ☐ involves diving work. |
| ANY HIGH-RISK MACHINER | Y OR EQUIPMENT NEARBY |
| | |
| | |
| | |



| RISK MATRIX | | | | | | | | | | |
|-------------------|--|--------------------|-----------------|------------------|--------------------|----------------|---|--------------------------------|--------------------------------------|--|
| LIKELIHOOD | INSIGNIFICANT | MINOR | MODERATE | MAJOR | CATASTROPHIC | SCORE | ACTION | HEI | RARCHY OF CONTROLS | |
| ALMOST CERTAIN | 3 HIGH | 3 HIGH | 4 ACUTE | 4 ACUTE | 4 ACUTE | SCORE ACTION | | Elimination Remove the hazard. | | |
| LIKELY | 2 MODERATE | 3 HIGH | 3 HIGH | 4 ACUTE | 4 ACUTE | 4A ACUTE | DO NOT PROCE | | Substitution | |
| POSSIBLE | 1 LOW | 2 MODERATE | 3 HIGH | 4 ACUTE | 4 ACUTE | 3H HIGH | Review before work starts. | | Replace the hazard. | |
| UNLIKELY | 1 LOW | 1 LOW | 2 MODERATE | 3 HIGH | 4 ACUTE | 2M MODERATE | Ensure control measures in place. | Isolate | e People from the hazard | |
| RARE | 1 LOW | 1 LOW | 2 MODERATE | 3 HIGH | 3 HIGH | 1L LOW | nitor and | | Engineering Isolate the hazard. | |
| is the second m | rchy of Controls: ost effective metho nging the work is th | d of controlling a | hazard. Enginee | ering by isolati | on is the in ost e | en 'ive, while | rd. Substitution Administrative effective | | Administrative Change the work. PPE | |

| | | | | PERS | | TIVE EQUIPM | | | | | |
|--------------------|--------------------|--------------------|------------------|-------------|--------------|---------------------------------------|----------------------|------------------------|--------------------|-------------------|---------------------------|
| | | Select the app | ropriate PPŁ | abo v uitab | cor the equi | pment used or | the job task | being perforr | ned (if applica | ıble). | |
| FOOT PROTECTION | HAND PROTECTION | HEAD PROTECTION | HEARING ETION | P ECTION | PROTECTION | FACE PROTECTION | HIGH-VIS CLOTHING | PROTECTIVE CLOTHING | FALL PROTECTION | SUN PROTECTION | HAIR/JEWELLERY SECURED |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| Other PPE R | equired: | | | | | | | | | | |
| | Pe | ermit or Licen | ses Requirem | ents | | Mandatory Qualifications and Training | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------|--|-----------------|---|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| 1. Preparation | Falls from ladders, Slips on debris, Tripping over equipment | 2M | Provide comprehensive training for worker on the use of ladders, including appropriate setting up and maintenance, to minimise the risk of falls. Regularly inspect and maintain ladders to entract cert safety and prevent accidents related to faulty equipment. Implement a clean working and policy that require fall drows to be cleared promptly, reducing the risk of slips on debris. Establish desir cared wan rays are storage are for equipment, helping to prevent tripping over equipment a timproving or rall organisation whe work site. Regress works to we presonal processe equipment (PPE), such as non-slip footwear, to minimise the risk of slipping to prevent tripping over equipment and be riers at the demolition site to indicate potentially hazardous areas and direct foot traffic an ayoun danger zones. Encourse oper communication among workers to report any hazardous conditions and swiftly address the storage under risk assessments of the work site to identify any additional hazards that may not have ten initially identified, ensuring all potential risks are addressed and controlled. Enouge strict adherence to safe work practices and procedures through supervision and monitoring, and provide additional training when necessary. Ensure adequate lighting is provided throughout the work site, particularly in areas where there may be trip hazards or poor visibility near ladders and equipment. Develop an emergency response plan, including worker training in first aid and the location of first-aid kits, so that any incidents can be promptly managed to minimise harm to workers. | 1L |
| 2. Site Setup | Hit by moving traffic, Dust inhalation | ЗН | Traffic Management Plan: Develop and implement a traffic management plan specific to the demolition site, ensuring the safe flow of vehicles and pedestrians, including the use of signs and barriers where necessary. Designated Access Points: Establish designated access points for personnel and vehicles entering and exiting the demolition area, minimising the risk of accidental contact with moving traffic. High Visibility Clothing: Ensure all workers wear high visibility clothing or vests while working at the demolition site, improving their visibility to moving traffic. Vehicle Speed Limits: Implement strictly enforced vehicle speed limits in areas where there is pedestrian activity, reducing the likelihood of collision incidents. Vehicle Operators Training: Provide ongoing training for vehicle operators, ensuring they understand risks associated with moving in close proximity to workers, pedestrians, and other vehicles. | 1L |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------------|--------------------------|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | - Dust Suppression Measures: Utilise dust suppression measures such as regular water spraying or misting systems on-site to minimise airborne dust particles. | |
| | | | - Appropriate Respiratory Protection: Supply employees with appropriate respiratory protection equipment (e.g., dust masks or respirators) and ensure protection use and maintenance. | |
| | | | - Regular Health Monitoring: Conduct regular health more ling to track dust exposure and health effects, addressing any issues promptly. | |
| | | | - Weather Monitoring and Adaptation: Monitor was conditions and suspend activities if the wind speed results in poor dust control or creased safety rise or worker | |
| | | | - Demolition Techniques: Employ modern demolition, unques where possible, such as silent demolition, which during the canting duce dust generation when compared to traditional methods. | |
| | | | - On-site War Management: Ensure effective vaste management systems are in place to prevent dust accumulation, cluding or ring or see the best stockpiles or spoil heaps. | |
| | | | - Site a ctions of caining: Include hazards related to moving traffic and dust inhalation in site induct in sining, siliarising workers with necessary controls, and encouraging vigilance. | |
| | | | - Period Review of Catrol Measures: Regularly review the effectiveness of implemented control measure, up using an defining them as necessary based on site-specific conditions or any incidents that avairs during the project. | |
| | | | Obtain the plans and verify the location of all utilities, such as electrical power lines, gas pipelines, ter mains, and sewage systems that may be affected by the demolition. | |
| | | | - Prior to starting work, coordinate with the relevant utility providers to ensure that all utility services are disconnected and documented. | |
| | | | - Secure necessary permits from the local authorities to carry out the safe deactivation and disconnection of utilities within the worksite. | |
| | | | - Before proceeding with any excavation or ground-penetrating activities, use appropriate equipment, such as a cable avoidance tool (CAT) or ground-piercing radar (GPR), to locate and detect buried utilities. | |
| 3. Utilities Deactivation | Electrocution, Gas leaks | 3H | - Assign a competent person to oversee the deactivation of utilities in accordance with the relevant Australian standards, workplace health and safety regulations, and manufacturer's guidelines. | 1L |
| | , | | - Establish a clear communication system, involving hand signals or two-way radios, for team members to communicate safely during the process of deactivating utilities. | |
| | | | - Create a detailed step-by-step plan for deactivating each utility, with shut-off points clearly marked on site drawings or maps. | |
| | | | - Mark out the locations of deactivated utilities with highly visible warning signs, barrier tape, or delineations to prevent accidental damage or activation during the demolition process. | |
| | | | - Isolate and lockout/tagout electrical systems before deactivation, ensuring that only authorised personnel can access and operate them. | |
| | | | - Use personal protective equipment (PPE) such as insulated gloves, safety goggles, and ear protection when working in proximity to live electrical wires or other hazardous utilities. | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------|------------------------|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | - Conduct regular inspections and maintenance on all tools, equipment, and machinery used in the deactivation process to avoid malfunctions and accidents. | |
| | | | - Organise regular toolbox talks and training session to educate workers on the hazards associated with utilities deactivation and the proper control measures to be followed. | |
| | | | - Establish an emergency response plan, it adding first a procedures and evacuation processes, in case of unexpected incidents like electrocution or a leak puring utilities deactivation. | |
| | | | | |
| | | | | |
| 4. Salvage/Rewiring | Cuts, electrical burp | VI | | 1L |
| | 5 | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|--------------------------|-------------------------------|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | | |
| 5. Structural Inspection | Collapse, Exposure o asbestos | 4A | | 2M |
| | | | | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|-----------------------------|---|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | | |
| 6. Fencing/Warning Signs | Intrusion, Accidental | 21 | | 1L |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|----------------------------|---------------------------------------|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| 7. Demolition Equipment | Machinery malfunction, noise exposure | ЗН | | 2M |
| 8. Demolition Process | Flying debris, Unstable structures | 4A | | 3H |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------|--------------------------------------|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | | |
| 9. Waste Removal | Ergonomics, Manual handling injuries | 3H | | 2M |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|----------------------|------------------------------------|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | | |
| 10. Dust Suppression | Silica exposure, Slippery surfaces | 2M | | 1L |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------|-------------------------|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | | |
| 11. Traffic Control | Accidents, Fall hazards | ЗН | | 1L |



| HAZARDS THAT MAY ARISE | INITIAL RISK | | |
|------------------------|-----------------|--|------------------|
| | Non | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | |
| | | | |
| ıres, Sharp objects | 2M | | 1L |
| | | | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------|------------------------|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | NIGR | | NION |
| | | | | |
| | | | | |
| | | | | |



EMERGENCY RESPONSE - CALL 000 FOR EMERGENCIES

Ensure to have an Emergency Management Plan in place as well as adequate numbers of trained first aid staff with easy access to fully stocked first aid kits, rescue equipment, material safety data sheets, adequate access to emergency communication equipment and fire-fighting equipment suitable for all classes of fire and ignition sources.

LEGISLATIVE REFERENCES

RELEVANT LEGISLATION AND CODES OF PRACTICE. DELETE THE LEGISLATIVE REFERENCES. ANY STATE OF AT ARE NOT APPLICABLE.

Queensland & Australian Capital Territory

Work Health and Safety Act 2011

Work Health and Safety Regulations 2011

Legislation QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/work-health-and-safety-laws

Codes of Practice QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/codes-of-practice Legislation ACT: https://www.worksafe.act.gov.au/laws-and-compliance/acts-and-regulations

Codes of Practice ACT: https://www.worksafe.act.gov.au/laws-and-compliance/codes-of-practice

New South Wales

Work Health and Safety Act 2011

Work Health and Safety Regulations 2017

Legislation NSW: https://www.safework.nsw.gov.au/legal-obligations/legislatide

Codes of Practice NSW: https://www.safework.nsw.gov.au/resource-library/lis > odes-oi racti

Northern Territory

Work Health and Safety (National Uniform Legislation) Act 2011

Work Health and Safety (National Uniform Legislation) Regulation 2011

Legislation NT: https://worksafe.nt.gov.au/laws-and-compliance/wo_place-

Codes of Practice NT: https://worksafe.nt.gov.au/f

South Australia

Work Health and Safety Act 2012 (SA)

Work Health and Safety Regulations 2012 (SA)

Legislation for SA: https://www.safework.sa.gov.au/resources/le_lation

Codes of Practice for SA: https://www.safework.sa.gov.au/work_aces/codes-of-practice#COPs

Tasmania

Work Health and Safety Act 2012

Work Health and Safety (Transitional and Consequential Provisions) Act 2012

Work Health and Safety Regulations 2012

Work Health and Safety (Transitional) Regulations 2012

Legislation for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/acts-and-regulations

Codes of Practice for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/codes-of-practice

Details of permits, licenses or access required by regulatory bodies (add or delete as required):

- Permits from local council
- Authorisation to commence work
- Any required documents.

Victoria

Occupational Health al. Safety Act

Occupational Health and affety gulations 2017

Legis on VIC: https://www.wksafe.vic.gov.au/occupational-health-and-safety-act-and-

gulat

des on actice VI autros://www.worksafe.vic.gov.au/compliance-codes-and-codes-practice

Western Australia

Work Health and Safety Act 2020

Work Health and Safety Regulations 2022

Legislation Western Australia: https://www.commerce.wa.gov.au/worksafe/legislation Codes of Practice WA: https://www.commerce.wa.gov.au/worksafe/codes-practice

Safe Work Australia Links

Law and Regulation (All States): https://www.safeworkaustralia.gov.au/law-and-regulation Model Codes of Practice: https://www.safeworkaustralia.gov.au/resources-publications/model-codes-of-practice

Model Codes of Practice

- Managing noise and preventing hearing loss at work
- Confined spaces
- Labelling of workplace hazardous chemicals
- Managing risks of hazardous chemicals in the workplace
- Welding processes
- First aid in the workplace
- Managing the risk of falls at workplaces
- Hazardous manual tasks
- Managing the risk of falls in housing construction
- Managing electrical risks in the workplace
- Demolition work
- Excavation work
- Work health and safety consultation, cooperation and coordination
- Managing the work environment and facilities
- How to manage work health and safety risks
- Managing risks of plant in the workplace
- Construction work





SIGNATORIES OF THE SAFE WORK METHOD STATEMENT

The signed and dated personnel listed below have cooperated in the consultation and development of this Safe Work Method Statement which has been approved by the Person/s Conducting a Business or Undertaking (PCBU). In signing this Safe Work Method Statement each individual acknowledges and confirms that they have read this SWMS in full, having raised any questions for items on this Safe Work Method Statement that require clarification, and confirms that they are competent, skilled and knowledgeable for the task assigned to them. Every person acknowledges that they have received the relevant training and qualifications where required, before carrying out any work contained in this Safe Work Method Statement. By signing this Safe Work Method Statement each individual agrees to work safely, to follow any safe work instructions which are provided, and agrees to use all Personal Protective Equipment where appropriate.

| Worker Name | Signature | Date |
|-------------|-----------|------|
| | | |
| | | |
| | | |
| | | |
| | | |

SAFE WORK IN THE STATEMENT MONITORING AND REVIEW

The SWMS must be reviewed regularly to make sure it remains a fective of must be reviewed (and revised if necessary) if relevant control measures are revised. The view process should be carried out in consultation with workers (including contractors of the SWMS and their health and safety representatives who represented that work group at the workplace.

When the SWMS has been revised the PCBU mast ensure that advised that a revision has been made and how they can access the revised SWMS, including all persons who will need to change a work procedure or system as a rest of the review are advised of the changes in a way that will enable them to implement their duties and the involved in the work must be provided with the relevant information and instruction that will assist them to understand and implement the revised SWMS.

The SWMS must be monitored regularly for the effectiveness of ensuring hazard controls are effective in reducing the risk of incidents, keeping the workplace safe for all personnel. The person responsible for monitoring the effectiveness of the Safe Work Method Statement should employ a multi-faceted approach which includes but is not limited to:

- Spot Checks.
- 2. Consultation with workers, contractors and sub-contractors.
- Internal audits on a continual basis.

An approach of continuous improvement, promptly recording inconsistencies or deficiencies, followed up by immediate corrective action and consultation with all relevant personnel ensures that the PCBU is consistently developing ever-improving systems of safe work principles.

| REVIEW NUMBER | 1 | 2 | 3 | 4 | 5 | 6 | 7 |
|---------------|---|---|---|---|---|---|---|
| NAME | | | | | | | |
| INITIALS | | | | | | | |
| DATE | | | | | | | |





SAFE WORK METHOD STATEMENT REVIEW CHECKLIST

This Safe Work Method Statement Review Checklist is to be followed and used upon initial development of the SWMS to help ensure that all steps have been adequately taken before work commences. Think of this document as an internal audit review checklist before commencing work, and may form part of a Toolbox Talk (safety meeting) and may be used as an opportunity for education and training.

| ITEMS WHICH MUST BE INCLUDED IN THE SWMS | COMPLETED | COMMENTS |
|---|---------------|----------|
| | | • |
| The company details have been entered, including the project name and address. | | |
| All relevant personnel consulted during the development of the SWMS. | | |
| Name, signature, position and date signed of the person approving the SWMS. | | |
| Specific personnel and qualifications, experience is noted in the SWMS. | 7 | |
| Provides a step-by-step process of tasks required to carry out the activity or task. | | |
| Adequate risk assessment of any identified hazards has been completed. | | |
| Foreseeable hazards are identified and documented for each step. | | |
| Any hazards listed in any site risk assessments have been added to the SWMS | | |
| SWMS initial risk (IR) column as well as residual risk (RR) column pleted. | | |
| Check control measures added to the SWMS are the most effective selective. | | |
| Responsible person is assigned and listed on the part the important of measures. | | |
| Permit or licenses requirements specified, sur as Hot Work, Electric Work, Work at Heights etc. | | |
| SWMS identifies plant and equipment to be us | | |
| Details of inspection checks required for any equipment listed at noted on the SWMS. | | |
| Describes any mandatory qualifications, experience, or skills required to perform the work. | | |
| Applicable personal protective equipment is selected on the SWMS. | | |
| Reflects and documents any legislative references and/or Australian Standards. | | |
| Identifies any hazardous substances used with specific control measures in line with any SDS. | | |
| | | |
| REVIEWED BY | DATE REVIEWE | D |
| SIGNATURE | DATE COMPLETE | ED |