



Elevator Installation	SAFE WORK METHOD S	TATEMENT (SWMS)	
TAS	K OR ACTIVITY: Elevator Install	ation	
Business Name:		ABN:	SWMS#
Business Address:			
Contact Person:	Phone:	E ill:	
THIS SAFE WORK METHOD	STATEMENT IS APPROVED BY	THE PCL OF THE ROJECT	
Under the Work Health and Safety Regulation (WHS Regulation), a person conduct the proposed work starts.	cting a business or undo	required to en. that a safe work method s	statement (SWMS) is prepared before
Full Name:			
Signature:		Title:	Date:
Details of the person(s) responsible for ensuring implementation, monitoring	roliance the VMS a vell as review	s and modifications of the SWMS.	
Full Name:		Title:	Phone:
ALL PERSONNEL PARTICIPATING IN ANY ACTIVITY ON THIS 5 MS M HAVE THE FOLLOWING COMMUNICATED	NAL OF ALL RELEVANT PERSONNI EVELOPMENT AND APPROVAL OF	EL WHO HAVE BEEN CONSULTED AND CO THIS SWMS	OMMUNICATED TO IN THE
Safety meetings or toolbox talks will be scheded in accomply with gislative requirements to first identify any site hazards, complying those hazards and then to further take steps to either eliminate or continuous each hazard.			
If an incident or a near miss occurs, all work must sto, quately. Depending on the severity of the incident, a meeting will be called with all workers to amend the SWMS if required. The meeting may also be an educational opportunity.			
Any changes made to the SWMS after an incident or a near miss must be approved by the Person Conducting Business or Undertaking and communicated to all relevant personnel.			
The SWMS must be kept and be available for inspection at least until the work is completed. Where a SWMS is revised, all versions should be kept. If a notifiable incident occurs in relation to which the SWMS relates, then the SWMS must be kept for at least two years from the occurrence of the notifiable incident.			

Version 2.5 Authorised by Review # Date of Issue: Review Date: 1





CLIENT OR PRINCIPAL	CONTRACTOR DETAILS
Client:	SCOPE OF WORKS
Project Name:	
Project Address:	
Project Manager:	
Contact Phone:	
Date SWMS supplied to Project Manager:	
ANY HIGH-RISK CONSTRUCTOR	ON WO K BEIN O KRIED OUT
☐ involves a risk of a person falling more than 2 meters	☐ is carried out on or near pressurised gas mains or piping
☐ is carried out on a telecommunication tower	carried out on or near chemical, fuel or refrigerant lines
☐ involves demolition of an element of a structure that is load-bearing	☐ is carried out on or near energised electrical installations or services
☐ involves demolition of an element related to the physical integral of a functure	☐ is carried out in an area that may have a contaminated or flammable atmosphere
☐ involves, or is likely to involve, disturbing asb	☐ involves tilt-up or precast concrete
☐ involves structural alteration or repair that — quires term — ov sup — rt to prevent collapse	☐ is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor
is carried out in or near a confined space	☐ is carried out in an area of a workplace where there is any movement of powered mobile plant
☐ is carried out in/near a shaft or trench deeper tha tunnel involving use of explosives	☐ is carried out in areas with artificial extremes of temperature.
☐ is carried out in or near water or other liquid that involves a risk of drowning.	☐ involves diving work.
ANY HIGH-RISK MACHINER	RY OR EQUIPMENT NEARBY

Version 2.5 Authorised by Review # Date of Issue: Review Date: 2



RISK MATRIX										
LIKELIHOOD	INSIGNIFICANT	MINOR	MODERATE	MAJOR	CATASTROPHIC	SCOBE	ACTION		HEIRARCHY OF CONTROLS	
ALMOST CERTAIN	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4 ACUTE	SCORE ACTION	SCORE		Elimination Remove the hazard.	
LIKELY	2 MODERATE	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4A ACUTE	DO NOT PROCE		Substitution	
POSSIBLE	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	4 ACUTE	3H HIGH	Review befor work starts.		Replace the hazard.	
UNLIKELY	1 LOW	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	2M MODERATE	Ensure control measures in place.		Isolate People from the hazard	
RARE	1 LOW	1 LOW	2 MODERATE	3 HIGH	3 HIGH	1L LOW	nitor and		Engineering Isolate the hazard.	
is the second m	rchy of Controls: ost effective metho nging the work is th	d of controlling a	hazard. Enginee	ring by isolati		et. 'ive, while	rd. Substitution Administrative effective		Administrative Change the work. PPE	

				PERS		TIVE EQUIPM					
		Select the app	ropriate PPL	abo. ~uitab	ic or the equip	oment used or	the job task	being perform	ned (if applica	able).	
FOOT PROTECTION	HAND PROTECTION	HEAD PROTECTION	ARING STION	F' CTIO	RL PIRATORY PROTECTION	FACE PROTECTION	HIGH-VIS CLOTHING	PROTECTIVE CLOTHING	FALL PROTECTION	SUN PROTECTION	HAIR/JEWELLERY SECURED
Other PPE R	equired:										
	Pe	ermit or Licen	ses Requirem	ents		Mandatory Qualifications and Training					



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			Review builder's construction program, lift scifications and shop drawings before works commence and confirm they match the engineering deciman Austria an Standards requirements	
			• Hold a site-specific induction for all lift installar assonnel covering emergency exits, muster points, first aid locations, exclusion zones and site rules	
	Unclear emergency procedures		Verify all lift installers, electric his, riggers and do ers in current High Risk Work Licences, electrical licences and VOCs returned to it is plant being used.	
	Unqualified personnel		• Request and —ew Safe ork N —od Stater—ts from subcontractors involved in structural, electrical or rigging w—and confirm—terface—ith th—JWMS	
Pre-start planning and	Inadequate subcontractor coordination Incorrect lift design documentation	3H	• Cor' † Dial Labre Y Dig and review service plans where any drilling, coring or pit penetration works are record near the services	2M
induction	Unidentified underground services Inadequate traffic management		Preplace traffic management plan for delivery trucks, crane set-up areas and loading zones, and so mit for incipal contractor approval	
	Manual handling of documentation crates		Schedul high lisk activities such as scaffoldless lift installation and marry-up elevator sections outside per traces movements to reduce congestion	
			Condumpre-start toolbox talk daily to discuss planned tasks, weather, crane operations, work at ights and changes to the workfront	
			Onfirm emergency communication methods (e.g. UHF channel, mobile coverage) and ensure at least one trained first aider is present during lift installation	
			DO NOT commence any elevator installation activities until the principal contractor has issued formal access to the shaft and written confirmation that the structure is ready	
			Install solid barriers or mesh guarding with self-closing, self-latching gates at all elevator landing openings in accordance with AS 1735 and site fall protection procedures	
	Unprotected shaft openings		• Fix warning signage and lockable hasps on landing doors or shaft access gates to prevent unauthorised entry	
	• Trip hazards on landings		• Inspect shaft floors, landings, and pit for debris, protruding reo, loose materials and remove or make safe before commencing work	
Site and shaft preparation	Falling objects into shaft Unstable working surfaces	4A	Provide temporary lighting in shaft and machine room to achieve adequate lux levels for detailed installation and testing tasks	2M
	Inadequate lighting Unisolated electrical services		Verify permanent power supplies to the lift equipment area are isolated and tagged by a licensed electrician before installation works start	
			• Install toeboards or debris netting at shaft openings where there is a risk of tools or materials falling to levels below	
			Confirm lift pit has safe access via fixed ladder or temporary stair access and that pit sump covers are secured	



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS Mark and maintain clear access paths to and around the shaft, keeping them free from hoses, cables and loose packaging DO NOT store materials or waste inside the shaft on the pit unless specifically allowed in the lift manufacturer's method instructions and approprint by the principal contractor	RESIDUAL RISK
Material delivery and handling	Unplanned vehicle movement Crush injury during unloading Overloaded lifting equipment Manual handling strain Falling load from forklift Obstructed access ways	ЗН	Schedule elevator component deliveries due a agrece windows and coordinate with site traffic controller to manage truck movements near the shaft Use forklifts, pallet jacks are tranes with rated verking Lore simits suitable for the heaviest elevator components and verify WLL better each use Inspect slings, chass, seakles of spreader bars prior to use and remove from service any item that is damaged or better an out-of-tree inspection tag. Position exception zones with cones of bearrier tape around unloading areas and prohibit non-essential personal from the friend uring lifting. Use evanical to set (trolleys, dollies, stair climbers) to transport heavy doors, guide rails and machine composition to each and items using proper lifting techniques, keeping the load close to the body and hiding visting overments. Plate of the product of the shaft and machine rawks of the shaft and machine room. The product of the shaft and panels and safety boots with steel caps when moving pallets or crates. DO NOT exceed the rated capacity of forklifts, hoists or temporary platforms when stacking multiple elevator sections or crates.	2M
Install and anchor elevator frame	Structural instability of frame Incorrect anchor placement Dust inhalation from drilling Impact from rotating tools Falling components in shaft Exposure to silica dust	4A		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
Assemble elevator shaft structure	Working at heights Falling objects from height Frame section collapse Pinch points between sections Inadequate tempora	14		2M
Install guide rails	 Falling from shaft edge Dropped rail sections Crush injuries at fixing points Misaligned guide rails Overexertion during lifting 	4A		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
Install elevator car and marry-up sections	Suspension failure during lifting Car movement in shaft Crush zone between conditions Incorrect alignment of sections Overloading term rary holds.	44		2M
Install rope grippers and suspension systems	Rope failure under load Entanglement in moving ropes Incorrect rope tension Uncontrolled car descent Contact with rotating machinery	4A		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
Installation of screw rod lifts	Entanglement with Shear points in drive assembly Overheating of drive n. Collapse due to misalignment Exposure to lubricants	ЗН		I 1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
Scaffoldless lift installation and work at heights	Fall into shaft Fall from temporary platform Platform structural failure Inadequate edge protection Limited egress in emergency	4A		2M
Upgrade or decommission old elevators	Live electrical components Unexpected car movement Asbestos-containing materials Lead-based paint exposure Falling debris during strip-out	4A		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
Electrical installation and control systems	Electric shock from live parts Arc flash during switching Incorrect earthing Fire from overloaded circuits Unexpected motor start	4A		2M
Testing, commissioning and new lift handover	Uncontrolled lift movement Entrapment in doors Failure of safety devices Overloading during tests Public access during commissioning	ЗН		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK



EMERGENCY RESPONSE - CALL 000 FOR EMERGENCIES

Ensure to have an Emergency Management Plan in place as well as adequate numbers of trained first aid staff with easy access to fully stocked first aid kits, rescue equipment, material safety data sheets, adequate access to emergency communication equipment and fire-fighting equipment suitable for all classes of fire and ignition sources.

LEGISLATIVE REFERENCES

RELEVANT LEGISLATION AND CODES OF PRACTICE. DELETE THE LEGISLATIVE REFERENCES. ANY STATE AT ARE NOT APPLICABLE.

Queensland & Australian Capital Territory

Work Health and Safety Act 2011

Work Health and Safety Regulations 2011

Legislation QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/work-health-and-safety-laws Codes of Practice QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/codes-of-practice

Legislation ACT: https://www.worksafe.act.gov.au/laws-and-compliance/acts-and-regulations

Codes of Practice ACT: https://www.worksafe.act.gov.au/laws-and-compliance/codes-of-practice

New South Wales

Work Health and Safety Act 2011

Work Health and Safety Regulations 2025

Legislation NSW: https://www.safework.nsw.gov.au/legal-obligations/legislati

Codes of Practice NSW: https://www.safework.nsw.gov.au/resource-library/lis

Northern Territory

Work Health and Safety (National Uniform Legislation) Act 2011

Work Health and Safety (National Uniform Legislation) Regulation 201

Codes of Practice NT: https://worksafe.nt.gov.au/f

South Australia

Work Health and Safety Act 2012 (SA)

Work Health and Safety Regulations 2012 (SA)

Legislation for SA: https://www.safework.sa.gov.au/resources/le_lation

Codes of Practice for SA: https://www.safework.sa.gov.au/wor/ aces/codes-of-practice#COPs

Tasmania

Work Health and Safety Act 2012

Work Health and Safety (Transitional and Consequential Provisions) Act 2012

Work Health and Safety Regulations 2012

Work Health and Safety (Transitional) Regulations 2012

Legislation for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/acts-and-regulations

Codes of Practice for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/codes-of-practice

Details of permits, licenses or access required by regulatory bodies (add or delete as required):

- Permits from local council
- Authorisation to commence work
- Any required documents.

Victoria

Or pational Health a. Safety Act J4

Occational Health and afety gulations 2017

Legis on VIC: https://www.sksafe.vic.gov.au/occupational-health-and-safety-act-and-

gulat

tes of actice VIC attps://www.worksafe.vic.gov.au/compliance-codes-and-codes-practice

Western Australia

Work Health and Safety Act 2020

Work Health and Safety Regulations 2022

Legislation Western Australia: https://www.commerce.wa.gov.au/worksafe/legislation

Codes of Practice WA: https://www.commerce.wa.gov.au/worksafe/codes-practice

Safe Work Australia Links

Law and Regulation (All States): https://www.safeworkaustralia.gov.au/law-and-regulation Model Codes of Practice: https://www.safeworkaustralia.gov.au/resources-publications/model-codes-of-practice

Model Codes of Practice

- Managing noise and preventing hearing loss at work
- Confined spaces
- Labelling of workplace hazardous chemicals
- Managing risks of hazardous chemicals in the workplace
- Welding processes
- First aid in the workplace
- Managing the risk of falls at workplaces
- Hazardous manual tasks
- Managing the risk of falls in housing construction
- Managing electrical risks in the workplace
- Demolition work
- Excavation work
- Work health and safety consultation, cooperation and coordination
- Managing the work environment and facilities
- How to manage work health and safety risks
- Managing risks of plant in the workplace
- Construction work





SIGNATORIES OF THE SAFE WORK METHOD STATEMENT

The signed and dated personnel listed below have cooperated in the consultation and development of this Safe Work Method Statement which has been approved by the Person/s Conducting a Business or Undertaking (PCBU). In signing this Safe Work Method Statement each individual acknowledges and confirms that they have read this SWMS in full, having raised any questions for items on this Safe Work Method Statement that require clarification, and confirms that they are competent, skilled and knowledgeable for the task assigned to them. Every person acknowledges that they have received the relevant training and qualifications where required, before carrying out any work contained in this Safe Work Method Statement. By signing this Safe Work Method Statement each individual agrees to work safely, to follow any safe work instructions which are provided, and agrees to use all Personal Protective Equipment where appropriate.

Worker Name	Signature

SAFE WORK IN THE STATEMENT MONITORING AND REVIEW

The SWMS must be reviewed regularly to make sure it remains fective of must be reviewed (and revised if necessary) if relevant control measures are rovised. The view respectively should be carried out in consultation with workers (including contractors as a sub-intractors of the SWMS and their health and safety representatives who represented that work group at the workplace.

When the SWMS has been revised the PCBU must ensure that advised that a revision has been made and how they can acces he revised SWMS, including all persons who will need to change a work procedure or system as a region of the review are advised of the changes in a way that will enable them to implement their duties and the revised SWMS. All workers that will be involved in the work must be provided with the relevant information and instruction that will assist them to understand and implement the revised SWMS.

The SWMS must be monitored regularly for the effectiveness of ensuring hazard controls are effective in reducing the risk of incidents, keeping the workplace safe for all personnel. The person responsible for monitoring the effectiveness of the Safe Work Method Statement should employ a multi-faceted approach which includes but is not limited to:

- Spot Checks.
- 2. Consultation with workers, contractors and sub-contractors.
- Internal audits on a continual basis.

An approach of continuous improvement, promptly recording inconsistencies or deficiencies, followed up by immediate corrective action and consultation with all relevant personnel ensures that the PCBU is consistently developing ever-improving systems of safe work principles.

REVIEW NUMBER	1	2	3	4	5	6	7
NAME							
INITIALS							
DATE							

Version 2.5 Authorised by Review # Date of Issue: Review Date: 13





SAFE WORK METHOD STATEMENT REVIEW CHECKLIST

This Safe Work Method Statement Review Checklist is to be followed and used upon initial development of the SWMS to help ensure that all steps have been adequately taken before work commences. Think of this document as an internal audit review checklist before commencing work, and may form part of a Toolbox Talk (safety meeting) and may be used as an opportunity for education and training.

ITEMS WHICH MUST BE INCLUDED IN THE SWMS	COMPLETED	COMMENTS
The company details have been entered, including the project name and address.		
All relevant personnel consulted during the development of the SWMS.		
Name, signature, position and date signed of the person approving the SWMS.		
Specific personnel and qualifications, experience is noted in the SWMS.	7	
Provides a step-by-step process of tasks required to carry out the activity or task.	k	
Adequate risk assessment of any identified hazards has been completed.	\boxtimes	
Foreseeable hazards are identified and documented for each step.	\boxtimes	
Any hazards listed in any site risk assessments have been added to the SWMS		
SWMS initial risk (IR) column as well as residual risk (RR) colum mpleted.	\boxtimes	
Check control measures added to the SWMS are the most effective selections.		
Responsible person is assigned and listed on the part of the important of	\boxtimes	
Permit or licenses requirements specified, sur as Hot Work, Electric Work, Work at Heights etc.	\boxtimes	
SWMS identifies plant and equipment to be use	\boxtimes	
Details of inspection checks required for any equipment listed an onthe SWMS.	\boxtimes	
Describes any mandatory qualifications, experience, use or skills required to perform the work.	\boxtimes	
Applicable personal protective equipment is selected on the SWMS.		
Reflects and documents any legislative references and/or Australian Standards.	\boxtimes	
Identifies any hazardous substances used with specific control measures in line with any SDS.	\boxtimes	
REVIEWED BY	DATE REVIEWED	
SIGNATURE	DATE COMPLETED	