



Excavation Work Over	1.5 SAFE WORK METHO	D STATEMENT (SWMS)	
TASK	OR ACTIVITY: Excavation Work (Over 1.5	
Business Name:		ABN:	SWMS#
Business Address:			
Contact Person:	Phone:	E 111:	
THIS SAFE WORK METHOD	STATEMENT IS APPRO' D BY	THE PCL OF THE ROJECT	
Under the Work Health and Safety Regulation (WHS Regulation), a person conduct the proposed work starts.	cting a business or under o (PC 1) is	required to en that a safe work method s	statement (SWMS) is prepared before
Full Name:			
Signature:	NY	Title:	Date:
Details of the person(s) responsible for ensuring implementation, monitoring	opliance the VMS a vell as review	s and modifications of the SWMS.	
Full Name:		Title:	Phone:
ALL PERSONNEL PARTICIPATING IN ANY ACTIVITY ON THIS MIS MIS MIS MIS MIS MIS MIS MIS MIS M	NA, ¿ OF ALL RELEVANT PERSONNI EVELOPMENT AND APPROVAL OF	EL WHO HAVE BEEN CONSULTED AND CO	OMMUNICATED TO IN THE
Safety meetings or toolbox talks will be sched ed in accomply with gislative requirements to first identify any site hazards, hazards and then to further take steps to either eliminate or continuate hazard.			
If an incident or a near miss occurs, all work must sto, an alately. Depending on the severity of the incident, a meeting will be called with all workers to amend the SWMS if required. The meeting may also be an educational opportunity.			
Any changes made to the SWMS after an incident or a near miss must be approved by the Person Conducting Business or Undertaking and communicated to all relevant personnel.			
The SWMS must be kept and be available for inspection at least until the work is completed. Where a SWMS is revised, all versions should be kept. If a notifiable incident occurs in relation to which the SWMS relates, then the SWMS must be kept for at least two years from the occurrence of the notifiable incident.			

Version 2.5 Authorised by Review # Date of Issue: Review Date: 1





CLIENT OR PRINCIPAL	CONTRACTOR DETAILS
Client:	SCOPE OF WORKS
Project Name:	
Project Address:	
Project Manager:	
Contact Phone:	
Date SWMS supplied to Project Manager:	
ANY HIGH BIOK CONSTRUCTOR	NAME OF THE POLIT
ANY HIGH-RISK CONSTRUCTOR	N WC & BEIN C ARIED OUT
☐ involves a risk of a person falling more than 2 meters	is carried out on or near pressurised gas mains or piping
☐ is carried out on a telecommunication tower	carried out on or near chemical, fuel or refrigerant lines
☐ involves demolition of an element of a structure that is load-bearing	\square is carried out on or near energised electrical installations or services
☐ involves demolition of an element related to the physical integral of a functure	☐ is carried out in an area that may have a contaminated or flammable atmosphere
☐ involves, or is likely to involve, disturbing asb	☐ involves tilt-up or precast concrete
☐ involves structural alteration or repair that —quires term — v sup —rt to prevent collapse	☐ is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor
☐ is carried out in or near a confined space	☐ is carried out in an area of a workplace where there is any movement of powered mobile plant
☐ is carried out in/near a shaft or trench deeper that. tunnel involving use of explosives	☐ is carried out in areas with artificial extremes of temperature.
\square is carried out in or near water or other liquid that involves a risk of drowning.	☐ involves diving work.
ANY HIGH-RISK MACHINER	Y OR EQUIPMENT NEARBY

Version 2.5 Authorised by Review # Date of Issue: Review Date: 2



RISK MATRIX										
LIKELIHOOD	INSIGNIFICANT	MINOR	MODERATE	MAJOR	CATASTROPHIC	SCORE	ACTION	HEI	RARCHY OF CONTROLS	
ALMOST CERTAIN	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4 ACUTE	SCORE	ACTION		Elimination Remove the hazard.	
LIKELY	2 MODERATE	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4A ACUTE	DO NOT PROCE		Substitution	
POSSIBLE	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	4 ACUTE	3H HIGH	Review before work starts.		Replace the hazard.	
UNLIKELY	1 LOW	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	2M MODERATE	Ensure control measures in place.	Isolate	e People from the hazard	
RARE	1 LOW	1 LOW	2 MODERATE	3 HIGH	3 HIGH	1L LOW	nitor and		Engineering Isolate the hazard.	
is the second m	otes on Hierarchy of Controls: Elimination methods are the most effective and preferrence on controls the second most effective method of controlling a hazard. Engineering by isolation is the virtuost entire, while Administrative ontrols by changing the work is the fourth most effective method. PPE (Personal Protective Equament), the least effective									

				PERS		TIVE EQUIPM					
		Select the app	ropriate PPŁ	abo v uitab	cor the equi	pment used or	the job task	being perforr	ned (if applica	ıble).	
FOOT PROTECTION	HAND PROTECTION	HEAD PROTECTION	HEARING ETION	P ECTION	PROTECTION	FACE PROTECTION	HIGH-VIS CLOTHING	PROTECTIVE CLOTHING	FALL PROTECTION	SUN PROTECTION	HAIR/JEWELLERY SECURED
Other PPE R	equired:										
	Pe	ermit or Licen	ses Requirem	ents		Mandatory Qualifications and Training					



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			- Conduct a thorough site assessment before commencing the excavation work, including identifying existing underground services and structure that could be risks during the excavation.	
			- Establish clear and well-defined access point accidents due to limited visibility or tight working aces.	
			- Ensure all workers are informal about the identificable on-site and have received proper training in safe excavation techniques, as a last retaining pote emergency situations.	
			- Regularly upolar and continuities the site across plan as necessary throughout the project to make sure all team embers start informed bout changes to the worksite conditions.	
			- Prove appropriate Proposal Protection Equipment (PPE) to workers, including protective footwear, high-relief close and hard hats, according to the hazard level in the area.	
1. Preparation	Poor site assessment, inaccessible area	2M	- Develop emerging response plan tailored to the specific site conditions, including processes for evacual give kers from the excavation area, and regularly drill and review the plan with employees to ensure a leffer reness	1L
			- enhigh visible barriers and warning signs to clearly demarcate the excavation area, reducing the risk of una sed access and incidents involving pedestrians or other site visitors.	
			xecute proper soil and geotechnical testing to understand the stability of the ground where the expation is being carried out, allowing for the selection of appropriate shoring or other support systems to prevent cave-ins or landslides.	
			- Schedule regular equipment inspections and maintenance for excavators and other heavy machinery used on-site, ensuring they remain in good working condition and don't contribute to any additional hazards.	
			- Implement a system for monitoring weather conditions and adjust work activities accordingly, reducing the chance of poor weather increasing the risk of incidents related to poor visibility or slippery surfaces.	
			- Conduct thorough pre-start inspections for all machinery and equipment to ensure they are in proper working condition, free from any defects or parts that may cause malfunctions.	
			- Implement a preventive maintenance schedule for all equipment used in excavation work, including regular servicing and replacement of worn out components as per the manufacturer's guidelines.	
2. Equipment Check	Faulty machinery, inadequate safety gear	3H	- Ensure that all operators have received adequate training and hold valid licenses for the specific machinery they operate, with refresher courses conducted periodically.	1L
			- Provide workers with appropriate Personal Protective Equipment (PPE), such as hard hats, high visibility vests, safety boots, gloves, and protective eyewear, and ensure they wear them consistently during the work process.	
			- Regularly review and update safe work procedures for equipment operation and report any new hazards or required adjustments to management immediately.	



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			- Periodically inspect the site and surrounding areas for potential hazards, such as overhead powerlines or uneven terrain, which could impact the safe use of machinery during excavations.	
			- Establish no-go zones around excavation work a sub-where only authorised personnel are allowed access, using clear signage and barriers to make an boundaries.	
			- Keep equipment in a clean and organised rate by removing any debris or obstructions that could affect its performance or pose a hazard to workers.	
			- Provide adequate communication devices, such as two-way ractios, for workers to report faults, hazards, or other concerns promptly, wing immediate in evention a rectification.	
			- Develop emergency response than in case of equal to failures, accidents, or unexpected hazardous situations, ensuring the error are ware of the necessary actions and source of first aid resources.	
			- Ensure all avators and Jachine are fitter with reversing alarms or sensors to alert workers in close proximity of the moveme and mining.	
			- Enclaire work report faulty machinery or inadequate safety gear using a hazard reporting system as phasis, a blame-free culture where all concerns are taken seriously and addressed promp	
			- Period cally a few an avaluate the effectiveness of implemented control measures to ensure they main a square prinimising hazards associated with equipment checks and excavation work. Make construct improvements where necessary, based on feedback and lessons learned.	
			ior to work commencement, conduct a thorough geotechnical investigation and soil analysis to assess the tability of the soil and determine if any contaminants are present.	
			Consult with a qualified engineer or geologist to ensure that the excavation design takes into account the identified soil conditions and hazards.	
			- Develop and implement a site-specific safety plan, addressing methods for managing unstable soil and hazardous contaminants.	
			- Identify and clearly mark excavation areas to minimise risk to workers and other personnel on-site.	
	Unatable as il associtione become		- Implement appropriate shoring or benching systems, as advised by an engineer, to stabilise excavation walls and prevent cave-ins caused by unstable soil conditions.	
3. Soil Analysis	Unstable soil conditions, hazardous contaminants	3H	- Install appropriate barriers or containment measures around hazardous contaminants (e.g., contaminated soil) to prevent worker exposure and environmental contamination.	2M
			- Conduct regular inspections of the excavation area and surrounding site for any signs of soil instability or hazardous contaminants, and take appropriate corrective actions, if required (e.g., adjusting shoring or cleaning up spills).	
			- Provide all workers involved in excavation activities with training on safe work practices, hazard recognition, and the proper use of personal protective equipment (PPE) required for their specific tasks.	
			- Ensure that workers operating in close proximity to unstable soil or hazardous contaminants wear suitable PPE, including gloves, safety glasses, face masks, and impermeable clothing.	
			- Establish exclusion zones around excavation areas and unstable soil, limiting access only to authorised personnel who have received relevant safety training.	



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
PECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUA RISK
			- Regularly monitor weather conditions, such as rainfall and high winds, which may contribute to soil instability, and modify work plans accordingly.	
			- Store excavated soil at an appropriate distance for the edge of the excavation to avoid overloading the excavation walls and destabilising the surroup soil.	
			- Properly dispose of contaminated materia, in accordant with local environmental regulations and guidelines, ensuring that a licensed waste displayed actor is utilised.	
			- Ensure ongoing communication among worker and site management regarding any changes to soil conditions, hazardous contain pants, or work processes. This caudes conducting regular toolbox talks and safety meetings to discuss takes and revised contains a surface of the safety meetings.	
Marking Out	Incorrect measure ents and markings	5W		1L
			_	



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
5. Protective Measures	Inadequate shoring, improved barricade	31		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
6. Excavator Operation				
	5			



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
7. Manual Digging	Ergonomic issues, hand tool injuries			1L
8. Utility Identification	Striking buried utilities, miscommunication with utility provider	3Н		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
9. Inspections	Incomplete inspection, overlooked hazards	2M		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
10. Load Transport	Overloading trucks, unstable load	ЗН		l 1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
11. Backfilling	Poor compaction, improper material selection	2M		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
12.Cleanup & Demobilization	Slips, trips & falls,faulty dismantling of barricades	2M		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
				KOK



EMERGENCY RESPONSE – CALL 000 FOR EMERGENCIES

Ensure to have an Emergency Management Plan in place as well as adequate numbers of trained first aid staff with easy access to fully stocked first aid kits, rescue equipment, material safety data sheets, adequate access to emergency communication equipment and fire-fighting equipment suitable for all classes of fire and ignition sources.

LEGISLATIVE REFERENCES

RELEVANT LEGISLATION AND CODES OF PRACTICE. DELETE THE LEGISLATIVE REFERENCES. ANY STATE OF AT ARE NOT APPLICABLE.

Queensland & Australian Capital Territory

Work Health and Safety Act 2011

Work Health and Safety Regulations 2011

 $\textbf{Legislation QLD:} \ \underline{\textbf{https://www.worksafe.qld.gov.au/laws-and-compliance/work-health-and-safety-laws}$

Codes of Practice QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/codes-of-practice Legislation ACT: https://www.worksafe.act.gov.au/laws-and-compliance/acts-and-regulations

Codes of Practice ACT: https://www.worksafe.act.gov.au/laws-and-compliance/codes-of-practice

New South Wales

Work Health and Safety Act 2011

Work Health and Safety Regulations 2017

Legislation NSW: https://www.safework.nsw.gov.au/legal-obligations/legislatide

Codes of Practice NSW: https://www.safework.nsw.gov.au/resource-library/lis > odes-oi racti

Northern Territory

Work Health and Safety (National Uniform Legislation) Act 2011

Work Health and Safety (National Uniform Legislation) Regulation 201

Codes of Practice NT: https://worksafe.nt.gov.au/f

South Australia

Work Health and Safety Act 2012 (SA)

Work Health and Safety Regulations 2012 (SA)

Legislation for SA: https://www.safework.sa.gov.au/resources/le_lation

Codes of Practice for SA: https://www.safework.sa.gov.au/work_aces/codes-of-practice#COPs

Tasmania

Work Health and Safety Act 2012

Work Health and Safety (Transitional and Consequential Provisions) Act 2012

Work Health and Safety Regulations 2012

Work Health and Safety (Transitional) Regulations 2012

Legislation for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/acts-and-regulations

Codes of Practice for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/codes-of-practice

Details of permits, licenses or access required by regulatory bodies (add or delete as required):

- Permits from local council
- Authorisation to commence work
- Any required documents.

Victoria

Occupational Health at Safety Act

Occupational Health and Infety gulations 2017

Legis on VIC: https://www.cksafe.vic.gov.au/occupational-health-and-safety-act-and-

gulat

des on actice VI autros://www.worksafe.vic.gov.au/compliance-codes-and-codes-practice

Western Australia

Work Health and Safety Act 2020

Work Health and Safety Regulations 2022

Legislation Western Australia: https://www.commerce.wa.gov.au/worksafe/legislation

Codes of Practice WA: https://www.commerce.wa.gov.au/worksafe/codes-practice

Safe Work Australia Links

Law and Regulation (All States): https://www.safeworkaustralia.gov.au/law-and-regulation Model Codes of Practice: https://www.safeworkaustralia.gov.au/resources-publications/model-codes-of-practice

Model Codes of Practice

- Managing noise and preventing hearing loss at work
- Confined spaces
- Labelling of workplace hazardous chemicals
- Managing risks of hazardous chemicals in the workplace
- Welding processes
- First aid in the workplace
- Managing the risk of falls at workplaces
- Hazardous manual tasks
- Managing the risk of falls in housing construction
- Managing electrical risks in the workplace
- Demolition work
- Excavation work
- Work health and safety consultation, cooperation and coordination
- Managing the work environment and facilities
- How to manage work health and safety risks
- Managing risks of plant in the workplace
- Construction work





SIGNATORIES OF THE SAFE WORK METHOD STATEMENT

The signed and dated personnel listed below have cooperated in the consultation and development of this Safe Work Method Statement which has been approved by the Person/s Conducting a Business or Undertaking (PCBU). In signing this Safe Work Method Statement each individual acknowledges and confirms that they have read this SWMS in full, having raised any questions for items on this Safe Work Method Statement that require clarification, and confirms that they are competent, skilled and knowledgeable for the task assigned to them. Every person acknowledges that they have received the relevant training and qualifications where required, before carrying out any work contained in this Safe Work Method Statement. By signing this Safe Work Method Statement each individual agrees to work safely, to follow any safe work instructions which are provided, and agrees to use all Personal Protective Equipment where appropriate.

Worker Name	Signature	Date

SAFE WORK IN THE STATEMENT MONITORING AND REVIEW

The SWMS must be reviewed regularly to make sure it remains a fective of must be reviewed (and revised if necessary) if relevant control measures are revised. The view process should be carried out in consultation with workers (including contractors of the SWMS and their health and safety representatives who represented that work group at the workplace.

When the SWMS has been revised the PCBU mast ensure that advised that a revision has been made and how they can access the revised SWMS, including all persons who will need to change a work procedure or system as a rest of the review are advised of the changes in a way that will enable them to implement their duties and the involved in the work must be provided with the relevant information and instruction that will assist them to understand and implement the revised SWMS.

The SWMS must be monitored regularly for the effectiveness of ensuring hazard controls are effective in reducing the risk of incidents, keeping the workplace safe for all personnel. The person responsible for monitoring the effectiveness of the Safe Work Method Statement should employ a multi-faceted approach which includes but is not limited to:

- Spot Checks.
- 2. Consultation with workers, contractors and sub-contractors.
- 3. Internal audits on a continual basis.

An approach of continuous improvement, promptly recording inconsistencies or deficiencies, followed up by immediate corrective action and consultation with all relevant personnel ensures that the PCBU is consistently developing ever-improving systems of safe work principles.

REVIEW NUMBER	1	2	3	4	5	6	7
NAME							
INITIALS							
DATE							

Version 2.5 Authorised by Review # Date of Issue: Review Date: 16





SAFE WORK METHOD STATEMENT REVIEW CHECKLIST

This Safe Work Method Statement Review Checklist is to be followed and used upon initial development of the SWMS to help ensure that all steps have been adequately taken before work commences. Think of this document as an internal audit review checklist before commencing work, and may form part of a Toolbox Talk (safety meeting) and may be used as an opportunity for education and training.

ITEMS WHICH MUST BE INCLUDED IN THE SWMS	COMPLETED	COMMENTS	
The company details have been entered, including the project name and address.			
All relevant personnel consulted during the development of the SWMS.			
Name, signature, position and date signed of the person approving the SWMS.			
Specific personnel and qualifications, experience is noted in the SWMS.	7		
Provides a step-by-step process of tasks required to carry out the activity or task.			
Adequate risk assessment of any identified hazards has been completed.			
Foreseeable hazards are identified and documented for each step.			
Any hazards listed in any site risk assessments have been added to the SWMS			
SWMS initial risk (IR) column as well as residual risk (RR) column mpleted.			
Check control measures added to the SWMS are the most effective selectives			
Responsible person is assigned and listed on the property the improvement of measures.			
Permit or licenses requirements specified, sur as Hot Work, Electric Work, Work at Heights etc.			
SWMS identifies plant and equipment to be us			
Details of inspection checks required for any equipment listed noted on the SWMS.			
Describes any mandatory qualifications, experience, and g or skills required to perform the work.			
Applicable personal protective equipment is selected on the SWMS.			
Reflects and documents any legislative references and/or Australian Standards.			
dentifies any hazardous substances used with specific control measures in line with any SDS.			
REVIEWED BY	DATE REVIEWED		
SIGNATURE	DATE COMPLETED		