



Excavator Use as Cra	ne   SAFE WORK METHOD	STATEMENT (SWMS)	
TASK	OR ACTIVITY: Excavator Use as	Crane	
Business Name:		ABN:	SWMS#
Business Address:			
Contact Person:	Phone:	E 111:	
THE SAFE WORK METHOD	OTATEMENT IO ARREONÉR DV	THE DO LOT THE CONTO	
THIS SAFE WORK METHOD	STATEMENT IS APPRO' D BY	THE PCL OF THE ROJECT	
Under the Work Health and Safety Regulation (WHS Regulation), a person conduct the proposed work starts.	eting a business or under a (PC 1) is	required to en that a safe work method s	statement (SWMS) is prepared before
Full Name:			
Signature:	NY	Title:	Date:
Details of the person(s) responsible for ensuring implementation, monitoring a	poliance the VMS a well as review	s and modifications of the SWMS.	
Full Name:		Title:	Phone:
ALL PERSONNEL PARTICIPATING IN ANY ACTIVITY ON THIS SUMS IN HAVE THE FOLLOWING COMMUNICATED	NAL 2 OF ALL RELEVANT PERSONNE EVELOPMENT AND APPROVAL OF	EL WHO HAVE BEEN CONSULTED AND COTHIS SWMS	OMMUNICATED TO IN THE
Safety meetings or toolbox talks will be sched ed in account with gislative requirements to first identify any site hazards, comparing those hazards and then to further take steps to either eliminate or continuous each hazard.			
If an incident or a near miss occurs, all work must sto, an attely. Depending on the severity of the incident, a meeting will be called with all workers to amend the SWMS if required. The meeting may also be an educational opportunity.			
Any changes made to the SWMS after an incident or a near miss must be approved by the Person Conducting Business or Undertaking and communicated to all relevant personnel.			
The SWMS must be kept and be available for inspection at least until the work is completed. Where a SWMS is revised, all versions should be kept. If a notifiable incident occurs in relation to which the SWMS relates, then the SWMS must be kept for at least two years from the occurrence of the notifiable incident.			

Version 2.5 Authorised by Review # Date of Issue: Review Date: 1





CLIENT OR PRINCIPAL	CONTRACTOR DETAILS
Client:	SCOPE OF WORKS
Project Name:	
Project Address:	
Project Manager:	
Contact Phone:	
Date SWMS supplied to Project Manager:	
ANY HIGH BIOK CONSTRUCTOR	NAME OF THE POLIT
ANY HIGH-RISK CONSTRUCTOR	N WC & BEIN C ARIED OUT
☐ involves a risk of a person falling more than 2 meters	is carried out on or near pressurised gas mains or piping
☐ is carried out on a telecommunication tower	carried out on or near chemical, fuel or refrigerant lines
☐ involves demolition of an element of a structure that is load-bearing	$\square$ is carried out on or near energised electrical installations or services
☐ involves demolition of an element related to the physical integral of a functure	☐ is carried out in an area that may have a contaminated or flammable atmosphere
☐ involves, or is likely to involve, disturbing asb	☐ involves tilt-up or precast concrete
☐ involves structural alteration or repair that —quires term — v sup —rt to prevent collapse	☐ is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor
☐ is carried out in or near a confined space	☐ is carried out in an area of a workplace where there is any movement of powered mobile plant
☐ is carried out in/near a shaft or trench deeper that. tunnel involving use of explosives	☐ is carried out in areas with artificial extremes of temperature.
$\square$ is carried out in or near water or other liquid that involves a risk of drowning.	☐ involves diving work.
ANY HIGH-RISK MACHINER	Y OR EQUIPMENT NEARBY

Version 2.5 Authorised by Review # Date of Issue: Review Date: 2



RISK MATRIX										
LIKELIHOOD	INSIGNIFICANT	MINOR	MODERATE	MAJOR	CATASTROPHIC	SCORE	ACTION	HEI	RARCHY OF CONTROLS	
ALMOST CERTAIN	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4 ACUTE	SCORE	ACTION		Elimination Remove the hazard.	
LIKELY	2 MODERATE	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4A ACUTE	DO NOT PROCE		Substitution	
POSSIBLE	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	4 ACUTE	3H HIGH	Review before work starts.		Replace the hazard.	
UNLIKELY	1 LOW	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	2M MODERATE	Ensure control measures in place.	Isolate	e People from the hazard	
RARE	1 LOW	1 LOW	2 MODERATE	3 HIGH	3 HIGH	1L LOW	nitor and		Engineering Isolate the hazard.	
is the second m	rchy of Controls: ost effective metho nging the work is th	d of controlling a	hazard. Enginee	ering by isolati	on is the in ost e	en 'ive, while	rd. Substitution Administrative effective		Administrative Change the work.  PPE	

				PERS		TIVE EQUIPM					
		Select the app	ropriate PPŁ	abo. auitab	le or the equi	pment used or	the job task	being perforr	ned (if applica	ıble).	
FOOT PROTECTION	HAND PROTECTION	HEAD PROTECTION	HEARING ETION	P ECTION	PROTECTION	FACE PROTECTION	HIGH-VIS CLOTHING	PROTECTIVE CLOTHING	FALL PROTECTION	SUN PROTECTION	HAIR/JEWELLERY SECURED
Other PPE R	Required:										
	Pe	ermit or Licen	ses Requirem	ents		Mandatory Qualifications and Training					



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
1. Preparation	Slips, trips, and falls, Incorrect PPE	2M	<ul> <li>Proper housekeeping: Maintain a clean are organised work area, regularly inspect and remove any obstacles, debris, or tripping hazards to prevent slips and alls.</li> <li>Clearly marked and designated walkways: En provat walkways around the excavation site are clearly marked and designated for padestrians so that here can safely a vigate around the worksite without encountering hazards.</li> <li>Appropriate safety because: Insult safety barriers and a the construction site, such as guardrails or fencing, to restrict wauth and across and reduce the risk of people accidentally entering hazardous work zones under slips or his may becur.</li> <li>Non-slip foots ar: Work a should we suppropriate non-slip safety footwear with a good tread pattern to provide slips or his may becur.</li> <li>Ponsult slips to be even surfaces, wet conditions, or loose material.</li> <li>Pers ta protect of Equipment (PPE) guidelines: Establish clear guidelines on the correct use and maintening of PPE, cluding gloves, eye protection, hard hats, and high-visibility clothing, to ensure that workers re via protex and against potential hazards.</li> <li>agular afety hining: Conduct ongoing safety training for all employees working in excavator open in ensuring they understand the proper lifting procedures and how to avoid hazards while vorking or und the crane.</li> <li>b Safety Analysis (JSA): Conduct a thorough JSA or risk assessment before commencing work, which into des identifying potential hazards and implementing control measures specific to the job tasks.</li> <li>Signage: Use clear, visible signs to alert workers to potential hazards, including slippery surfaces or areas prone to tripping hazards.</li> <li>Toolbox talks: Hold regular toolbox talks for workers to reinforce safe work practices and discuss any new hazards that may have arisen during the course of work.</li> <li>Inspection and maintenance: Implement an inspection and maintenance schedule for all equipment used, including cranes and lifting accessories, to ensure</li></ul>	1L
2. Site assessment	Uneven ground, Overhead obstructions	3Н	<ul> <li>Conduct a thorough site inspection before commencing any tasks, identifying areas with uneven ground and marking them clearly for all workers.</li> <li>Ensure that a competent person is assigned to evaluate the stability and load-carrying capacity of the ground where the excavator will be used as a crane.</li> <li>Implement temporary ground-fixing solutions such as stabilising mats or pads to provide an even surface for the excavator to operate on, helping to minimise the risk of tipping over or unexpected load shifts.</li> <li>Maintain clear communication between the excavator operator and a spotter who has full visibility of overhead obstructions, ensuring constant monitoring during the lifting process.</li> <li>Create an exclusion zone surrounding the work area to keep uninvolved personnel and bystanders at a safe distance, preventing incidents caused by swinging loads or sudden movements of the equipment.</li> </ul>	2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR	
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK	
			- Prioritise the use of alternative lifting equipment, such as mobile cranes, in areas where overhead obstructions are present, lessening the chances of creating contact with power lines or structures.		
			- Develop a detailed plan for lifting operations, according for site-specific hazards and outlining the intended route for load transport to mitigate potential risks posed by obstructions or uneven terrain.		
			- Provide comprehensive training for all inversed personner focusing on proper techniques for operating an excavator as a crane and emphasising the apport of maintaining vigilance when working around hazards like uneven ground and overhead obs		
			- Equip the excavator with profinity warning devictor sense to alert the operator to nearby obstructions, offering increase situational awarene care comoting safer operation.		
			- Coordinate with the composition assess the feasibility of temporarily de-energising power lines in the work area or requiring electricity to luce the proof contact with overhead cables.		
			- Establish class and concile signals in a municating with the excavator operator during lifting operators, ensuing the changes in we conditions, like the sudden appearance of overhead obstructions or grown softening, can be promptly acted upon.		
			- Imple en routing spection and maintenance schedule for the excavator and its attachments to ensure concents main in good working condition, minimising the chance of equipment failure that sould let to heardous situations on-site.		
	1	\	Concernally pre-start inspections of the excavator, checking for any visible defects, damages to draulic toses, loose parts, or other issues that may compromise the equipment's integrity.		
			- In lement a regular maintenance schedule for the excavator to ensure all parts are in good working condition, and replace any damaged or worn components promptly.		
			- Ensure all operators are comprehensively trained and competent in conducting visual inspections and identifying potential hazards in accordance with manufacturer guidelines.		
			- Verify that the appropriate load charts and lifting capacities are available for the specific excavator model and task, and cross-reference them with the proposed loads to lift.		
				- Provide clear instructions near the operator cab specifying stringent requirements for inspecting attachment points, quick couplers, and lifting accessories such as chains and slings prior to each use.	
. Excavator inspection	Faulty equipment, Loose parts	3H	- Incorporate a system for reporting faulty equipment or identified hazards immediately upon discovery, ensuring timely maintenance or repair by qualified personnel.	1L	
			- Prohibit any modifications or alterations to the excavator without written approval from the manufacturer, maintaining the equipment's original design as much as possible.		
			- Utilise external inspection services, if necessary, to conduct detailed technical assessments or non- destructive testing of critical components, ensuring their reliability when lifting loads.		
			- Implement a lockout/tagout system to prevent unauthorised use of any faulty or compromised excavators, limiting risk exposure during critical operations.		
			<ul> <li>Regularly update workers on the latest safety practices, regulations, and industry standards regarding excavator use as a crane, promoting continual improvement in the identification and mitigation of associated hazards.</li> </ul>		



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUA RISK
			- Encourage open communication between operators, supervisors, and workplace health and safety personnel, fostering a strong safety culture and proactively addressing concerns related to this work step and relevant hazards.	
			- Periodically review and reassess the risks as thated with excavator use as a crane, making necessary adjustments to control measures to accomplicate changes in technology, processes, or workplace requirements.	
. Setting up exclusion one	Unauthorised access voving vehicles			1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
5. Positioning excavator	Ground instability, Collina with object	21		1L
				I



8

JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
6. Attaching lifting gear	Falling objects, Struck by a wing load	34		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
7. Lifting load	Load collapse, Lifting above the rated capacity	4A		3H



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
				•
8. Load transportation	Load swing, Obstacles in travel path	ЗН		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
9. Load placement	Incorrect placement, Crush hazards	2M		1L
10. Detaching lifting gear	Caught in-between, Falling objects	2M		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
11. Restoring excavator to original configuration	Pinch points, Inadequate securing	ЗН		1 1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
12. Work area/site clean-up	Protruding materials, Equipment left in place	2M		1L



HAZARDS THAT MAY ARISE	INITIAL		
	RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUA RISK
			i



#### **EMERGENCY RESPONSE - CALL 000 FOR EMERGENCIES**

Ensure to have an Emergency Management Plan in place as well as adequate numbers of trained first aid staff with easy access to fully stocked first aid kits, rescue equipment, material safety data sheets, adequate access to emergency communication equipment and fire-fighting equipment suitable for all classes of fire and ignition sources.

#### LEGISLATIVE REFERENCES

RELEVANT LEGISLATION AND CODES OF PRACTICE. DELETE THE LEGISLATIVE REFERENCES. ANY STATE OF AT ARE NOT APPLICABLE.

#### **Queensland & Australian Capital Territory**

Work Health and Safety Act 2011

Work Health and Safety Regulations 2011

Legislation QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/work-health-and-safety-laws Codes of Practice QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/codes-of-practice

Legislation ACT: https://www.worksafe.act.gov.au/laws-and-compliance/acts-and-regulations

Codes of Practice ACT: https://www.worksafe.act.gov.au/laws-and-compliance/codes-of-practice

#### **New South Wales**

Work Health and Safety Act 2011

Work Health and Safety Regulations 2017

Legislation NSW: https://www.safework.nsw.gov.au/legal-obligations/legislatide

Codes of Practice NSW: https://www.safework.nsw.gov.au/resource-library/lis

#### **Northern Territory**

Work Health and Safety (National Uniform Legislation) Act 2011

Work Health and Safety (National Uniform Legislation) Regulation 2011

Codes of Practice NT: https://worksafe.nt.gov.au/f

#### South Australia

Work Health and Safety Act 2012 (SA)

Work Health and Safety Regulations 2012 (SA)

Legislation for SA: https://www.safework.sa.gov.au/resources/le

Codes of Practice for SA: https://www.safework.sa.gov.au/work\_aces/codes-of-practice#COPs

#### Tasmania

Work Health and Safety Act 2012

Work Health and Safety (Transitional and Consequential Provisions) Act 2012

Work Health and Safety Regulations 2012

Work Health and Safety (Transitional) Regulations 2012

Legislation for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/acts-and-regulations

Codes of Practice for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/codes-of-practice

Details of permits, licenses or access required by regulatory bodies (add or delete as required):

- Permits from local council
- Authorisation to commence work
- Any required documents.

#### Victoria

Occupational Health al. Safety Act

Occupational Health and affety gulations 2017

Legis on VIC: https://www.ssafe.vic.gov.au/occupational-health-and-safety-act-and-

gulat

des on actice VI autros://www.worksafe.vic.gov.au/compliance-codes-and-codes-practice

#### Western Australia

Work Health and Safety Act 2020

Work Health and Safety Regulations 2022

Legislation Western Australia: https://www.commerce.wa.gov.au/worksafe/legislation

Codes of Practice WA: https://www.commerce.wa.gov.au/worksafe/codes-practice

#### Safe Work Australia Links

Law and Regulation (All States): https://www.safeworkaustralia.gov.au/law-and-regulation Model Codes of Practice: https://www.safeworkaustralia.gov.au/resources-publications/model-codes-of-practice

#### **Model Codes of Practice**

- Managing noise and preventing hearing loss at work
- Confined spaces
- Labelling of workplace hazardous chemicals
- Managing risks of hazardous chemicals in the workplace
- Welding processes
- First aid in the workplace
- Managing the risk of falls at workplaces
- Hazardous manual tasks
- Managing the risk of falls in housing construction
- Managing electrical risks in the workplace
- Demolition work
- Excavation work
- Work health and safety consultation, cooperation and coordination
- Managing the work environment and facilities
- How to manage work health and safety risks
- Managing risks of plant in the workplace
- Construction work





#### SIGNATORIES OF THE SAFE WORK METHOD STATEMENT

The signed and dated personnel listed below have cooperated in the consultation and development of this Safe Work Method Statement which has been approved by the Person/s Conducting a Business or Undertaking (PCBU). In signing this Safe Work Method Statement each individual acknowledges and confirms that they have read this SWMS in full, having raised any questions for items on this Safe Work Method Statement that require clarification, and confirms that they are competent, skilled and knowledgeable for the task assigned to them. Every person acknowledges that they have received the relevant training and qualifications where required, before carrying out any work contained in this Safe Work Method Statement. By signing this Safe Work Method Statement each individual agrees to work safely, to follow any safe work instructions which are provided, and agrees to use all Personal Protective Equipment where appropriate.

Worker Name	Signature	Date

#### SAFE WORK IN THE STATEMENT MONITORING AND REVIEW

The SWMS must be reviewed regularly to make sure it remains a fective of must be reviewed (and revised if necessary) if relevant control measures are revised. The view process should be carried out in consultation with workers (including contractors as support ractors of the SWMS and their health and safety representatives who represented that work group at the workplace.

When the SWMS has been revised the PCBU mast ensure that advised that a revision has been made and how they can access the revised SWMS, including all persons who will need to change a work procedure or system as a rest of the review are advised of the changes in a way that will enable them to implement their duties and the involved in the work must be provided with the relevant information and instruction that will assist them to understand and implement the revised SWMS.

The SWMS must be monitored regularly for the effectiveness of ensuring hazard controls are effective in reducing the risk of incidents, keeping the workplace safe for all personnel. The person responsible for monitoring the effectiveness of the Safe Work Method Statement should employ a multi-faceted approach which includes but is not limited to:

- Spot Checks.
- 2. Consultation with workers, contractors and sub-contractors.
- 3. Internal audits on a continual basis.

An approach of continuous improvement, promptly recording inconsistencies or deficiencies, followed up by immediate corrective action and consultation with all relevant personnel ensures that the PCBU is consistently developing ever-improving systems of safe work principles.

REVIEW NUMBER	1	2	3	4	5	6	7
NAME							
INITIALS							
DATE							

Version 2.5 Authorised by Review # Date of Issue: Review Date: 16





### SAFE WORK METHOD STATEMENT REVIEW CHECKLIST

This Safe Work Method Statement Review Checklist is to be followed and used upon initial development of the SWMS to help ensure that all steps have been adequately taken before work commences. Think of this document as an internal audit review checklist before commencing work, and may form part of a Toolbox Talk (safety meeting) and may be used as an opportunity for education and training.

ITEMS WHICH MUST BE INCLUDED IN THE SWMS	COMPLETED	COMMENTS
The company details have been entered, including the project name and address.		
All relevant personnel consulted during the development of the SWMS.		
Name, signature, position and date signed of the person approving the SWMS.		
Specific personnel and qualifications, experience is noted in the SWMS.	7	
Provides a step-by-step process of tasks required to carry out the activity or task.		
Adequate risk assessment of any identified hazards has been completed.		
Foreseeable hazards are identified and documented for each step.		
Any hazards listed in any site risk assessments have been added to the SWMS		
SWMS initial risk (IR) column as well as residual risk (RR) column ppleted.		
Check control measures added to the SWMS are the most effective selectives		
Responsible person is assigned and listed on the property the improvement of measures.		
Permit or licenses requirements specified, sur as Hot Work, Electric Work, Work at Heights etc.		
SWMS identifies plant and equipment to be us		
Details of inspection checks required for any equipment listed noted on the SWMS.		
Describes any mandatory qualifications, experience, and g or skills required to perform the work.		
Applicable personal protective equipment is selected on the SWMS.		
Reflects and documents any legislative references and/or Australian Standards.		
dentifies any hazardous substances used with specific control measures in line with any SDS.		
REVIEWED BY	DATE REVIEWED	
SIGNATURE	DATE COMPLETE	D