



Hydraulic Cylinder Bench Nu	t Cracker SAFE WORK M	ETHOD STATEMENT (SWMS)
TASK OR AC	TIVITY: Hydraulic Cylinder Benc	h Nut Cracker	
Business Name:		ABN:	SWMS#
Business Address:			
Contact Person:	Phone:	E 111:	
THIS SAFE WORK METHOD	STATEMENT IS APPROX O BY	THE PC. OF THE ROJECT	
Under the Work Health and Safety Regulation (WHS Regulation), a person conduct the proposed work starts.	eting a business or under or (PC 1) is	required to en that a safe work method s	statement (SWMS) is prepared before
Full Name:			
Signature:	NY	Title:	Date:
Details of the person(s) responsible for ensuring implementation, monitoring	apliance the VMS a well as review	s and modifications of the SWMS.	
Full Name:		Title:	Phone:
ALL PERSONNEL PARTICIPATING IN ANY ACTIVITY ON THIS : VMS IV HAVE THE FOLLOWING COMMUNICATED	NAL 2 OF ALL RELEVANT PERSONNE EVELOPMENT AND APPROVAL OF	EL WHO HAVE BEEN CONSULTED AND COTHIS SWMS	OMMUNICATED TO IN THE
Safety meetings or toolbox talks will be sched ed in account with gislative requirements to first identify any site hazards, comparing those hazards and then to further take steps to either eliminate or continuous each hazard.			
If an incident or a near miss occurs, all work must sto, adately. Depending on the severity of the incident, a meeting will be called with all workers to amend the SWMS if required. The meeting may also be an educational opportunity.			
Any changes made to the SWMS after an incident or a near miss must be approved by the Person Conducting Business or Undertaking and communicated to all relevant personnel.			
The SWMS must be kept and be available for inspection at least until the work is completed. Where a SWMS is revised, all versions should be kept. If a notifiable incident occurs in relation to which the SWMS relates, then the SWMS must be kept for at least two years from the occurrence of the notifiable incident.			

Version 2.5 Authorised by Review # Date of Issue: Review Date: 1





CLIENT OR PRINCIPAL	CONTRACTOR DETAILS
Client:	SCOPE OF WORKS
Project Name:	
Project Address:	
Project Manager:	
Contact Phone:	
Date SWMS supplied to Project Manager:	
ANY HIGH BIOK CONSTRUCTOR	NAME OF THE POLIT
ANY HIGH-RISK CONSTRUCTOR	N WC & BEIN C ARIED OUT
☐ involves a risk of a person falling more than 2 meters	is carried out on or near pressurised gas mains or piping
☐ is carried out on a telecommunication tower	carried out on or near chemical, fuel or refrigerant lines
☐ involves demolition of an element of a structure that is load-bearing	\square is carried out on or near energised electrical installations or services
☐ involves demolition of an element related to the physical integral of a functure	☐ is carried out in an area that may have a contaminated or flammable atmosphere
☐ involves, or is likely to involve, disturbing asb	☐ involves tilt-up or precast concrete
☐ involves structural alteration or repair that —quires term — v sup —rt to prevent collapse	☐ is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor
☐ is carried out in or near a confined space	☐ is carried out in an area of a workplace where there is any movement of powered mobile plant
☐ is carried out in/near a shaft or trench deeper that. tunnel involving use of explosives	☐ is carried out in areas with artificial extremes of temperature.
\square is carried out in or near water or other liquid that involves a risk of drowning.	☐ involves diving work.
ANY HIGH-RISK MACHINER	Y OR EQUIPMENT NEARBY

Version 2.5 Authorised by Review # Date of Issue: Review Date: 2



RISK MATRIX										
LIKELIHOOD	INSIGNIFICANT	MINOR	MODERATE	MAJOR	CATASTROPHIC	SCORE	ACTION	HEI	RARCHY OF CONTROLS	
ALMOST CERTAIN	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4 ACUTE	SCORE ACTION	SCORE ACTION		Elimination Remove the hazard.	
LIKELY	2 MODERATE	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4A ACUTE	DO NOT PROCE		Substitution	
POSSIBLE	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	4 ACUTE	3H HIGH	Review before work starts.		Replace the hazard.	
UNLIKELY	1 LOW	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	2M MODERATE	Ensure control measures in place.	Isolate	e People from the hazard	
RARE	1 LOW	1 LOW	2 MODERATE	3 HIGH	3 HIGH	1L LOW	nitor and		Engineering Isolate the hazard.	
is the second m	Administrative Otes on Hierarchy of Controls: Elimination methods are the most effective and preferrence on the second most effective method of controlling a hazard. Engineering by isolation is the life toost entitive, while Administrative controls by changing the work is the fourth most effective method. PPE (Personal Protective Equament), the least effective									

				PERS		TIVE EQUIPM					
		Select the app	ropriate PPŁ	abo v uitab	cor the equi	pment used or	the job task	being perforr	ned (if applica	ıble).	
FOOT PROTECTION	HAND PROTECTION	HEAD PROTECTION	HEARING ETION	P ECTION	PROTECTION	FACE PROTECTION	HIGH-VIS CLOTHING	PROTECTIVE CLOTHING	FALL PROTECTION	SUN PROTECTION	HAIR/JEWELLERY SECURED
Other PPE R	equired:										
	Pe	ermit or Licen	ses Requirem	ents		Mandatory Qualifications and Training					



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
1. Preparation	Slips and trips, Manual handling injuries	2M	 Ensure that the work area is clean, free from any obstructions or debris, and has adequate lighting to minimise the risk of slips and trips. Place appropriate signage to clearly warn interactions of potential hazards in the workspace or use safety barriers if necessary. Employ proper housekeeping ractices such as reminely caning up spills or removing excess materials to maintain a clutter-from notion cent. Utilise anti-slip dats or fluoring whose possible of provide effective grip and reduce slipping risks. Store tools and equipment properly in the materials areas when not in use to avoid creating tripping hazar. Provide apper the ring on safe lifting techniques and manual handling procedures for workers involved in hear lifting tasks. Use micharchil lift area or equipment (e.g., hydraulic pallet jacks, trolleys) to minimise manual handling tasks who lever in saible. Envirace workers to seek assistance from their colleagues when lifting or moving heavy or awkward hads. In courage regular stretching and breaks between tasks to allow muscles to recover and prevent strucking or overuse injuries. Conduct a thorough pre-operation inspection of hydraulic cylinder bench and nut cracker, ensuring they are in good working order, safe to use, and compliant with safety regulations. Establish clear communication channels (e.g., hand signals, walkie-talkies) among workers to coordinate lifting and transportation activities effectively and prevent accidents due to miscommunication. By implementing these control measures, the risks associated with slip/trip incidents and manual handling injuries can be significantly reduced within this work step, promoting a safer work environment overall. 	1L
2. Equipment Inspection	Falls from height, Pinch points	ЗН	 Make sure all workers are trained and competent in the required tasks, including equipment inspection and working with hydraulic cylinder bench – nut cracker. Ensure that pre-start inspections are conducted for all equipment before each use. This includes checking for any leaks, damage or deterioration of the hydraulic cylinder bench, as well as ensuring that all protective guards are in place. Conduct a thorough risk assessment before starting any work to identify potential hazards and outline appropriate control measures. Utilise appropriate fall protection and restraint systems when accessing heights, such as guardrails or harnesses. Ensure workers are trained on the correct use and maintenance of these systems. Implement a buddy system during any work involving pinch points or heights, with one worker spotting another to reduce the risk of accidents. 	1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			- Ensure proper housekeeping practices are in place, including keeping walkways clear, promptly addressing any spills or leaks, and maintaining adequate lighting in the work area.	
			- Use signage, barrier tape, or cones to designate ardous areas or exclusion zones around pinch point hazards.	
			- Regularly inspect and maintain the hydracy cylinder both according to the manufacturer's recommendations, ensuring any worn or danged powers promptly replaced.	
			- Consider implementing a permit-to-work system of high-risk activities, which requires formal authorization before work be s.	
			- Encourage open communication among workers to the they feel comfortable reporting any hazards, near-misses, or in the thought of reprisal.	
			- Establish a mergency reponse in n, including procedures for evacuation, first aid, and contacting emergency selected, and all work and expense procedures.	
			- Alwayse approprie hand tools and additional safety equipment, such as never using hands to stop or guild be still be stop or guild be stop of the st	
			Involve work in one ng safety reviews and toolbox talks, so they are consistently aware of the safety suirements an ean contribute to improvements in workplace health and safety practices.	
	7		Condust pre-start inspection of the hydraulic cylinder bench to ensure all components are in proper tking condition, with no signs of wear or damage.	
			- Ensure sufficient space is available around the work area, with clear access maintained to avoid any slip, trip, or fall hazards during cylinder installation.	
			- Provide adequate training and competency checks for all operatives involved in the cylinder installation process, with specific emphasis on handling heavy loads and operating the hydraulic equipment safely.	
			- Utilise appropriate personal protective equipment (PPE) such as safety gloves, safety glasses, steel-toed boots, and hearing protection as required.	
Cylinder Installation	Crushing injuries, High pressure release	4A	- Assess the need for additional mechanical lifting aids or equipment, such as hoists or overhead cranes, to assist in the installation of heavy cylinders and reduce the risk of crush injuries.	2M
3. Cylinder installation	Crushing injuries, High pressure release	4A	- Establish a designated exclusion zone around the hydraulic bench during installation, with visible barriers and signage in place to prevent unauthorised personnel from entering the area.	ZIVI
			- Institute a permit-to-work system or similar procedure to formalize communication between maintenance, production, and management teams, minimising the risk of tasks being carried out simultaneously.	
			- Implement a step-by-step 'Installation Procedure' that all operatives must follow, along with visual reminders at the workstation as necessary.	
			- Develop a strategy for safely managing high-pressure releases during the installation process, including isolation and pressure relief protocols as well as regular testing/checking of connections.	
			- Utilise manufacturer-provided technical information and recommended installation procedures whenever possible to ensure reliability and safety.	



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			- Carry out regular inspections and audits of the hydraulic cylinder installation area to identify any potential hazards or deviations from safe working practices promptly and take corrective action as needed.	
			- Perform routine maintenance on hydraulic equipment and tools according to the manufacturer's guidelines, with thorough inspections and time placement of parts subject to wear or degradation.	
			- Encourage a workplace culture focused of afety, open mmunication, and continuous improvement, where all employees are empowered to report once and contribute to hazard identification and risk reduction efforts.	
			- Ensure proper incident investigation, documentating, and for w-up in the event of an accident or nearmiss related to hydraulic cylind installation to prevent researce and support ongoing safety improvements.	
	•			
4. Workspace Setup	Trip hazards, Inade	₽M		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
5. Hydraulic Pump Assembly	Leaks, Electrical hazarus	2M		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
				•
6. System Pressurization	High pressure release, Hose vallures	эH		2M
				I



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
7. Nut Cracking Process	Flying debris, Noise exp	31		



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
8. System Depressurization	Uncontrolled depressurization, Residual energy	ЗН		2M
9. Cylinder Removal	Crushing injuries, Manual handling injuries	2M		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
				1
	5			
10. Housekeeping and Cleaning	Slips and trips, Hazardous materials exposure	2M		I 1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
11. Equipment Maintenance	Pinch points, Confined spaces	ЗН		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
12. Tool Storage and Transport	Manual handling injuries, Safety	2M		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK



EMERGENCY RESPONSE - CALL 000 FOR EMERGENCIES

Ensure to have an Emergency Management Plan in place as well as adequate numbers of trained first aid staff with easy access to fully stocked first aid kits, rescue equipment, material safety data sheets, adequate access to emergency communication equipment and fire-fighting equipment suitable for all classes of fire and ignition sources.

LEGISLATIVE REFERENCES

RELEVANT LEGISLATION AND CODES OF PRACTICE. DELETE THE LEGISLATIVE REFERENCES. ANY STATE OF AT ARE NOT APPLICABLE.

Queensland & Australian Capital Territory

Work Health and Safety Act 2011

Work Health and Safety Regulations 2011

Legislation QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/work-health-and-safety-laws

Codes of Practice QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/codes-of-practice Legislation ACT: https://www.worksafe.act.gov.au/laws-and-compliance/acts-and-regulations

Codes of Practice ACT: https://www.worksafe.act.gov.au/laws-and-compliance/codes-of-practice

New South Wales

Work Health and Safety Act 2011

Work Health and Safety Regulations 2017

Legislation NSW: https://www.safework.nsw.gov.au/legal-obligations/legislati

Codes of Practice NSW: https://www.safework.nsw.gov.au/resource-library/lis codes-of ractions of Practice NSW: https://www.safework.nsw.gov.au/resource-library/lis codes-of-ractions-of-racti

Northern Territory

Work Health and Safety (National Uniform Legislation) Act 2011

Work Health and Safety (National Uniform Legislation) Regulation 201

Legislation NT: https://worksafe.nt.gov.au/laws-and-compliance/wo_place-

Codes of Practice NT: https://worksafe.nt.gov.au/f

South Australia

Work Health and Safety Act 2012 (SA)

Work Health and Safety Regulations 2012 (SA)

Legislation for SA: https://www.safework.sa.gov.au/resources/le_lation

Codes of Practice for SA: https://www.safework.sa.gov.au/wor aces/codes-of-practice#COPs

Tasmania

Work Health and Safety Act 2012

Work Health and Safety (Transitional and Consequential Provisions) Act 2012

Work Health and Safety Regulations 2012

Work Health and Safety (Transitional) Regulations 2012

Legislation for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/acts-and-regulations

Codes of Practice for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/codes-of-practice

Details of permits, licenses or access required by regulatory bodies (add or delete as required):

- Permits from local council
- Authorisation to commence work
- Any required documents.

Victoria

Occupational Health al. Safety Act

Occupational Health and affety gulations 2017

Legis on VIC: https://www.csafe.vic.gov.au/occupational-health-and-safety-act-and-

gulat

tes of actice VIC attps://www.worksafe.vic.gov.au/compliance-codes-and-codes-practice

Western Australia

Work Health and Safety Act 2020

Work Health and Safety Regulations 2022

Legislation Western Australia: https://www.commerce.wa.gov.au/worksafe/legislation Codes of Practice WA: https://www.commerce.wa.gov.au/worksafe/codes-practice

Safe Work Australia Links

Law and Regulation (All States): https://www.safeworkaustralia.gov.au/law-and-regulation Model Codes of Practice: https://www.safeworkaustralia.gov.au/resources-publications/model-codes-of-practice

Model Codes of Practice

- Managing noise and preventing hearing loss at work
- Confined spaces
- Labelling of workplace hazardous chemicals
- Managing risks of hazardous chemicals in the workplace
- Welding processes
- First aid in the workplace
- Managing the risk of falls at workplaces
- Hazardous manual tasks
- Managing the risk of falls in housing construction
- Managing electrical risks in the workplace
- Demolition work
- Excavation work
- Work health and safety consultation, cooperation and coordination
- Managing the work environment and facilities
- How to manage work health and safety risks
- Managing risks of plant in the workplace
- Construction work





SIGNATORIES OF THE SAFE WORK METHOD STATEMENT

The signed and dated personnel listed below have cooperated in the consultation and development of this Safe Work Method Statement which has been approved by the Person/s Conducting a Business or Undertaking (PCBU). In signing this Safe Work Method Statement each individual acknowledges and confirms that they have read this SWMS in full, having raised any questions for items on this Safe Work Method Statement that require clarification, and confirms that they are competent, skilled and knowledgeable for the task assigned to them. Every person acknowledges that they have received the relevant training and qualifications where required, before carrying out any work contained in this Safe Work Method Statement. By signing this Safe Work Method Statement each individual agrees to work safely, to follow any safe work instructions which are provided, and agrees to use all Personal Protective Equipment where appropriate.

Worker Name	Signature	Date

SAFE WORK IN THE STATEMENT MONITORING AND REVIEW

The SWMS must be reviewed regularly to make sure it remains a fective of must be reviewed (and revised if necessary) if relevant control measures are revised. The view process should be carried out in consultation with workers (including contractors as support ractors of the SWMS and their health and safety representatives who represented that work group at the workplace.

When the SWMS has been revised the PCBU mast ensure that advised that a revision has been made and how they can access the revised SWMS, including all persons who will need to change a work procedure or system as a rest of the review are advised of the changes in a way that will enable them to implement their duties and the involved in the work must be provided with the relevant information and instruction that will assist them to understand and implement the revised SWMS.

The SWMS must be monitored regularly for the effectiveness of ensuring hazard controls are effective in reducing the risk of incidents, keeping the workplace safe for all personnel. The person responsible for monitoring the effectiveness of the Safe Work Method Statement should employ a multi-faceted approach which includes but is not limited to:

- Spot Checks.
- 2. Consultation with workers, contractors and sub-contractors.
- 3. Internal audits on a continual basis.

An approach of continuous improvement, promptly recording inconsistencies or deficiencies, followed up by immediate corrective action and consultation with all relevant personnel ensures that the PCBU is consistently developing ever-improving systems of safe work principles.

REVIEW NUMBER	1	2	3	4	5	6	7
NAME							
INITIALS							
DATE							

Version 2.5 Authorised by Review # Date of Issue: Review Date: 16





SAFE WORK METHOD STATEMENT REVIEW CHECKLIST

This Safe Work Method Statement Review Checklist is to be followed and used upon initial development of the SWMS to help ensure that all steps have been adequately taken before work commences. Think of this document as an internal audit review checklist before commencing work, and may form part of a Toolbox Talk (safety meeting) and may be used as an opportunity for education and training.

ITEMS WHICH MUST BE INCLUDED IN THE SWMS	COMPLETED	COMMENTS
The company details have been entered, including the project name and address.		
All relevant personnel consulted during the development of the SWMS.		
Name, signature, position and date signed of the person approving the SWMS.		
Specific personnel and qualifications, experience is noted in the SWMS.	7	
Provides a step-by-step process of tasks required to carry out the activity or task.		
Adequate risk assessment of any identified hazards has been completed.		
Foreseeable hazards are identified and documented for each step.		
Any hazards listed in any site risk assessments have been added to the SWMS		
SWMS initial risk (IR) column as well as residual risk (RR) column ppleted.		
Check control measures added to the SWMS are the most effective selectives		
Responsible person is assigned and listed on the property the improvement of measures.		
Permit or licenses requirements specified, sur as Hot Work, Electric Work, Work at Heights etc.		
SWMS identifies plant and equipment to be us		
Details of inspection checks required for any equipment listed noted on the SWMS.		
Describes any mandatory qualifications, experience, and g or skills required to perform the work.		
Applicable personal protective equipment is selected on the SWMS.		
Reflects and documents any legislative references and/or Australian Standards.		
dentifies any hazardous substances used with specific control measures in line with any SDS.		
REVIEWED BY	DATE REVIEWED	
SIGNATURE	DATE COMPLETE	D