



Lathe Wood Turning	SAFE WORK METHOD S	STATEMENT (SWMS)	
TAS	K OR ACTIVITY: Lathe Wood Tu	rning	
Business Name:		ABN:	SWMS#
Business Address:			
Contact Person:	Phone:	E fil:	
THIS SAFE WORK METHOD	STATEMENT IS APPROVED BY	THE PCL OF THE ROJECT	
Under the Work Health and Safety Regulation (WHS Regulation), a person conduct the proposed work starts.	eting a business or under o (PC 1) is	required to en that a safe work method s	statement (SWMS) is prepared before
Full Name:			
Signature:		Title:	Date:
Details of the person(s) responsible for ensuring implementation, monitoring	apliance the VMS a vell as review	es and modifications of the SWMS.	
Full Name:		Title:	Phone:
ALL PERSONNEL PARTICIPATING IN ANY ACTIVITY ON THIS S /MS M HAVE THE FOLLOWING COMMUNICATED	NA, 2 OF ALL RELEVANT PERSONNI EVELOPMENT AND APPROVAL OF	EL WHO HAVE BEEN CONSULTED AND CO	OMMUNICATED TO IN THE
Safety meetings or toolbox talks will be sched ed in accomply with gislative requirements to first identify any site hazards, hazards and then to further take steps to either eliminate or continuous each hazard.			
If an incident or a near miss occurs, all work must sto, an atately. Depending on the severity of the incident, a meeting will be called with all workers to amend the SWMS if required. The meeting may also be an educational opportunity.			
Any changes made to the SWMS after an incident or a near miss must be approved by the Person Conducting Business or Undertaking and communicated to all relevant personnel.			
The SWMS must be kept and be available for inspection at least until the work is completed. Where a SWMS is revised, all versions should be kept. If a notifiable incident occurs in relation to which the SWMS relates, then the SWMS must be kept for at least two years from the occurrence of the notifiable incident.			





CLIENT OR PRINCIPAL	CONTRACTOR DETAILS
Client:	SCOPE OF WORKS
Project Name:	
Project Address:	
Project Manager:	
Contact Phone:	
Date SWMS supplied to Project Manager:	
ANY HIGH BIOK CONSTRUCTOR	NAME OF THE POLIT
ANY HIGH-RISK CONSTRUCTOR	N WC & BEIN C ARIED OUT
☐ involves a risk of a person falling more than 2 meters	is carried out on or near pressurised gas mains or piping
☐ is carried out on a telecommunication tower	carried out on or near chemical, fuel or refrigerant lines
☐ involves demolition of an element of a structure that is load-bearing	$\square$ is carried out on or near energised electrical installations or services
☐ involves demolition of an element related to the physical integral of a functure	☐ is carried out in an area that may have a contaminated or flammable atmosphere
☐ involves, or is likely to involve, disturbing asb	☐ involves tilt-up or precast concrete
☐ involves structural alteration or repair that —quires term — v sup —rt to prevent collapse	☐ is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor
☐ is carried out in or near a confined space	☐ is carried out in an area of a workplace where there is any movement of powered mobile plant
☐ is carried out in/near a shaft or trench deeper that. tunnel involving use of explosives	☐ is carried out in areas with artificial extremes of temperature.
$\square$ is carried out in or near water or other liquid that involves a risk of drowning.	☐ involves diving work.
ANY HIGH-RISK MACHINER	Y OR EQUIPMENT NEARBY



RISK MATRIX										
LIKELIHOOD	INSIGNIFICANT	MINOR	MODERATE	MAJOR	CATASTROPHIC	SCORE	ACTION	HEI	RARCHY OF CONTROLS	
ALMOST CERTAIN	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4 ACUTE	SCORE	ACTION		Elimination Remove the hazard.	
LIKELY	2 MODERATE	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4A ACUTE	DO NOT PROCE		Substitution	
POSSIBLE	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	4 ACUTE	3H HIGH	Review before work starts.		Replace the hazard.	
UNLIKELY	1 LOW	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	2M MODERATE	Ensure control measures in place.	Isolate	e People from the hazard	
RARE	1 LOW	1 LOW	2 MODERATE	3 HIGH	3 HIGH	1L LOW	nitor and		Engineering Isolate the hazard.	
is the second m	rchy of Controls: ost effective metho nging the work is th	d of controlling a	hazard. Enginee	ering by isolati	on is the in ost e	en 'ive, while	rd. Substitution Administrative effective		Administrative Change the work.  PPE	

				PERS		TIVE EQUIPM					
		Select the app	ropriate PPŁ	abo v uitab	cor the equi	pment used or	the job task	being perforr	ned (if applica	ıble).	
FOOT PROTECTION	HAND PROTECTION	HEAD PROTECTION	HEARING ETION	P ECTION	PROTECTION	FACE PROTECTION	HIGH-VIS CLOTHING	PROTECTIVE CLOTHING	FALL PROTECTION	SUN PROTECTION	HAIR/JEWELLERY SECURED
Other PPE R	equired:										
	Pe	ermit or Licen	ses Requirem	ents			Ma	andatory Qual	ifications and	Training	



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
1. Preparation	Sharp tools, Slippery surfaces	2M	Equipment inspection and maintenance: Proutarly inspect the sharp tools used in wood turning, such as chisels, gouges, and knives, to ensure they be in good and ition and properly sharpened. Replace any damaged or overly blunt tools.  Proper training and instruction: Ensure all work or using these barp tools and equipment have received adequate training and know to safest techniques or their works of prevent accidental injuries.  Clean work environment Thor whilly clean the work of floor and maintain a dry surface to prevent slips and falls can any very insite of opportunity surfaces. Consider implementing regular cleaning schedules and routines.  Personal procedures and the risk of injury while operating wood-turning machines and handling sharp tools.  Clean group and chard identification: Clearly mark potential hazards in the work area and display signage egan and the received embedding sequences and emergency procedures specific to wood turning machines.  Yorkspiece orgustation: Arrange the workspace to promote clear access to materials and spaces for turn of equiring mats clamps and securing equipment are kept close at hand and that floor space is free from the curring mats: Place anti-slip mats in areas with a higher risk of falling or slipping due to wetness or work as shavings, such as around the wood-turning machine and workbenches.  Tool storage safety: Store sharp tools in dedicated holders or cases when not in use, preventing unnecessary exposure to individuals working in the vicinity.  Emergency safety protocols: Establish and practice emergency safety procedures for incidents related to sharp tools and slippery surfaces. Ensure all staff members know how to access first aid kits and report accidents or near-miss events.  Encourage open communication: Create an open atmosphere where workers can voice concerns or suggestions about potential hazards related to wood turning, helping further refine safety practices and preemptively address any additional risks.  Regular safety audits: Schedule and condu	1L
2. Machine setup	Electrical hazards, Entanglement	3H	<ul> <li>Regular inspection and maintenance of electrical equipment: Ensure that all electrical cords, outlets, and tools are inspected and maintained regularly to detect any faults, damages, or wear.</li> <li>Use of proper protective gear: Mandatory use of safety glasses or a face shield to reduce the risk of eye injuries from flying debris and proper gloves for hand protection during machine setup.</li> <li>In-depth tool training: Provide comprehensive training for employees on the specific wood-turning lathe being used, including safe operating procedures, handling techniques, and entanglement prevention.</li> </ul>	2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			- Ensuring machine guards are in place: Verify that all machine guards, including emergency stop buttons, are functioning correctly and are securely fitted before the operation begins.	
			- Proper workspace planning and layout: Designate clear work area with sufficient lighting and space for easy movement, ensuring there is no clutter property, which could contribute to entanglement risks.	
			- Implement a lockout/tagout system: Deve and enforce trict lockout/tagout procedures to safeguard against unintended machine start-up or energy ation and setup and maintenance tasks.	
			- Emergency shut-off procedures: Establish clear nergency shut-off procedures and ensure all workers are aware of these protocols case of electrical pards or languement incidents.	
			- Work at manageable speeds: courage operators at slower speeds during machine setup and initial phases to missing a risk accidents associated with high-speed rotations.	
			- Proper calculation anagement. Keep power corrected and cables neatly organised and secured to prevent tripping, entail general, or antact with a graph parts during machine setup.	
			- Esta a buo concern: Encourage a culture of teamwork where workers double-check each other's setup in the dheren to safety protocols, reducing the chance of oversights.	
			- Restriction is to a corised personnel only: Limit access to the wood-turning lathe to trained, authorised the connection of the connecti	
			- Concet polbox talks and refresher courses: Regularly review safety protocols and update employees n any conges or improvements to workplace health and safety practices surrounding wood-turning nes.	
	6		Pre-assessment of wood: Before the wood selection, make sure to conduct a thorough assessment to identify any signs of visible cracks, knots, or other imperfections that may increase the risk of splinters or excessive dust during the turning process.	
			- Proper storage and handling: Ensure that wood materials are stored in a clean, dry, and organised environment, with proper stacking methods in place to minimise the risks of accidents or damage to the materials.	
			- Personal Protective Equipment (PPE): Workers should wear appropriate PPE, including safety goggles, gloves, respiratory masks, and long-sleeved clothing to protect against splinters, wood dust, and other potential hazards.	
3. Wood selection	Splinters, Wood dust	2M	- Training and education: Provide ongoing training and education to employees on safe wood handling techniques and best practices for reducing the risks associated with splinters and wood dust exposure.	1L
			- Ventilation and air filtration systems: Install adequate ventilation and air filtration systems to help control the level of airborne wood dust in the work area and minimise inhalation hazards for workers.	
			- Regular cleaning and maintenance: Implement regular cleaning procedures for the workspace, tools, and equipment to help reduce the build-up of wood dust and minimise the risk of splinters during the wood selection process.	
			- Safe lifting techniques: Encourage workers to use proper lifting techniques when handling heavy or large pieces of wood, such as bending at the knees and keeping the back straight, to minimise the risk of injury from splinters or other hazards.	



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			- Selection of appropriate tools: Use suitable cutting and shaping tools, designed specifically for the type of wood being used, to minimise the risk of splinters and help control the generation of wood dust during the turning process.	
			- Waste disposal management: Establish and conce clear guidelines for disposing of waste materials, including how to safely handle and contain unitered or damaged pieces of wood.	
			<ul> <li>Inspection and monitoring: Regularly inspect and monor the work area for any signs of excessive wood splinters or dust, and be proactive in addressing the identified hazards to ensure a safer working environment.</li> <li>Signage and warning system. Display clear and to bless gnage in the workplace to remind workers of</li> </ul>	
			the potential hazarda siated with wood selection, auding the risks posed by splinters and wood dust.  - Encouraging communication and registring a ster a culture of open communication within the workplace, encouraging a kers to represent y concerns related to the handling and selection of wood	
4. Roughing	Flying wood chips, Excessive noise	2M	mate venable the response and risk mitigation strategies to be implemented.	1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
5. Shaping	Vibration, Overheating tools	2M		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
6. Sanding	Dust inhalation, Ey injury	ЗН		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
7. Finishing	Chemical exposure, Fire hazard	2M		11.
8. Quality inspection	Ergonomic stress, Eye strain	1L		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
9. Cleanup	Slips and trips, Chemical spills	2M		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
10. Waste disposal	Manual handling injuries, Environmental hazards	2M		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
11. Maintenance	Equipment malfunction, Unplanned movement of machinery	ЗН		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
				•
				I
12. Storage	Collapse of storage was, buying injuries			1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAI RISK
	5			



#### **EMERGENCY RESPONSE - CALL 000 FOR EMERGENCIES**

Ensure to have an Emergency Management Plan in place as well as adequate numbers of trained first aid staff with easy access to fully stocked first aid kits, rescue equipment, material safety data sheets, adequate access to emergency communication equipment and fire-fighting equipment suitable for all classes of fire and ignition sources.

#### LEGISLATIVE REFERENCES

RELEVANT LEGISLATION AND CODES OF PRACTICE. DELETE THE LEGISLATIVE REFERENCES. ANY STATE OF AT ARE NOT APPLICABLE.

#### **Queensland & Australian Capital Territory**

Work Health and Safety Act 2011

Work Health and Safety Regulations 2011

 $\underline{\textbf{Legislation QLD:}} \ \underline{\textbf{https://www.worksafe.qld.gov.au/laws-and-compliance/work-health-and-safety-laws}}$ 

Codes of Practice QLD: <a href="https://www.worksafe.qld.gov.au/laws-and-compliance/codes-of-practice">https://www.worksafe.qld.gov.au/laws-and-compliance/codes-of-practice</a> Legislation ACT: <a href="https://www.worksafe.act.gov.au/laws-and-compliance/acts-and-regulations">https://www.worksafe.act.gov.au/laws-and-compliance/acts-and-regulations</a>

Codes of Practice ACT: https://www.worksafe.act.gov.au/laws-and-compliance/codes-of-practice

#### **New South Wales**

Work Health and Safety Act 2011

Work Health and Safety Regulations 2017

Legislation NSW: https://www.safework.nsw.gov.au/legal-obligations/legislatide

Codes of Practice NSW: https://www.safework.nsw.gov.au/resource-library/lis

#### **Northern Territory**

Work Health and Safety (National Uniform Legislation) Act 2011

Work Health and Safety (National Uniform Legislation) Regulation 201

Legislation NT: https://worksafe.nt.gov.au/laws-and-compliance/wo\_place-

Codes of Practice NT: https://worksafe.nt.gov.au/f

#### South Australia

Work Health and Safety Act 2012 (SA)

Work Health and Safety Regulations 2012 (SA)

Legislation for SA: https://www.safework.sa.gov.au/resources/le\_lation

Codes of Practice for SA: https://www.safework.sa.gov.au/work\_aces/codes-of-practice#COPs

#### Tasmania

Work Health and Safety Act 2012

Work Health and Safety (Transitional and Consequential Provisions) Act 2012

Work Health and Safety Regulations 2012

Work Health and Safety (Transitional) Regulations 2012

Legislation for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/acts-and-regulations

Codes of Practice for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/codes-of-practice

Details of permits, licenses or access required by regulatory bodies (add or delete as required):

- Permits from local council
- Authorisation to commence work
- Any required documents.

#### Victoria

Occupational Health al. Safety Act

Occupational Health and affety gulations 2017

Legis on VIC: https://www.wsafe.vic.gov.au/occupational-health-and-safety-act-and-

gulat

des on actice VI autros://www.worksafe.vic.gov.au/compliance-codes-and-codes-practice

#### Western Australia

Work Health and Safety Act 2020

Work Health and Safety Regulations 2022

Legislation Western Australia: https://www.commerce.wa.gov.au/worksafe/legislation Codes of Practice WA: https://www.commerce.wa.gov.au/worksafe/codes-practice

#### Safe Work Australia Links

Law and Regulation (All States): https://www.safeworkaustralia.gov.au/law-and-regulation Model Codes of Practice: https://www.safeworkaustralia.gov.au/resources-publications/model-codes-of-practice

#### **Model Codes of Practice**

- Managing noise and preventing hearing loss at work
- Confined spaces
- Labelling of workplace hazardous chemicals
- Managing risks of hazardous chemicals in the workplace
- Welding processes
- First aid in the workplace
- Managing the risk of falls at workplaces
- Hazardous manual tasks
- Managing the risk of falls in housing construction
- Managing electrical risks in the workplace
- Demolition work
- Excavation work
- Work health and safety consultation, cooperation and coordination
- Managing the work environment and facilities
- How to manage work health and safety risks
- Managing risks of plant in the workplace
- Construction work





#### SIGNATORIES OF THE SAFE WORK METHOD STATEMENT

The signed and dated personnel listed below have cooperated in the consultation and development of this Safe Work Method Statement which has been approved by the Person/s Conducting a Business or Undertaking (PCBU). In signing this Safe Work Method Statement each individual acknowledges and confirms that they have read this SWMS in full, having raised any questions for items on this Safe Work Method Statement that require clarification, and confirms that they are competent, skilled and knowledgeable for the task assigned to them. Every person acknowledges that they have received the relevant training and qualifications where required, before carrying out any work contained in this Safe Work Method Statement. By signing this Safe Work Method Statement each individual agrees to work safely, to follow any safe work instructions which are provided, and agrees to use all Personal Protective Equipment where appropriate.

Worker Name	Signature	Date

#### SAFE WORK IN THE STATEMENT MONITORING AND REVIEW

The SWMS must be reviewed regularly to make sure it remains a fective of must be reviewed (and revised if necessary) if relevant control measures are revised. The view process should be carried out in consultation with workers (including contractors of the SWMS and their health and safety representatives who represented that work group at the workplace.

When the SWMS has been revised the PCBU mast ensure that advised that a revision has been made and how they can access the revised SWMS, including all persons who will need to change a work procedure or system as a rest of the review are advised of the changes in a way that will enable them to implement their duties and the involved in the work must be provided with the relevant information and instruction that will assist them to understand and implement the revised SWMS.

The SWMS must be monitored regularly for the effectiveness of ensuring hazard controls are effective in reducing the risk of incidents, keeping the workplace safe for all personnel. The person responsible for monitoring the effectiveness of the Safe Work Method Statement should employ a multi-faceted approach which includes but is not limited to:

- Spot Checks.
- 2. Consultation with workers, contractors and sub-contractors.
- Internal audits on a continual basis.

An approach of continuous improvement, promptly recording inconsistencies or deficiencies, followed up by immediate corrective action and consultation with all relevant personnel ensures that the PCBU is consistently developing ever-improving systems of safe work principles.

REVIEW NUMBER	1	2	3	4	5	6	7
NAME							
INITIALS							
DATE							





### SAFE WORK METHOD STATEMENT REVIEW CHECKLIST

This Safe Work Method Statement Review Checklist is to be followed and used upon initial development of the SWMS to help ensure that all steps have been adequately taken before work commences. Think of this document as an internal audit review checklist before commencing work, and may form part of a Toolbox Talk (safety meeting) and may be used as an opportunity for education and training.

ITEMS WHICH MUST BE INCLUDED IN THE SWMS	COMPLETED	COMMENTS	
		•	
The company details have been entered, including the project name and address.			
All relevant personnel consulted during the development of the SWMS.			
Name, signature, position and date signed of the person approving the SWMS.			
Specific personnel and qualifications, experience is noted in the SWMS.	7		
Provides a step-by-step process of tasks required to carry out the activity or task.			
Adequate risk assessment of any identified hazards has been completed.			
Foreseeable hazards are identified and documented for each step.			
Any hazards listed in any site risk assessments have been added to the SWMS			
SWMS initial risk (IR) column as well as residual risk (RR) column pleted.			
Check control measures added to the SWMS are the most effective selective.			
Responsible person is assigned and listed on the part of the important of measures.			
Permit or licenses requirements specified, sur as Hot Work, Electric Work, Work at Heights etc.			
SWMS identifies plant and equipment to be us			
Details of inspection checks required for any equipment listed at noted on the SWMS.			
Describes any mandatory qualifications, experience, or skills required to perform the work.			
Applicable personal protective equipment is selected on the SWMS.			
Reflects and documents any legislative references and/or Australian Standards.			
Identifies any hazardous substances used with specific control measures in line with any SDS.			
REVIEWED BY	DATE REVIEWE	D	
SIGNATURE	DATE COMPLETED		