

Plywood Handling | SAFE WORK METHOD STATEMENT (SWMS)

TASK OR ACTIVITY: Plywood Handling

| | | |
|-------------------|--------|--------|
| Business Name: | ABN: | SWMS# |
| Business Address: | | |
| Contact Person: | Phone: | Email: |

THIS SAFE WORK METHOD STATEMENT IS APPROVED BY THE PCBU OF THE PROJECT

Under the Work Health and Safety Regulation (WHS Regulation), a person conducting a business or undertaking (PCBU) is required to ensure that a safe work method statement (SWMS) is prepared before the proposed work starts.

| | | |
|---|--------|--------|
| Full Name: | | |
| Signature: | Title: | Date: |
| Details of the person(s) responsible for ensuring implementation, monitoring compliance of the SWMS as well as reviews and modifications of the SWMS. | | |
| Full Name: | Title: | Phone: |

ALL PERSONNEL PARTICIPATING IN ANY ACTIVITY ON THIS SWMS MUST HAVE THE FOLLOWING COMMUNICATED

Safety meetings or toolbox talks will be scheduled in accordance with legislative requirements to first identify any site hazards, then to communicate those hazards and then to further take steps to either eliminate or control each hazard.

If an incident or a near miss occurs, all work must stop immediately. Depending on the severity of the incident, a meeting will be called with all workers to amend the SWMS if required. The meeting may also be an educational opportunity.

Any changes made to the SWMS after an incident or a near miss must be approved by the Person Conducting Business or Undertaking and communicated to all relevant personnel.

The SWMS must be kept and be available for inspection at least until the work is completed. Where a SWMS is revised, all versions should be kept. If a notifiable incident occurs in relation to which the SWMS relates, then the SWMS must be kept for at least two years from the occurrence of the notifiable incident.

NAME OF ALL RELEVANT PERSONNEL WHO HAVE BEEN CONSULTED AND COMMUNICATED TO IN THE DEVELOPMENT AND APPROVAL OF THIS SWMS

CLIENT OR PRINCIPAL CONTRACTOR DETAILS

| | |
|--|----------------|
| Client: | SCOPE OF WORKS |
| Project Name: | |
| Project Address: | |
| Project Manager: | |
| Contact Phone: | |
| Date SWMS supplied to Project Manager: | |

ANY HIGH-RISK CONSTRUCTION WORK BEING CARRIED OUT

- | | |
|--|--|
| <input type="checkbox"/> involves a risk of a person falling more than 2 meters | <input type="checkbox"/> is carried out on or near pressurised gas mains or piping |
| <input type="checkbox"/> is carried out on a telecommunication tower | <input type="checkbox"/> is carried out on or near chemical, fuel or refrigerant lines |
| <input type="checkbox"/> involves demolition of an element of a structure that is load-bearing | <input type="checkbox"/> is carried out on or near energised electrical installations or services |
| <input type="checkbox"/> involves demolition of an element related to the physical integrity of a structure | <input type="checkbox"/> is carried out in an area that may have a contaminated or flammable atmosphere |
| <input type="checkbox"/> involves, or is likely to involve, disturbing asbestos | <input type="checkbox"/> involves tilt-up or precast concrete |
| <input type="checkbox"/> involves structural alteration or repair that requires temporary support to prevent collapse | <input type="checkbox"/> is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor |
| <input type="checkbox"/> is carried out in or near a confined space | <input type="checkbox"/> is carried out in an area of a workplace where there is any movement of powered mobile plant |
| <input type="checkbox"/> is carried out in/near a shaft or trench deeper than 1.5m or tunnel involving use of explosives | <input type="checkbox"/> is carried out in areas with artificial extremes of temperature. |
| <input type="checkbox"/> is carried out in or near water or other liquid that involves a risk of drowning. | <input type="checkbox"/> involves diving work. |

ANY HIGH-RISK MACHINERY OR EQUIPMENT NEARBY

RISK MATRIX

| LIKELIHOOD | INSIGNIFICANT | MINOR | MODERATE | MAJOR | CATASTROPHIC | SCORE | ACTION | HEIRARCHY OF CONTROLS |
|---|---------------|---------------|---------------|------------|--------------|----------------|-----------------------------------|--|
| ALMOST CERTAIN | 3 HIGH | 3 HIGH | 4 ACUTE | 4 ACUTE | 4 ACUTE | | | Elimination Remove the hazard. |
| LIKELY | 2 MODERATE | 3 HIGH | 3 HIGH | 4 ACUTE | 4 ACUTE | 4A ACUTE | DO NOT PROCEED | Substitution Replace the hazard. |
| POSSIBLE | 1 LOW | 2 MODERATE | 3 HIGH | 4 ACUTE | 4 ACUTE | 3H HIGH | Review before work starts. | Isolation Isolate People from the hazard |
| UNLIKELY | 1 LOW | 1 LOW | 2 MODERATE | 3 HIGH | 4 ACUTE | 2M MODERATE | Ensure control measures in place. | Engineering Isolate the hazard. |
| RARE | 1 LOW | 1 LOW | 2 MODERATE | 3 HIGH | 3 HIGH | 1L LOW | Monitor and keep records | Administrative Change the work. |
| Notes on Hierarchy of Controls: Elimination methods are the most effective and preferred when controlling a hazard. Substitution is the second most effective method of controlling a hazard. Engineering by isolation is the third most effective, while Administrative Controls by changing the work is the fourth most effective method. PPE (Personal Protective Equipment) is the least effective method. | | | | | | | | PPE |

PERSONAL PROTECTIVE EQUIPMENT (PPE)

Select the appropriate PPE above suitable for the equipment used or the job task being performed (if applicable).

| FOOT PROTECTION | HAND PROTECTION | HEAD PROTECTION | HEARING PROTECTION | EYE PROTECTION | RESPIRATORY PROTECTION | FACE PROTECTION | HIGH-VIS CLOTHING | PROTECTIVE CLOTHING | FALL PROTECTION | SUN PROTECTION | HAIR/JEWELLERY SECURED |
|--|--|--|--|--|---|--|--|--|--|--|--|
|  |  |  |  |  |  |  |  |  |  |  |  |
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

Other PPE Required:

Permit or Licenses Requirements

Mandatory Qualifications and Training

| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------------|---|--------------|--|---------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| 1. Preparation | Incorrect manual handling, Exposure to chemicals from plywood | 2M | <ul style="list-style-type: none"> - Conduct manual handling training sessions for all workers to ensure proper lifting techniques and ergonomics. - Use mechanical aids, such as trolleys or forklifts, to move heavy plywood sheets whenever possible. - Implement a two-person lift policy for handling large or heavy pieces of plywood to distribute the load evenly. - Ensure workers are wearing appropriate personal protective equipment (PPE), such as gloves and masks, to prevent exposure to chemicals. - Store plywood sheets in a well-ventilated area to minimize the accumulation of chemical fumes. - Regularly inspect workplace ventilation systems to ensure they are functioning effectively to disperse chemical fumes. - Rotate tasks among workers to minimise prolonged exposure to any potential chemical hazards from plywood. - Provide Material Safety Data Sheets (MSDS) for plywood materials to inform workers about safe handling and potential chemical hazards. - Establish clear pathways free from obstructions to safely transport plywood within the workspace. - Encourage frequent rest breaks to reduce strain and fatigue from manual handling tasks. - Label and store chemicals related to plywood treatment separately to prevent accidental exposure. - Allow only trained personnel to handle or work with treated plywood that may contain hazardous chemicals. - Perform regular risk assessments on manual handling tasks and chemical exposures related to handling plywood. | 1L |
| 2. Plywood Transportation | Vehicle collision, Falling objects | 3H | <ul style="list-style-type: none"> - Ensure all employees involved in the transportation of plywood hold a valid driver's licence and are trained in safe driving practices. - Conduct regular maintenance checks on all vehicles to ensure they are in safe working condition before transporting plywood. - Use suitable vehicles with appropriate load capacity to safely handle and transport plywood sheets without overloading. - Securely fasten plywood sheets using ratchet straps or other secure tie-down methods to prevent movement during transport. - Implement a traffic management plan to control vehicle movements within the worksite, including designated loading and unloading areas. - Use spotters to assist drivers when manoeuvring in tight spaces or around obstacles to reduce the risk of collision. | 2M |

| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|----------------------|---|--------------|---|---------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | <ul style="list-style-type: none"> - Plan routes in advance to avoid areas with heavy traffic, low clearance, or unsuitable road conditions that may pose risks during transportation. - Clearly mark the transport vehicle to alert other road users of oversized loads or potential hazards. - Equip transport vehicles with safety features such as reversing alarms and cameras to improve visibility and prevent accidents. - Use appropriate personal protective equipment (PPE) such as high-visibility vests for workers involved in loading and unloading. - Regularly inspect tie-downs and restraints for wear and damage, ensuring they are replaced when necessary to maintain effectiveness. - Maintain clear communication between drivers and ground personnel through radios or mobile phones to coordinate operations safely. - Conduct a pre-shift briefing to inform staff of the transport schedule, route, and any potential hazards identified. - Monitor weather conditions prior to transport and postpone operations if adverse weather increases the risk of accidents or injury. | |
| 3. Unloading Plywood | Falling objects, Struck by moving vehicle | 3H | <ul style="list-style-type: none"> - Establish a clearly defined unloading zone marked with cones or barriers to prevent unauthorised personnel access. - Implement a designated spotter to guide drivers and equipment operators during unloading operations. - Conduct pre-operational checks on all lifting equipment, such as forklifts or cranes, ensuring they are in good working order and have valid service certifications. - Train all employees involved in the unloading process in safe lifting techniques and manual handling procedures. - Utilise proper personal protective equipment (PPE), including steel-toed boots, high visibility vests, hard hats, and gloves. - Ensure plywood stacks are secured with appropriate strapping or wrapping during transit to prevent shifting. - Use certified lifting slings or attachments appropriate for the weight and size of the plywood. - Implement a system where vehicles have the ability to be immobilised when being loaded or unloaded to prevent accidental movement. - Display clear signage in the unloading area to remind workers of potential hazards and safety precautions. - Conduct regular toolbox talks focusing on site-specific hazards and best practice unloading procedures. - Supervise the entire unloading process to ensure compliance with safety protocols and address any unsafe behaviour immediately. - In adverse weather conditions, assess the situation and postpone unloading activities if it compromises safety, such as strong winds or rain affecting grip and visibility. | 1L |

| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------|---|--------------|---|---------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| 4. Plywood Stacking | Incorrect manual handling, Slips, trips and falls | 2M | <div>SAMPLE</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> | 1L |
| 5. Cutting Plywood | Noise exposure, Hand injuries from tools | 3H | <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> | 1L |

| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|-----------------------|---|--------------|---|---------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> | |
| 6. Assembling Plywood | Splinters causing skin injuries, incorrect use of tools | 2M | <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> | 1L |

| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------|--|--------------|---|---------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| 7. Bonding Plywood | Chemical exposure, Fire hazards | 3H | <div>SAMPLE</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> | 2M |
| 8. Sanding Plywood | Dust inhalation, Eye injury from particles | 3H | <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> <div>[REDACTED]</div> | 1L |

ure, Fire hazard

| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|------------------------|--|--------------|--|---------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | | |
| 10. Drying Plywood | Fire hazard, Heat exposure | 3H | | 2M |
| 11. Inspecting Plywood | Cuts from splinters, Slips, trips, and falls | 2M | | 1L |

[illegible]

| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|----------------------|---|--------------|--|---------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | | |
| 13. Marking Plywood | Incorrect posture, Repetitive movement strain | 2M | | 1L |
| 14. Shipping Plywood | Vehicle collision, Falling objects | 3H | | 2M |

3H

Section Headers, Wood

[illegible]

| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|-----------------------------------|--|--------------|--|---------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | | |
| 19. Equipment Servicing | Electrical hazards, Getting caught in machinery | 3H | | 2M |
| 20. Emergency Procedures Training | Failure to understand instructions, Panic during emergencies | 2M | | 1L |

SAMPLE

EMERGENCY RESPONSE – CALL 000 FOR EMERGENCIES

Ensure to have an Emergency Management Plan in place as well as adequate numbers of trained first aid staff with easy access to fully stocked first aid kits, rescue equipment, material safety data sheets, adequate access to emergency communication equipment and fire-fighting equipment suitable for all classes of fire and ignition sources.

LEGISLATIVE REFERENCES

RELEVANT LEGISLATION AND CODES OF PRACTICE. DELETE THE LEGISLATIVE REFERENCES IF ANY STATE THAT ARE NOT APPLICABLE

Queensland & Australian Capital Territory

Work Health and Safety Act 2011

Work Health and Safety Regulations 2011

Legislation QLD: <https://www.worksafe.qld.gov.au/laws-and-compliance/work-health-and-safety-laws>

Codes of Practice QLD: <https://www.worksafe.qld.gov.au/laws-and-compliance/codes-of-practice>

Legislation ACT: <https://www.worksafe.act.gov.au/laws-and-compliance/acts-and-regulations>

Codes of Practice ACT: <https://www.worksafe.act.gov.au/laws-and-compliance/codes-of-practice>

New South Wales

Work Health and Safety Act 2011

Work Health and Safety Regulations 2017

Legislation NSW: <https://www.safework.nsw.gov.au/legal-obligations/legislation>

Codes of Practice NSW: <https://www.safework.nsw.gov.au/resource-library/list-codes-of-practice>

Northern Territory

Work Health and Safety (National Uniform Legislation) Act 2011

Work Health and Safety (National Uniform Legislation) Regulations 2011

Legislation NT: <https://worksafe.nt.gov.au/laws-and-compliance/workplace-safety-laws>

Codes of Practice NT: <https://worksafe.nt.gov.au/laws-and-compliance/codes-of-practice>

South Australia

Work Health and Safety Act 2012 (SA)

Work Health and Safety Regulations 2012 (SA)

Legislation for SA: <https://www.safework.sa.gov.au/resources/legislation>

Codes of Practice for SA: <https://www.safework.sa.gov.au/workplaces/codes-of-practice#COPs>

Tasmania

Work Health and Safety Act 2012

Work Health and Safety (Transitional and Consequential Provisions) Act 2012

Work Health and Safety Regulations 2012

Work Health and Safety (Transitional) Regulations 2012

Legislation for TAS: <https://worksafe.tas.gov.au/topics/laws-and-compliance/acts-and-regulations>

Codes of Practice for TAS: <https://worksafe.tas.gov.au/topics/laws-and-compliance/codes-of-practice>

Details of permits, licenses or access required by regulatory bodies (add or delete as required):

- Permits from local council
- Authorisation to commence work
- Any required documents.

Victoria

Occupational Health and Safety Act 2004

Occupational Health and Safety Regulations 2017

Legislation VIC: <https://www.worksafe.vic.gov.au/occupational-health-and-safety-act-and-regulations>

Codes of Practice VIC: <https://www.worksafe.vic.gov.au/compliance-codes-and-codes-practice>

Western Australia

Work Health and Safety Act 2020

Work Health and Safety Regulations 2022

Legislation Western Australia: <https://www.commerce.wa.gov.au/worksafe/legislation>

Codes of Practice WA: <https://www.commerce.wa.gov.au/worksafe/codes-practice>

Safe Work Australia Links

Law and Regulation (All States): <https://www.safeworkaustralia.gov.au/law-and-regulation>

Model Codes of Practice: <https://www.safeworkaustralia.gov.au/resources-publications/model-codes-of-practice>

Model Codes of Practice

- Managing noise and preventing hearing loss at work
- Confined spaces
- Labelling of workplace hazardous chemicals
- Managing risks of hazardous chemicals in the workplace
- Welding processes
- First aid in the workplace
- Managing the risk of falls at workplaces
- Hazardous manual tasks
- Managing the risk of falls in housing construction
- Managing electrical risks in the workplace
- Demolition work
- Excavation work
- Work health and safety consultation, cooperation and coordination
- Managing the work environment and facilities
- How to manage work health and safety risks
- Managing risks of plant in the workplace
- Construction work

SIGNATORIES OF THE SAFE WORK METHOD STATEMENT

The signed and dated personnel listed below have cooperated in the consultation and development of this Safe Work Method Statement which has been approved by the Person/s Conducting a Business or Undertaking (PCBU). In signing this Safe Work Method Statement each individual acknowledges and confirms that they have read this SWMS in full, having raised any questions for items on this Safe Work Method Statement that require clarification, and confirms that they are competent, skilled and knowledgeable for the task assigned to them. Every person acknowledges that they have received the relevant training and qualifications where required, before carrying out any work contained in this Safe Work Method Statement. By signing this Safe Work Method Statement each individual agrees to work safely, to follow any safe work instructions which are provided, and agrees to use all Personal Protective Equipment where appropriate.

| Worker Name | Signature | Date |
|-------------|-----------|------|
| | | |
| | | |
| | | |
| | | |
| | | |

SAFE WORK METHOD STATEMENT MONITORING AND REVIEW

The SWMS must be reviewed regularly to make sure it remains effective and must be reviewed (and revised if necessary) if relevant control measures are revised. The review must be carried out in consultation with workers (including contractors and sub-contractors) who may be affected by the operation of the SWMS and their health and safety representatives who represent that work group at the workplace.

When the SWMS has been revised the PCBU must ensure that all persons involved with the work are advised that a revision has been made and how they can access the revised SWMS, including all persons who will need to change a work procedure or system as a result of the review are advised of the changes in a way that will enable them to implement their duties consistently with the revised SWMS. All workers that will be involved in the work must be provided with the relevant information and instruction that will assist them to understand and implement the revised SWMS.

The SWMS must be monitored regularly for the effectiveness of ensuring hazard controls are effective in reducing the risk of incidents, keeping the workplace safe for all personnel. The person responsible for monitoring the effectiveness of the Safe Work Method Statement should employ a multi-faceted approach which includes but is not limited to:

1. Spot Checks.
2. Consultation with workers, contractors and sub-contractors.
3. Internal audits on a continual basis.

An approach of continuous improvement, promptly recording inconsistencies or deficiencies, followed up by immediate corrective action and consultation with all relevant personnel ensures that the PCBU is consistently developing ever-improving systems of safe work principles.

| REVIEW NUMBER | 1 | 2 | 3 | 4 | 5 | 6 | 7 |
|---------------|---|---|---|---|---|---|---|
| NAME | | | | | | | |
| INITIALS | | | | | | | |
| DATE | | | | | | | |

SAFE WORK METHOD STATEMENT REVIEW CHECKLIST

This Safe Work Method Statement Review Checklist is to be followed and used upon initial development of the SWMS to help ensure that all steps have been adequately taken before work commences. Think of this document as an internal audit review checklist before commencing work, and may form part of a Toolbox Talk (safety meeting) and may be used as an opportunity for education and training.

| ITEMS WHICH MUST BE INCLUDED IN THE SWMS | COMPLETED | COMMENTS |
|--|-------------------------------------|-----------------------|
| The company details have been entered, including the project name and address. | <input checked="" type="checkbox"/> | |
| All relevant personnel consulted during the development of the SWMS. | <input checked="" type="checkbox"/> | |
| Name, signature, position and date signed of the person approving the SWMS. | <input type="checkbox"/> | |
| Specific personnel and qualifications, experience is noted in the SWMS. | <input checked="" type="checkbox"/> | |
| Provides a step-by-step process of tasks required to carry out the activity or task. | <input checked="" type="checkbox"/> | |
| Adequate risk assessment of any identified hazards has been completed. | <input checked="" type="checkbox"/> | |
| Foreseeable hazards are identified and documented for each step. | <input checked="" type="checkbox"/> | |
| Any hazards listed in any site risk assessments have been added to the SWMS. | <input checked="" type="checkbox"/> | |
| SWMS initial risk (IR) column as well as residual risk (RR) column completed. | <input checked="" type="checkbox"/> | |
| Check control measures added to the SWMS are the most effective selected. | <input checked="" type="checkbox"/> | |
| Responsible person is assigned and listed on the SWMS for the implementation of control measures. | <input checked="" type="checkbox"/> | |
| Permit or licenses requirements specified, such as Hot Work, Electrical Work, Work at Heights etc. | <input checked="" type="checkbox"/> | |
| SWMS identifies plant and equipment to be used. | <input checked="" type="checkbox"/> | |
| Details of inspection checks required for any equipment listed and noted on the SWMS. | <input checked="" type="checkbox"/> | |
| Describes any mandatory qualifications, experience, training or skills required to perform the work. | <input checked="" type="checkbox"/> | |
| Applicable personal protective equipment is selected on the SWMS. | <input checked="" type="checkbox"/> | |
| Reflects and documents any legislative references and/or Australian Standards. | <input checked="" type="checkbox"/> | |
| Identifies any hazardous substances used with specific control measures in line with any SDS. | <input checked="" type="checkbox"/> | |
| | | |
| REVIEWED BY | | DATE REVIEWED |
| SIGNATURE | | DATE COMPLETED |