



Power Flange Machir	ne   SAFE WORK METHOD	STATEMENT (SWMS)	
TASK	OR ACTIVITY: Power Flange Ma	achine	
Business Name:		ABN:	SWMS#
Business Address:			
Contact Person:	Phone:	E 111:	
TUIS SAFE WORK METHOD	STATEMENT IS APPRO\\\O\D BY	THE PC. OF THE ROJECT	
Under the Work Health and Safety Regulation (WHS Regulation), a person conduct the proposed work starts.	cting a business or under a (PC 1) is	required to en that a safe work method s	statement (SWMS) is prepared before
Full Name:			
Signature:	NY	Title:	Date:
Details of the person(s) responsible for ensuring implementation, monitoring a	opliance the VMS a well as review	s and modifications of the SWMS.	
Full Name:		Title:	Phone:
ALL PERSONNEL PARTICIPATING IN ANY ACTIVITY ON THIS S (MS M) HAVE THE FOLLOWING COMMUNICATED	NA 2 OF ALL RELEVANT PERSONNI EVELOPMENT AND APPROVAL OF	EL WHO HAVE BEEN CONSULTED AND COTHIS SWMS	OMMUNICATED TO IN THE
Safety meetings or toolbox talks will be sched sed in account with gislative requirements to first identify any site hazards, and then to further take steps to either eliminate or continuous each hazard.			
If an incident or a near miss occurs, all work must sto, quately. Depending on the severity of the incident, a meeting will be called with all workers to amend the SWMS if required. The meeting may also be an educational opportunity.			
Any changes made to the SWMS after an incident or a near miss must be approved by the Person Conducting Business or Undertaking and communicated to all relevant personnel.			
The SWMS must be kept and be available for inspection at least until the work is completed. Where a SWMS is revised, all versions should be kept. If a notifiable incident occurs in relation to which the SWMS relates, then the SWMS must be kept for at least two years from the occurrence of the notifiable incident.			





CLIENT OR PRINCIPAL	CONTRACTOR DETAILS
Client:	SCOPE OF WORKS
Project Name:	
Project Address:	
Project Manager:	
Contact Phone:	
Date SWMS supplied to Project Manager:	
ANY HIGH BIOK CONSTRUCTOR	NAME OF THE POLIT
ANY HIGH-RISK CONSTRUCTOR	N WC & BEIN C ARIED OUT
☐ involves a risk of a person falling more than 2 meters	is carried out on or near pressurised gas mains or piping
☐ is carried out on a telecommunication tower	carried out on or near chemical, fuel or refrigerant lines
☐ involves demolition of an element of a structure that is load-bearing	$\square$ is carried out on or near energised electrical installations or services
☐ involves demolition of an element related to the physical integral of a functure	☐ is carried out in an area that may have a contaminated or flammable atmosphere
☐ involves, or is likely to involve, disturbing asb	☐ involves tilt-up or precast concrete
☐ involves structural alteration or repair that —quires term — v sup —rt to prevent collapse	☐ is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor
☐ is carried out in or near a confined space	☐ is carried out in an area of a workplace where there is any movement of powered mobile plant
☐ is carried out in/near a shaft or trench deeper that. tunnel involving use of explosives	☐ is carried out in areas with artificial extremes of temperature.
$\square$ is carried out in or near water or other liquid that involves a risk of drowning.	☐ involves diving work.
ANY HIGH-RISK MACHINER	Y OR EQUIPMENT NEARBY



RISK MATRIX										
LIKELIHOOD	INSIGNIFICANT	MINOR	MODERATE	MAJOR	CATASTROPHIC	SCORE	ACTION	HEIRARCHY OF CONTROLS		
ALMOST CERTAIN	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4 ACUTE	SCORE	ACTION	Elimination Remove the hazard.		
LIKELY	2 MODERATE	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4A ACUTE	DO NOT PROCE	Substitution		
POSSIBLE	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	4 ACUTE	3H HIGH	Review before work starts.	Replace the hazard.		
UNLIKELY	1 LOW	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	2M MODERATE	Ensure control measures in place.	Isolate People from the hazard		
RARE	1 LOW	1 LOW	2 MODERATE	3 HIGH	3 HIGH	1L LOW	nitor and	Engineering Isolate the hazard.		
is the second m	rchy of Controls: ost effective metho nging the work is th	d of controlling a	hazard. Enginee	ering by isolati	on is the in ost e	en 'ive, while	rd. Substitution Administrative effective	Administrative Change the work.  PPE		

				PERS		TIVE EQUIPM					
		Select the app	propriate PPL	abo√ ≃uitab	ic or the equi	pment used or	the job task	being perforr	ned (if applica	ıble).	
FOOT PROTECTION	HAND PROTECTION	HEAD PROTECTION	HEARING ETION	P ECTION	R PIRATORY PROTECTION	FACE PROTECTION	HIGH-VIS CLOTHING	PROTECTIVE CLOTHING	FALL PROTECTION	SUN PROTECTION	HAIR/JEWELLERY SECURED
Other PPE R	Required:										
	Pe	ermit or Licen	ses Requirem	ents		Mandatory Qualifications and Training					



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
1. Preparation	Inadequate lighting, Incorrect PPE	2M	- Proper lighting: Ensure that adequate lighting is provided in the work area, including temporary lighting if necessary, to allow for clear visibility of all work tasks and obential hazards.  - Inspection of lighting: Regularly inspect and in the mall lighting systems to ensure they are functioning correctly and providing sufficient illumination.  - PPE training: Provide training all workers on the opportunate selection, use, storage, and maintenance of required PPE for the mediatory use of correct PPE, including safety glasses, protective gloves, safe notwear, an samplugh cear has as needed, during the operation of the power flange machine.  - Signar and later a Display visible signs and labels around the work area, reminding workers to wear the colar PPE are informing them of potential hazards.  - PPE it peed has Color uct regular inspections of all PPE, ensuring they are in good working condition and repusing by damaged or worn equipment as necessary.  - Thesek oping: A aintain a clean and organised work environment, reducing trip hazards and other issues to bould arise due to inadequate lighting.  - Pre-start toolbox talks: Conduct briefings prior to work commencement to remind workers about potential has rids, required PPE, and safe work practices specific to the task at hand.  - Emergency response planning: Develop and implement an emergency response plan outlining the steps to follow in case of an incident involving inadequate lighting or incorrect PPE use.  - PPE availability: Ensure an adequate supply of appropriate PPE is readily available to all workers performing tasks involving the power flange machine.  - Supervisor monitoring: Assign a supervisor to closely monitor the work area, ensuring that all workers are utilising proper PPE and following safe work procedures.  - Incident reporting and investigation: Establish a system for workers to report any safety concerns related to lighting or PPE use. Investigate reported incidents thoroughly and implement corrective actions to prevent future occurre	1L
2. Set Up Machine	Mechanical hazards, Electrocution	3Н	<ul> <li>Ensure that only trained and authorised personnel are allowed to operate the power flange machine, thus minimising the risk of mechanical hazards due to inexperienced handling.</li> <li>Perform regular maintenance checks on the power flange machine, including inspections for wear and tear, ensuring all bolts and connections are tightened securely, and conducting electrical tests to identify any potential faults or defects.</li> <li>Implement a lockout/tagout procedure for the power flange machine, ensuring it is powered off and disconnected from the main power supply when not in use or during maintenance activities, preventing accidental startup or electrocution.</li> </ul>	2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			- Familiarise workers with emergency stop procedures and clearly mark the location of emergency stop buttons or switches.	
			- Provide workers with appropriate personal protection, equipment (PPE), such as safety glasses, gloves, hearing protection, and steel-toed boots when the wing with or near the power flange machine.	
			- Properly ground the power flange machine a reduce the sk of electrocution through adequate grounding and bonding techniques.	
			- Make sure that all cables, plugs, and electrical imponents are in good condition, free of damages or signs of wear, and maintain in many regularly to avoid possible of circuition hazards.	
			- Establish a clear and tidy work ace around the potential managemachine, ensuring ample space for maneuvering and the potential free of tripping hazards.	
			- Install safe't evices, such as guar and shous, to cover any moving parts, pinch points, or areas where mechanial hazard have been accessed to these danger zones while the machine is in our ation.	
			- Implying a Job crety Analysis (JSA) or similar risk assessment method before starting work with the power and machine to identify potential hazards and develop strategies for controlling and mitigating risks as ocial with a hispecific job.	
			Insure ropely hiting and visibility in the work area to reduce the likelihood of accidents or incidents reliable to poor visibility while setting up and operating the power flange machine.	
			Conduct olbox talks or safety briefings with workers involved in the operation of the power flange chine, outlining relevant hazards, control measures, and safe working practices to increase awareness are reduce potential risks associated with the equipment.	
	6		Always follow the manufacturer's guidelines for machine set up, operation, and maintenance, ensuring adherence to established safety standards and promoting consistent use of safe work procedures throughout the workplace.	
			- Ensure operators are well-trained in the appropriate use of the Power Flange Machine, including proper inspection and alignment techniques.	
			- Implement a pre-operation checklist that must be completed before any work with the flanges begins. This can help to ensure equipment is safely aligned and minimise the risk of accidents.	
			- Always use personal protective equipment (PPE) suitable for the specific task, such as gloves, safety footwear, and eye protection, to prevent injury from pinch points and slipping hazards.	
Check Flange     Alignment	Pinch points, Slipping hazards	2M	- Conduct regular maintenance checks on the Power Flange Machine to ensure its proper functioning. Proper maintenance can reduce the chances of misalignment and other issues.	1L
			- Keep the working area clean and free of debris to avoid any slipping hazards that may occur while handling the flanges or adjusting the alignment.	
			- Develop and enforce safe operating procedures (SOPs) that include thorough instructions on the correct method for checking flange alignment as well as steps to take if the alignment is found to be incorrect.	
			- Use appropriate tools and support devices like clamps, jacks, or wedges to hold flanges securely in place while aligning and joining them.	



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			<ul> <li>Implement a system of communication that allows operators and other personnel to quickly alert each other of any potential hazards, such as misaligned flanges or the sudden release of tension during alignment.</li> </ul>	
			- Establish designated walking areas around the ower Flange Machine, ensuring they are kept clear of hazards and providing proper signage to discovers.	
			- Regularly review and update the SWMS to dress , changes in equipment or processes and ensure that all employees are informed of these update.	
			- Encourage a culture of safe, within your workpines, promoting open dialogue between management and employees regarding haze sidentification, including the relating, and suggestions for improving workplace health architecture.	
4. Secure Flanges	Falling objects, Cal	ВН		2M
4. Secure Flanges				



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
5. Power Up Machine	Electrical shorts, lest damage from noise	2M		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
5. Start Initial Cut Fl	lying debris, Core ct with moving parts	ЗН		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
7. Stop Machine for Inspection	Burns, Exposure to coolant	2M		1L
8. Make Adjustments	Release of energy, Pinch points	3H		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
9. Resume Cutting	Entanglement, Coolant spills	2M		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
10. Perform Final Cut	Blind spots, Excessive vibration	3Н		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
11. Power Down Machine	Arc flash, Inadvertent activation	2M		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
				_
				•
				•
				_
				•
				I
				ı
12. Remove Machined	Ergonomic strain, Sharp	ЗН		2M
Flange	Ergonomic strain, Snarp	эп		ZIVI
				1



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
				I



#### **EMERGENCY RESPONSE - CALL 000 FOR EMERGENCIES**

Ensure to have an Emergency Management Plan in place as well as adequate numbers of trained first aid staff with easy access to fully stocked first aid kits, rescue equipment, material safety data sheets, adequate access to emergency communication equipment and fire-fighting equipment suitable for all classes of fire and ignition sources.

#### LEGISLATIVE REFERENCES

RELEVANT LEGISLATION AND CODES OF PRACTICE. DELETE THE LEGISLATIVE REFERENCES. ANY STATE OF AT ARE NOT APPLICABLE.

#### **Queensland & Australian Capital Territory**

Work Health and Safety Act 2011

Work Health and Safety Regulations 2011

Legislation QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/work-health-and-safety-laws Codes of Practice QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/codes-of-practice

Legislation ACT: https://www.worksafe.act.gov.au/laws-and-compliance/acts-and-regulations

Codes of Practice ACT: https://www.worksafe.act.gov.au/laws-and-compliance/codes-of-practice

#### **New South Wales**

Work Health and Safety Act 2011

Work Health and Safety Regulations 2017

Legislation NSW: https://www.safework.nsw.gov.au/legal-obligations/legislative

Codes of Practice NSW: https://www.safework.nsw.gov.au/resource-library/lis codes-of ractions of Practice NSW: https://www.safework.nsw.gov.au/resource-library/lis codes-of-ractions-of-racti

#### **Northern Territory**

Work Health and Safety (National Uniform Legislation) Act 2011

Work Health and Safety (National Uniform Legislation) Regulation 2011

Legislation NT: https://worksafe.nt.gov.au/laws-and-compliance/worksafe.nt.gov.au/laws-and-compl

Codes of Practice NT: https://worksafe.nt.gov.au/f

#### South Australia

Work Health and Safety Act 2012 (SA)

Work Health and Safety Regulations 2012 (SA)

Legislation for SA: https://www.safework.sa.gov.au/resources/le

Codes of Practice for SA: https://www.safework.sa.gov.au/work\_aces/codes-of-practice#COPs

#### Tasmania

Work Health and Safety Act 2012

Work Health and Safety (Transitional and Consequential Provisions) Act 2012

Work Health and Safety Regulations 2012

Work Health and Safety (Transitional) Regulations 2012

Legislation for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/acts-and-regulations

Codes of Practice for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/codes-of-practice

Details of permits, licenses or access required by regulatory bodies (add or delete as required):

- Permits from local council
- Authorisation to commence work
- Any required documents.

#### Victoria

Occupational Health al. Safety Act

Occupational Health and affety gulations 2017

Legis on VIC: https://www.csafe.vic.gov.au/occupational-health-and-safety-act-and-

gulat

les on actice VI atps://www.worksafe.vic.gov.au/compliance-codes-and-codes-practice

#### Western Australia

Work Health and Safety Act 2020

Work Health and Safety Regulations 2022

Legislation Western Australia: <a href="https://www.commerce.wa.gov.au/worksafe/legislation">https://www.commerce.wa.gov.au/worksafe/legislation</a>

Codes of Practice WA: https://www.commerce.wa.gov.au/worksafe/codes-practice

#### Safe Work Australia Links

Law and Regulation (All States): https://www.safeworkaustralia.gov.au/law-and-regulation Model Codes of Practice: https://www.safeworkaustralia.gov.au/resources-publications/model-codes-of-practice

#### **Model Codes of Practice**

- Managing noise and preventing hearing loss at work
- Confined spaces
- Labelling of workplace hazardous chemicals
- Managing risks of hazardous chemicals in the workplace
- Welding processes
- First aid in the workplace
- Managing the risk of falls at workplaces
- Hazardous manual tasks
- Managing the risk of falls in housing construction
- Managing electrical risks in the workplace
- Demolition work
- Excavation work
- Work health and safety consultation, cooperation and coordination
- Managing the work environment and facilities
- How to manage work health and safety risks
- Managing risks of plant in the workplace
- Construction work





#### SIGNATORIES OF THE SAFE WORK METHOD STATEMENT

The signed and dated personnel listed below have cooperated in the consultation and development of this Safe Work Method Statement which has been approved by the Person/s Conducting a Business or Undertaking (PCBU). In signing this Safe Work Method Statement each individual acknowledges and confirms that they have read this SWMS in full, having raised any questions for items on this Safe Work Method Statement that require clarification, and confirms that they are competent, skilled and knowledgeable for the task assigned to them. Every person acknowledges that they have received the relevant training and qualifications where required, before carrying out any work contained in this Safe Work Method Statement. By signing this Safe Work Method Statement each individual agrees to work safely, to follow any safe work instructions which are provided, and agrees to use all Personal Protective Equipment where appropriate.

Worker Name	Signature	Date

#### SAFE WORK IN THE STATEMENT MONITORING AND REVIEW

The SWMS must be reviewed regularly to make sure it remains a fective of must be reviewed (and revised if necessary) if relevant control measures are revised. The view process should be carried out in consultation with workers (including contractors of the SWMS and their health and safety representatives who represented that work group at the workplace.

When the SWMS has been revised the PCBU mast ensure that advised that a revision has been made and how they can access the revised SWMS, including all persons who will need to change a work procedure or system as a rest of the review are advised of the changes in a way that will enable them to implement their duties and the involved in the work must be provided with the relevant information and instruction that will assist them to understand and implement the revised SWMS.

The SWMS must be monitored regularly for the effectiveness of ensuring hazard controls are effective in reducing the risk of incidents, keeping the workplace safe for all personnel. The person responsible for monitoring the effectiveness of the Safe Work Method Statement should employ a multi-faceted approach which includes but is not limited to:

- Spot Checks.
- 2. Consultation with workers, contractors and sub-contractors.
- Internal audits on a continual basis.

An approach of continuous improvement, promptly recording inconsistencies or deficiencies, followed up by immediate corrective action and consultation with all relevant personnel ensures that the PCBU is consistently developing ever-improving systems of safe work principles.

REVIEW NUMBER	1	2	3	4	5	6	7
NAME							
INITIALS							
DATE							





### SAFE WORK METHOD STATEMENT REVIEW CHECKLIST

This Safe Work Method Statement Review Checklist is to be followed and used upon initial development of the SWMS to help ensure that all steps have been adequately taken before work commences. Think of this document as an internal audit review checklist before commencing work, and may form part of a Toolbox Talk (safety meeting) and may be used as an opportunity for education and training.

ITEMS WHICH MUST BE INCLUDED IN THE SWMS	COMPLETED	COMMENTS
		•
The company details have been entered, including the project name and address.		
All relevant personnel consulted during the development of the SWMS.		
Name, signature, position and date signed of the person approving the SWMS.		
Specific personnel and qualifications, experience is noted in the SWMS.	7	
Provides a step-by-step process of tasks required to carry out the activity or task.		
Adequate risk assessment of any identified hazards has been completed.		
Foreseeable hazards are identified and documented for each step.		
Any hazards listed in any site risk assessments have been added to the SWMS		
SWMS initial risk (IR) column as well as residual risk (RR) column pleted.		
Check control measures added to the SWMS are the most effective selective.		
Responsible person is assigned and listed on the part the improvention control measures.		
Permit or licenses requirements specified, sur as Hot Work, Electric Work, Work at Heights etc.		
SWMS identifies plant and equipment to be us		
Details of inspection checks required for any equipment listed a noted on the SWMS.		
Describes any mandatory qualifications, experience, or skills required to perform the work.		
Applicable personal protective equipment is selected on the SWMS.		
Reflects and documents any legislative references and/or Australian Standards.		
Identifies any hazardous substances used with specific control measures in line with any SDS.		
REVIEWED BY	DATE REVIEWE	D
SIGNATURE	DATE COMPLETE	ED .