Replacement Of Spark P	lugs. SAFE WORK METH	OD STATEMENT (SWMS)						
TASK OF	R ACTIVITY: Replacement Of Spa	ark Plugs.						
Business Name:		ABN:	SWMS#					
Business Address:								
Contact Person:	Phone:	E ail:						
THIS SAFE WORK METHOD	STATEMENT IS APPROVED BY							
Under the Work Health and Safety Regulation (WHS Regulation), a person conducting a business or under the proposed work starts.								
Full Name:								
Signature:		Title:	Date:					
Details of the person(s) responsible for ensuring implementation, monitoring	ppliance the VMS a well as review	s and modifications of the SWMS.						
Full Name:		Title:	Phone:					
ALL PERSONNEL PARTICIPATING IN ANY ACTIVITY ON THIS MAN PHAVE THE FOLLOWING COMMUNICATED	NAME OF ALL RELEVANT PERSONNI EVELOPMENT AND APPROVAL OF	EL WHO HAVE BEEN CONSULTED AND CO THIS SWMS	DMMUNICATED TO IN THE					
Safety meetings or toolbox talks will be sched ed in according with a gislative requirements to first identify any site hazards, such to compare the compared those hazards and then to further take steps to either eliminate or contract each hazard.								
If an incident or a near miss occurs, all work must stop an ately. Depending on the severity of the incident, a meeting will be called with all workers to amend the SWMS if required. The meeting may also be an educational opportunity.								
Any changes made to the SWMS after an incident or a near miss must be approved by the Person Conducting Business or Undertaking and communicated to all relevant personnel.								
The SWMS must be kept and be available for inspection at least until the work is completed. Where a SWMS is revised, all versions should be kept. If a notifiable incident occurs in relation to which the SWMS relates, then the SWMS must be kept for at least two years from the occurrence of the notifiable incident.								



CLIENT OR PRINCIPAL	CONTRACTOR DETAILS
Client:	SCOPE OF WORKS
Project Name:	
Project Address:	
Project Manager:	
Contact Phone:	
Date SWMS supplied to Project Manager:	
ANY HIGH-RISK CONSTRUC	
☐ involves a risk of a person falling more than 2 meters	I is carried out on or near pressurised gas mains or piping
□ is carried out on a telecommunication tower	carried out on or near chemical, fuel or refrigerant lines
☐ involves demolition of an element of a structure that is load-bearing	□ is carried out on or near energised electrical installations or services
□ involves demolition of an element related to the physical integration of a superture	\square is carried out in an area that may have a contaminated or flammable atmosphere
□ involves, or is likely to involve, disturbing asb	☐ involves tilt-up or precast concrete
involves structural alteration or repair that quires terminary support to prevent collapse	☐ is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor
is carried out in or near a confined space	\Box is carried out in an area of a workplace where there is any movement of powered mobile plant
is carried out in/near a shaft or trench deeper that tunnel involving use of explosives	☐ is carried out in areas with artificial extremes of temperature.
☐ is carried out in or near water or other liquid that involves a risk of drowning.	☐ involves diving work.
ANY HIGH-RISK MACHINEF	RY OR EQUIPMENT NEARBY



	RISK MATRIX									
LIKELIHOOD	INSIGNIFICANT	MINOR	MODERATE	MAJOR	CATASTROPHIC	00005			HEIRARCHY OF CONTROLS	
ALMOST CERTAIN	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4 ACUTE	SCORE	ACTION		Elimination	
LIKELY	2 MODERATE	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4A ACUTE	DO NOT PROCE		Substitution	
POSSIBLE	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	4 ACUTE	3H HIGH	Review befor work starts.		Replace the hazard.	
UNLIKELY	1 LOW	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	2M MODERATE	Ensure control measures in place.		Isolate People from the hazard	
RARE	1 LOW	1 LOW	2 MODERATE	3 HIGH	3 HIGH	1L LOW	nitor and k⊾ records		Engineering Isolate the hazard.	
Notes on Hiera is the second m Controls by cha method.	LOW LOW MODERATE HIGH HIGH LOW Revecode Isolate the hazard. Notes on Hierarchy of Controls: Elimination methods are the most effective and preferre use in converting a hazard. Substitution is the second most effective method of controlling a hazard. Engineering by isolation is the virture ost environ the least effective. Administrative Change the work. Controls by changing the work is the fourth most effective method. PPE (Personal Protective Equipment). The least effective Fersonal Protective Equipment). The least effective PPE									

	PERS VAL TECTIVE EQUIPMENT (PPE) Select the appropriate PPE abo, suitable or the equipment used or the job task being performed (if applicable).										
FOOT PROTECTION	HAND PROTECTION	HEAD PROTECTION	HEARING CTION		R⊾ ⇒PIRATORY PROTECTION	FACE PROTECTION	HIGH-VIS CLOTHING	PROTECTIVE CLOTHING	FALL PROTECTION	SUN PROTECTION	HAIR/JEWELLERY SECURED
Other PPE Required:											
Permit or Licenses Requirements					Mandatory Qualifications and Training						



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
1. Preparation	Incorrect tools, unorganised workspace	ЗН	 Select the correct tools for the specific matrix and model of the vehicle to ensure compatibility. Regularly inspect tools for wear and damage replacit unem as needed to maintain safety standards. Use tool organisers, like trays or toolboxes, to use tools neatly arranged and within easy reach. Prepare a checklist of require tools before begin and the new to avoid unnecessary delays. Ensure all equipment coleane and free of oil or one substances that could cause slippage. Wear appropriate person porteous equipment out as gloves and safety glasses to prevent injuries. Clean able and tidy seriounding a new avoid hazards such as tripping over misplaced items. Clean able an obtaind parts to ensure quick and accurate identification during work. Security are any use objects that are not needed immediately to prevent accidents. Establish a usignate area for completed tasks to ensure a smooth workflow and organisation. Verify virkspan lighting is adequate to identify tools and vehicle components without strain. Man of an districted the work area if necessary to prevent unauthorised access and distractions. Inform team members of the ongoing task and workspace boundaries to promote awareness. Appoint a person responsible for maintaining order and responding swiftly to potential hazards. 	2M
2. Identifying plug condition	Debris in plug well, old or worn plugs	2М	 Ensure the vehicle is parked on a stable, flat surface with the handbrake applied to prevent unexpected movement. Wear appropriate personal protective equipment such as safety goggles and gloves to protect against accidental debris exposure or sharp edges. Use compressed air or a vacuum designed for automotive maintenance to clear any debris from the spark plug well prior to removal. Perform a visual inspection of the spark plug area with adequate lighting to identify and remove potential hazards. Disconnect the vehicle's battery before beginning work to avoid electrical risks. Apply a small amount of penetrating oil if spark plugs appear stuck, allowing it to penetrate for a few minutes before attempting removal. Use the correct type and size of spark plug socket and extension to avoid damaging plugs or surrounding components during removal. Inspect removed spark plugs immediately for signs of wear or damage such as carbon build-up, oil deposits, or eroded electrodes. Dispose of old spark plugs in accordance with local environmental regulations to prevent contamination. 	1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
			 Conduct a tool check before starting the task to ensure all necessary tools are available and in good condition. Refer to the vehicle manufacturer's service manufactor specifications and procedures particular to the make and model being serviced. Mark each spark plug lead and coil pack to insure that to y are reinstalled in their respective positions after inspection or replacement. 	
3. Removing Old Plugs	Risk of electric shock, damage to span plug thread		 Ensure the vehicle is turnet off and the keys are innoved from the ignition before beginning work to prevent accidental starting. Disconnect the beauty memory of the negative terminal first to eliminate the risk of electric shock. Use insulate tools specifically desired for a domotive work to minimise the risk of conducting electricity. Allow engine a negative equipment, including safety goggles and gloves, to protect against flying debris and ship of upponent. Inspect parking sockets and ratchets for insulation and proper condition before use to reduce elevated azards. Follow manufacturer's instructions and specifications to prevent damage to the spark plug threads aring removal. Use a thread chaser tool to clean and restore damaged spark plug threads in the cylinder head if necessary. Keep the work area clear of any flammable materials that could ignite from an electrical short or loose spark. Conduct a visual inspection for oil or moisture around the spark plug area, addressing leaks that may cause slipping or corrosion. Use a torque wrench for initial loosening, ensuring no excessive force is applied that might damage the thread. Provide appropriate training for workers on the safe removal of spark plugs and the recognition of potential threading issues. 	2М
4. Inspecting old plugs	Sharp edges, debris on plug	2M		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
5. Preparing New Plugs	Incorrect gap size, sharp edges	ЗН		2M





Version 2.5

Date of Issue:





Version 2.5



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
9. Troubleshooting Issues	Damage to vehicle components, misfire during driving	44		2M
10. Cleaning up	Slips and trips, hazardous waste disposal	2M		1L
Version 2.5	Authorised by		Review # Date of Issue: Review Date:	9



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR				
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK				



EMERGENCY RESPONSE – CALL 000 FOR EMERGENCIES

Ensure to have an Emergency Management Plan in place as well as adequate numbers of trained first aid staff with easy access to fully stocked first aid kits, rescue equipment, material safety data sheets, adequate access to emergency communication equipment and fire-fighting equipment suitable for all classes of fire and ignition sources.

LEGISLATIVE REFI	
RELEVANT LEGISLATION AND CODES OF PRACTICE. DELETE THE LEGISLA	TIVE REFERENCES ANY STATE AT ARE NOT APPLICABLE
Queensland & Australian Capital Territory Work Health and Safety Act 2011 Work Health and Safety Regulations 2011 Legislation QLD: <u>https://www.worksafe.qld.gov.au/laws-and-compliance/work-health-and-safety-laws</u> Codes of Practice QLD: <u>https://www.worksafe.qld.gov.au/laws-and-compliance/codes-of-practice</u> Legislation ACT: <u>https://www.worksafe.act.gov.au/laws-and-compliance/codes-of-practice</u> Codes of Practice ACT: <u>https://www.worksafe.act.gov.au/laws-and-compliance/codes-of-practice</u>	Victoria Occupational Health and Safety Act and Occupational Health and Safety Act and Legis from VIC: <u>https://www.worksafe.vic.gov.au/occupational-health-and-safety-act-and- rular s</u> Unles of wractice VIC <u>attps://www.worksafe.vic.gov.au/compliance-codes-and-codes-practice</u>
New South Wales Work Health and Safety Act 2011 Work Health and Safety Regulations 2017 Legislation NSW: https://www.safework.nsw.gov.au/legal-obligations/legislati Codes of Practice NSW: https://www.safework.nsw.gov.au/legal-obligations/legislati	Western Australia Work Health and Safety Act 2020 Work Health and Safety Regulations 2022 Legislation Western Australia: <u>https://www.commerce.wa.gov.au/worksafe/legislation</u> Codes of Practice WA: <u>https://www.commerce.wa.gov.au/worksafe/codes-practice</u>
Northern Territory Work Health and Safety (National Uniform Legislation) Act 2011 Work Health and Safety (National Uniform Legislation) Regulation 2011 Legislation NT: https://worksafe.nt.gov.au/laws-and-compliance/worplace-serve-laws Codes of Practice NT: https://worksafe.nt.gov.au/factored-resource t/corplace-serve-laws Codes of Practice NT: https://worksafe.nt.gov.au/factored-resource t/corplace-serve-laws	Safe Work Australia Links Law and Regulation (All States): <u>https://www.safeworkaustralia.gov.au/law-and-regulation</u> Model Codes of Practice: <u>https://www.safeworkaustralia.gov.au/resources-publications/model- codes-of-practice</u>
South Australia Work Health and Safety Act 2012 (SA) Work Health and Safety Regulations 2012 (SA) Legislation for SA: <u>https://www.safework.sa.gov.au/resources/legislation</u> Codes of Practice for SA: <u>https://www.safework.sa.gov.au/work_saces/codes-of-practice#COPs</u>	Model Codes of Practice Managing noise and preventing hearing loss at work Confined spaces Labelling of workplace hazardous chemicals Managing risks of hazardous chemicals in the workplace Welding processes
Tasmania Work Health and Safety Act 2012 Work Health and Safety (Transitional and Consequential Provisions) Act 2012 Work Health and Safety Regulations 2012 Work Health and Safety (Transitional) Regulations 2012 Legislation for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/acts-and-regulations Codes of Practice for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/codes-of-practice	 First aid in the workplace Managing the risk of falls at workplaces Hazardous manual tasks Managing the risk of falls in housing construction Managing electrical risks in the workplace Demolition work Excavation work
Details of permits, licenses or access required by regulatory bodies (add or delete as required): - Permits from local council - Authorisation to commence work - Any required documents.	 Managing the work environment and facilities How to manage work health and safety risks Managing risks of plant in the workplace Construction work



SIGNATORIES OF THE SAFE WORK METHOD STATEMENT

The signed and dated personnel listed below have cooperated in the consultation and development of this Safe Work Method Statement which has been approved by the Person/s Conducting a Business or Undertaking (PCBU). In signing this Safe Work Method Statement each individual acknowledges and confirms that they have read this SWMS in full, having raised any questions for items on this Safe Work Method Statement that require clarification, and confirms that they are competent, skilled and knowledgeable for the task assigned to them. Every person acknowledges that they have received the relevant training and gualifications where required, before carrying out any work contained in this Safe Work Method Statement. By signing this Safe Work Method Statement each individual agrees to work safely, to follow any safe work instructions which are provided, and agrees to use all Personal Protective Equipment where appropriate.

Worker Name	Signature	Date

SAFE WORK N THE ST ATEM ANT MONITORING AND REVIEW

d must reviewed (and

hav be sted by the operation

should be carried out in

The SWMS must be reviewed regularly to make sure it remains fective revised if necessary) if relevant control measures are revised. The viewn consultation with workers (including contractors htractors Vb of the SWMS and their health and safety representatives who represented that work group at the workplace.

When the SWMS has been revised the PCBU must ensure that persons involved with the work are advised that a revision has been made and how they can acces he revised SWMS, including all persons who will need to change a work procedure or system as a region of the review are advised of the changes in a way that will enable them to implement their duties antly with the revised SWMS. All workers that will be involved in the work must be provided with the relevant information and instruction that will assist them to understand and implement the revised SWMS.

The SWMS must be monitored regularly for the effectiveness of ensuring hazard controls are effective in reducing the risk of incidents, keeping the workplace safe for all personnel. The person responsible for monitoring the effectiveness of the Safe Work Method Statement should employ a multi-faceted approach which includes but is not limited to:

- 1. Spot Checks.
- 2. Consultation with workers, contractors and sub-contractors.
- 3. Internal audits on a continual basis.

An approach of continuous improvement, promptly recording inconsistencies or deficiencies. followed up by immediate corrective action and consultation with all relevant personnel ensures that the PCBU is consistently developing ever-improving systems of safe work principles.

REVIEW NUMBER	1	2	3	4	5	6	7
NAME							
INITIALS							
DATE							



SAFE WORK METHOD STATEMENT REVIEW CHECKLIST

This Safe Work Method Statement Review Checklist is to be followed and used upon initial development of the SWMS to help ensure that all steps have been adequately taken before work commences. Think of this document as an internal audit review checklist before commencing work, and may form part of a Toolbox Talk (safety meeting) and may be used as an opportunity for education and training.

ITEMS WHICH MUST BE INCLUDED IN THE SWMS		COMPLETED	COMMENTS	
The company details have been entered, including the project name and address.				
All relevant personnel consulted during the development of the SWMS.				
Name, signature, position and date signed of the person approving the SWMS.				
Specific personnel and qualifications, experience is noted in the SWMS.		7		
Provides a step-by-step process of tasks required to carry out the activity or task.				
Adequate risk assessment of any identified hazards has been completed.		\boxtimes		
Foreseeable hazards are identified and documented for each step.		\boxtimes		
Any hazards listed in any site risk assessments have been added to the SWMS		\boxtimes		
SWMS initial risk (IR) column as well as residual risk (RR) column completed.		\boxtimes		
Check control measures added to the SWMS are the most effective selectives		\boxtimes		
Responsible person is assigned and listed on the property of the improvement of measures.		\boxtimes		
Permit or licenses requirements specified, sur as Hot Work, Electric Work, Work at Heights etc.		\boxtimes		
SWMS identifies plant and equipment to be use		\boxtimes		
Details of inspection checks required for any equipment listed photoe on the SWMS.		\boxtimes		
Describes any mandatory qualifications, experience, using or skills required to perform the work.		\boxtimes		
Applicable personal protective equipment is selected on the SWMS.		\boxtimes		
Reflects and documents any legislative references and/or Australian Standards.		\boxtimes		
Identifies any hazardous substances used with specific control measures in line with any SDS.		\boxtimes		
REVIEWED BY		DATE REVIEWED		
SIGNATURE		DATE CO	IPLETED	