



Roof Plumbing and Gutt	ering SAFE WORK METH	OD STATEMENT (SWMS)	
TASK OF	R ACTIVITY: Roof Plumbing and	Guttering	
Business Name:		ABN:	SWMS#
Business Address:			
Contact Person:	Phone:	E ail:	
THIS SAFE WORK METHOD	STATEMENT IS APPROVED BY	THE PCL OF THE ROJECT	
Under the Work Health and Safety Regulation (WHS Regulation), a person conduct the proposed work starts.	cting a business or undo	required to en. sthat a safe work method s	statement (SWMS) is prepared before
Full Name:			
Signature:		Title:	Date:
Details of the person(s) responsible for ensuring implementation, monitoring	roliance the VMS a vell as review	s and modifications of the SWMS.	
Full Name:		Title:	Phone:
ALL PERSONNEL PARTICIPATING IN ANY ACTIVITY ON THIS S /MS M HAVE THE FOLLOWING COMMUNICATED	NAL 2 OF ALL RELEVANT PERSONN EVELOPMENT AND APPROVAL OF	EL WHO HAVE BEEN CONSULTED AND CO THIS SWMS	OMMUNICATED TO IN THE
Safety meetings or toolbox talks will be scheded in accomply with gislative requirements to first identify any site hazards, complying those hazards and then to further take steps to either eliminate or continuous each hazard.			
If an incident or a near miss occurs, all work must sto, quately. Depending on the severity of the incident, a meeting will be called with all workers to amend the SWMS if required. The meeting may also be an educational opportunity.			
Any changes made to the SWMS after an incident or a near miss must be approved by the Person Conducting Business or Undertaking and communicated to all relevant personnel.			
The SWMS must be kept and be available for inspection at least until the work is completed. Where a SWMS is revised, all versions should be kept. If a notifiable incident occurs in relation to which the SWMS relates, then the SWMS must be kept for at least two years from the occurrence of the notifiable incident.			

Version 2.5 Authorised by Review # Date of Issue: Review Date: 1





CLIENT OR PRINCIPAL	CONTRACTOR DETAILS
Client:	SCOPE OF WORKS
Project Name:	
Project Address:	
Project Manager:	
Contact Phone:	
Date SWMS supplied to Project Manager:	
ANY HIGH-RISK CONSTRUCTOR	ON WO K BEIN O KRIED OUT
☐ involves a risk of a person falling more than 2 meters	☐ is carried out on or near pressurised gas mains or piping
☐ is carried out on a telecommunication tower	carried out on or near chemical, fuel or refrigerant lines
☐ involves demolition of an element of a structure that is load-bearing	☐ is carried out on or near energised electrical installations or services
☐ involves demolition of an element related to the physical integration of a ructure	☐ is carried out in an area that may have a contaminated or flammable atmosphere
☐ involves, or is likely to involve, disturbing asb	☐ involves tilt-up or precast concrete
☐ involves structural alteration or repair that — quires term — ov sup — rt to prevent collapse	☐ is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor
is carried out in or near a confined space	☐ is carried out in an area of a workplace where there is any movement of powered mobile plant
☐ is carried out in/near a shaft or trench deeper tha tunnel involving use of explosives	☐ is carried out in areas with artificial extremes of temperature.
☐ is carried out in or near water or other liquid that involves a risk of drowning.	☐ involves diving work.
ANY HIGH-RISK MACHINER	RY OR EQUIPMENT NEARBY

Version 2.5 Authorised by Review # Date of Issue: Review Date: 2



RISK MATRIX											
LIKELIHOOD	INSIGNIFICANT	MINOR	MODERATE	MAJOR	CATASTROPHIC	SCORE	ACTION		HEIRARCHY OF CONTROLS		
ALMOST CERTAIN	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4 ACUTE	SCORE	ACTION		Elimination Remove the hazard.		
LIKELY	2 MODERATE	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4A ACUTE	DO NOT PROCE		Substitution		
POSSIBLE	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	4 ACUTE	3H HIGH	Review befor work starts.		Replace the hazard.		
UNLIKELY	1 LOW	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	2M MODERATE	Ensure control measures in place.		Isolate People from the hazard		
RARE	1 LOW	1 LOW	2 MODERATE	3 HIGH	3 HIGH	1L LOW	nitor and		Engineering Isolate the hazard.		
is the second m	Notes on Hierarchy of Controls: Elimination methods are the most effective and preferrement of controls by changing the work is the fourth most effective method. PPE (Personal Protective Equ. ment). The least effective shows the second most effective method of controlling a hazard. Protective Equ. ment). The least effective method of controlling a hazard. Protective Equ. ment). The least effective method of controlling a hazard. Protective Equ. ment). The least effective method of controlling a hazard. Protective Equ. ment). The least effective method of controlling a hazard. Protective Equ. ment). The least effective method of controlling a hazard. Protective Equ. ment). The least effective method of controlling a hazard. Protective Equ. ment).										

				PERS		TIVE EQUIPM					
		Select the app	ropriate PPL	abo. ~uitab	ic or the equip	oment used or	the job task	being perform	ned (if applica	able).	
FOOT PROTECTION	HAND PROTECTION	HEAD PROTECTION	ARING STION	F' CTIO	RL PIRATORY PROTECTION	FACE PROTECTION	HIGH-VIS CLOTHING	PROTECTIVE CLOTHING	FALL PROTECTION	SUN PROTECTION	HAIR/JEWELLERY SECURED
Other PPE Required:											
	Pe	ermit or Licen	ses Requirem	ents			Mandatory Qualifications and Training				



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
Site assessment and planning	Unidentified overhead services Unmarked underground services Unstable ground conditions Unauthorised public access Inadequate access and egress Adverse weather conditions	ЗН	 Review current site plans, Dial Before Young information, and service drawings before starting any roof plumbing or guttering work Walk the site and inspect ground conditions a work areas, vehicle standing zones, and access ways; relocate work if ground is soft, eroded, or verlogged Identify and mark exclusion are shelw roof edgrand work areas using barricades and warning signage to so note works from the public Confirm safe cless and cress are test to roof fiel, including ladders, scaffolds, or stair towers, and ensure they inply with AS IZS 18, and field applicable Check weather precasor wind, rain, sorms, or extreme heat and reschedule roof work if conditions excellent a field in company procedures Estal she emerging plan covering falls, electric shock, and severe weather events, and brief all workers in a municular methods and muster points Verify that all brakers hold relevant High Risk Work Licences or competencies for scaffolds, EWPs, or pictory brackers in the principal contractor 	2M
Set up access and fall protection	Falls from unprotected edges Ladder instability Scaffold collapse Falling objects from height Incorrect anchor installation	4A	Install edge protection or scaffolding with guardrails, midrails, and toeboards to AS/NZS 1576 and AS/NZS 4576 before commencing roof plumbing work • Erect ladders on firm, level ground at a 4:1 angle, secure them at top and bottom, and extend at least 1 m above the landing as per AS/NZS 1892 • Have a competent person inspect and tag all scaffolds, temporary stairs, and platforms before use and at required intervals • Fit debris mesh, toeboards, and brick guards where people may pass beneath roof edges to prevent guttering, tools, or offcuts from falling • Select engineered roof anchors or static lines rated to AS/NZS 5532 and install them as per manufacturer instructions prior to connecting harnesses • Require workers using harness-based systems to complete a documented rescue plan and to carry suitable fall arrest and retrieval equipment • Use portable guardrails or temporary roof edge barriers where permanent scaffold cannot be installed, ensuring they are rated to withstand expected loads • DO NOT use gutters, downpipes, or lightweight fascia as anchorage or as a step or support surface at any time	2M
Manual handling and material delivery	Musculoskeletal strain from lifting	3H		2M



HAZARDS THAT MAY ARISE h injury from shifting loads erations from sharp edges entrolled load movement during ng	INITIAL RISK	Plan delivery locations so gutter lengths, fascia, soffits, and flashing can be unloaded as close as practicable to the installation area to eliminate long carries Use mechanical aids such as material hoists, crass, or EWPs to lift long gutter sections and bundles of fascia to roof level instead of carrying by ladde Team-lift long or awkward components are agree on crass nands before moving; nominate a single spotter to coordinate movement Wear cut-resistant gloves compliant with AS/N 2161 and long sleeves when handling metal guttering, flashings, and roof plumbing amponents Store materials on flat stable apports away from and secure stacks with chocks or straps to prevent rolling or crass. Lift from when neight when possib avoid for sung while carrying, and take regular micro-breaks during repetitive handing tasks Use approte and sharp metal sections during lifting with slings and ensure all slings and lifting gear as a hin WL and inspected before use DO N T carv long after sections up ladders; use rope systems, hoists, or EWPs for all long or heavy items	RESIDUAL RISK
erations from sharp edges ontrolled load movement during		 Use mechanical aids such as material hoists, cracks, or EWPs to lift long gutter sections and bundles of fascia to roof level instead of carrying by ladde Team-lift long or awkward components are agree on commands before moving; nominate a single spotter to coordinate movement Wear cut-resistant gloves compliant with AS/N 2161 and long sleeves when handling metal guttering, flashings, and roof plumbing imponents Store materials on flat stable imports away from a and secure stacks with chocks or straps to prevent rolling or rooms Lift from worm neight whe possible avoid for sung while carrying, and take regular micro-breaks during repetitive handing tasks Use a protein of sharp metal sections during lifting with slings and ensure all slings and lifting gear a protein of sharp metal sections up ladders; use rope systems, hoists, or EWPs for all long or heavy 	
ontrolled load movement during		fascia to roof level instead of carrying by ladde Team-lift long or awkward components are agree on commands before moving; nominate a single spotter to coordinate movement Wear cut-resistant gloves compliant with AS/N 2161 and long sleeves when handling metal guttering, flashings, and roof plumbings imponents Store materials on flat stable imports away from a and secure stacks with chocks or straps to prevent rolling or comply Lift from work neight when possibly avoid for sung while carrying, and take regular micro-breaks during repetitive handing tasks Use the protein of sharp metal sections during lifting with slings and ensure all slings and lifting gear a significant of the sections up ladders; use rope systems, hoists, or EWPs for all long or heavy	
y .		spotter to coordinate movement • Wear cut-resistant gloves compliant with AS/N 2161 and long sleeves when handling metal guttering, flashings, and roof plumbing imponents • Store materials on flat stable imports away from a and secure stacks with chocks or straps to prevent rolling or a stable imports away from a and secure stacks with chocks or straps to prevent rolling or a stable imports away from a and secure stacks with chocks or straps to prevent rolling or a stable imports away from a and secure stacks with chocks or straps to prevent rolling or a stable imports away from a and secure stacks with chocks or straps to prevent rolling or a stable imports away from a and secure stacks with chocks or straps to prevent rolling or a stable imports away from a and secure stacks with chocks or straps to prevent rolling or a stable imports away from a stack with chocks or straps to prevent rolling or a stable imports away from a stack with chocks or straps to prevent rolling or a stable imports away from a stack with chocks or straps to prevent rolling or a stack with chocks or straps to prevent rolling or a stack with chocks or straps to prevent rolling or a stack with chocks or straps to prevent rolling or a stack with chocks or straps to prevent rolling or a stack with chocks or straps to prevent rolling or a stack with chocks or straps to prevent rolling or a stack with chocks or straps to prevent rolling or a stack with chocks or straps to prevent rolling or a stack with chocks or straps to prevent rolling or a stack with chocks or straps to prevent rolling or a stack with chocks or straps to prevent rolling or a stack with chocks or straps to prevent rolling or a stack with chocks or straps to prevent rolling or a stack with chocks or straps to prevent rolling or a stack with chocks or straps to prevent rolling or a stack with chocks or straps to prevent rolling or a stack with chocks or straps to prevent rolling or a stack with chocks or straps to prevent rolling or a stack with chocks or straps to preven	
		flashings, and roof plumbing imponents • Store materials on flat stable imports away from a and secure stacks with chocks or straps to prevent rolling or comp • Lift from workleight whe possible avoid fooding while carrying, and take regular micro-breaks during repetitive handing tasks • Use the protein of sharp metal sections during lifting with slings and ensure all slings and lifting gear a shain William of inspected before use • DO No Tick villing after sections up ladders; use rope systems, hoists, or EWPs for all long or heavy	
		• Lift from worneight whe possib avoid oung while carrying, and take regular micro-breaks during repetitive hancing tasks • Use a prote or an sharp metal sections during lifting with slings and ensure all slings and lifting gear a sharp in ML and inspected before use • DO N T cov long after sections up ladders; use rope systems, hoists, or EWPs for all long or heavy	
		repetitive han any tasks • Use the protein of sharp metal sections during lifting with slings and ensure all slings and lifting gear and hin WL and inspected before use • DO N T conviously ter sections up ladders; use rope systems, hoists, or EWPs for all long or heavy	
		gear a hin WL and inspected before use • DO N T cov long ter sections up ladders; use rope systems, hoists, or EWPs for all long or heavy	
through frage roofing hazards from roor tixtures on wet or dusty surfaces of balance on steep proof eact with overhead powerlines	4A		2M
while removing guttering ng gutter sections and debris	3H		2M
ha or a	azards from roor rixtures in wet or dusty surfaces of balance on steep pulsar ct with overhead powerlines while removing guttering ig gutter sections and debris	Azards from roor lixtures In wet or dusty surfaces If balance on steep proof In with overhead powerlines While removing guttering If gutter sections and debris 3H	azards from roor rixtures n wet or dusty surfaces of balance on steep proof ct with overhead powerlines while removing guttering



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
	Exposure to asbestos containing materials			
	Hand tool injuries			
	Collapse of unsuported fascia			
	• Falling sections c			1
Iter fascia and soffits	Exposure to dust and fibres	3H		2M
	Nail and screw punctur injurie			
	Contact with concealed wiring			
	Falls from working at height			
stall gutter supports	Struck by dropped tools or brackets			
nd brackets	Incorrect bracket spacing	3H		1L
	Contact with live electrical cables			



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
Cut and prepare gutter sections	Lacerations from sharp metal edges Eye injury from flying swarf Noise from cutting to Inhalation of metal or fibre dust Electric shock from power	21		2M
Install and fix roof gutters	Falls while affixing gutters Finger crush between gutter and fascia Strain from holding awkward sections Incorrect fall causing overflow Falling sections during fixing	4A		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
Install downpipes and secure rainwater pipes	Falls installing downpipes Impact from swinging pipe lengths Drilling into concealed services Water discharge near electricals Ladder overreach	ЗН		1L
Install roof flashings and valleys	 Falls along roof valleys Cuts from flashing edges Lead exposure from moulding Heat stress on exposed roofs Incorrect weatherproofing 	ЗН		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
Seal gutter joints and check stability	Falls when inspecting gutters Exposure to sealant vapours Failure of gutter joints Overfilling causing overflow Allergic reaction to sealants	ЗН		1L
Manage rainfall and weather during works	Slip on wet roof surfaces Uncontrolled water ingress Sudden storms or high winds Electrical hazards from wet tools Floating debris blocking outlets	3H		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
Clean-up, waste handling and final inspection	Trips from leftover materials Cuts from sharp offcuts Exposure to lead or sealant residues Unstable stacked waste Undetected installation defects	2M		1L



EMERGENCY RESPONSE - CALL 000 FOR EMERGENCIES

Ensure to have an Emergency Management Plan in place as well as adequate numbers of trained first aid staff with easy access to fully stocked first aid kits, rescue equipment, material safety data sheets, adequate access to emergency communication equipment and fire-fighting equipment suitable for all classes of fire and ignition sources.

LEGISLATIVE REFERENCES

RELEVANT LEGISLATION AND CODES OF PRACTICE. DELETE THE LEGISLATIVE REFERENCES. ANY STATE AT ARE NOT APPLICABLE.

Queensland & Australian Capital Territory

Work Health and Safety Act 2011

Work Health and Safety Regulations 2011

Legislation QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/work-health-and-safety-laws Codes of Practice QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/codes-of-practice

Legislation ACT: https://www.worksafe.act.gov.au/laws-and-compliance/acts-and-regulations
Codes of Practice ACT: https://www.worksafe.act.gov.au/laws-and-compliance/codes-of-practice

New South Wales

Work Health and Safety Act 2011

Work Health and Safety Regulations 2025

Legislation NSW: https://www.safework.nsw.gov.au/legal-obligations/legislations/

Codes of Practice NSW: https://www.safework.nsw.gov.au/resource-library/lis

Northern Territory

Work Health and Safety (National Uniform Legislation) Act 2011

Work Health and Safety (National Uniform Legislation) Regulation 201

Codes of Practice NT: https://worksafe.nt.gov.au/f

South Australia

Work Health and Safety Act 2012 (SA)

Work Health and Safety Regulations 2012 (SA)

Legislation for SA: https://www.safework.sa.gov.au/resources/le__lation

Codes of Practice for SA: https://www.safework.sa.gov.au/wor/ aces/codes-of-practice#COPs

Tasmania

Work Health and Safety Act 2012

Work Health and Safety (Transitional and Consequential Provisions) Act 2012

Work Health and Safety Regulations 2012

Work Health and Safety (Transitional) Regulations 2012

Legislation for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/acts-and-regulations

Codes of Practice for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/codes-of-practice

Details of permits, licenses or access required by regulatory bodies (add or delete as required):

- Permits from local council
- Authorisation to commence work
- Any required documents.

Victoria

Or pational Health a. Safety Act J4

Occational Health and afety gulations 2017

Legis on VIC: https://www.safe.vic.gov.au/occupational-health-and-safety-act-and-

gulat

tes of actice VIC attps://www.worksafe.vic.gov.au/compliance-codes-and-codes-practice

Western Australia

Work Health and Safety Act 2020

Work Health and Safety Regulations 2022

Legislation Western Australia: https://www.commerce.wa.gov.au/worksafe/legislation Codes of Practice WA: https://www.commerce.wa.gov.au/worksafe/codes-practice

Safe Work Australia Links

Law and Regulation (All States): https://www.safeworkaustralia.gov.au/law-and-regulation Model Codes of Practice: https://www.safeworkaustralia.gov.au/resources-publications/model-codes-of-practice

Model Codes of Practice

- Managing noise and preventing hearing loss at work
- Confined spaces
- Labelling of workplace hazardous chemicals
- Managing risks of hazardous chemicals in the workplace
- Welding processes
- First aid in the workplace
- Managing the risk of falls at workplaces
- Hazardous manual tasks
- Managing the risk of falls in housing construction
- Managing electrical risks in the workplace
- Demolition work
- Excavation work
- Work health and safety consultation, cooperation and coordination
- Managing the work environment and facilities
- How to manage work health and safety risks
- Managing risks of plant in the workplace
- Construction work





SIGNATORIES OF THE SAFE WORK METHOD STATEMENT

The signed and dated personnel listed below have cooperated in the consultation and development of this Safe Work Method Statement which has been approved by the Person/s Conducting a Business or Undertaking (PCBU). In signing this Safe Work Method Statement each individual acknowledges and confirms that they have read this SWMS in full, having raised any questions for items on this Safe Work Method Statement that require clarification, and confirms that they are competent, skilled and knowledgeable for the task assigned to them. Every person acknowledges that they have received the relevant training and qualifications where required, before carrying out any work contained in this Safe Work Method Statement. By signing this Safe Work Method Statement each individual agrees to work safely, to follow any safe work instructions which are provided, and agrees to use all Personal Protective Equipment where appropriate.

Worker Name	Signature	Date

SAFE WORK N. THE STATEMENT MONITORING AND REVIEW

The SWMS must be reviewed regularly to make sure it remains fective of must be reviewed (and revised if necessary) if relevant control measures are rovised. The view respectively should be carried out in consultation with workers (including contractors as a sub-intractors of the SWMS and their health and safety representatives who represented that work group at the workplace.

When the SWMS has been revised the PCBU must ensure that advised that a revision has been made and how they can access the revised SWMS, including all persons who will need to change a work procedure or system as a rest of the review are advised of the changes in a way that will enable them to implement their duties and the revised SWMS. All workers that will be involved in the work must be provided with the relevant information and instruction that will assist them to understand and implement the revised SWMS.

The SWMS must be monitored regularly for the effectiveness of ensuring hazard controls are effective in reducing the risk of incidents, keeping the workplace safe for all personnel. The person responsible for monitoring the effectiveness of the Safe Work Method Statement should employ a multi-faceted approach which includes but is not limited to:

- Spot Checks.
- 2. Consultation with workers, contractors and sub-contractors.
- 3. Internal audits on a continual basis.

An approach of continuous improvement, promptly recording inconsistencies or deficiencies, followed up by immediate corrective action and consultation with all relevant personnel ensures that the PCBU is consistently developing ever-improving systems of safe work principles.

REVIEW NUMBER	1	2	3	4	5	6	7
NAME							
INITIALS							
DATE							

Version 2.5 Authorised by Review # Date of Issue: Review Date: 12





SAFE WORK METHOD STATEMENT REVIEW CHECKLIST

This Safe Work Method Statement Review Checklist is to be followed and used upon initial development of the SWMS to help ensure that all steps have been adequately taken before work commences. Think of this document as an internal audit review checklist before commencing work, and may form part of a Toolbox Talk (safety meeting) and may be used as an opportunity for education and training.

ITEMS WHICH MUST BE INCLUDED IN THE SWMS	COMPLETED	COMMENTS
The company details have been entered, including the project name and address.		
All relevant personnel consulted during the development of the SWMS.		
Name, signature, position and date signed of the person approving the SWMS.		
Specific personnel and qualifications, experience is noted in the SWMS.	7	
Provides a step-by-step process of tasks required to carry out the activity or task.	k	
Adequate risk assessment of any identified hazards has been completed.	\boxtimes	
Foreseeable hazards are identified and documented for each step.	\boxtimes	
Any hazards listed in any site risk assessments have been added to the SWMS		
SWMS initial risk (IR) column as well as residual risk (RR) colum mpleted.	\boxtimes	
Check control measures added to the SWMS are the most effective selections.	\boxtimes	
Responsible person is assigned and listed on the part of the important of	\boxtimes	
Permit or licenses requirements specified, sur as Hot Work, Electric Work, Work at Heights etc.	\boxtimes	
SWMS identifies plant and equipment to be use	\boxtimes	
Details of inspection checks required for any equipment listed an onthe SWMS.	\boxtimes	
Describes any mandatory qualifications, experience, use or skills required to perform the work.	\boxtimes	
Applicable personal protective equipment is selected on the SWMS.		
Reflects and documents any legislative references and/or Australian Standards.	\boxtimes	
Identifies any hazardous substances used with specific control measures in line with any SDS.	\boxtimes	
REVIEWED BY	DATE REV	/IEWED
SIGNATURE	DATE COM	PLETED