



| Snib Lock Mechanism Repair Or  | Replacement   SAFE WOR                                       | K METHOD STATEMENT (SV                         | VMS)                                |
|--|--|--|-------------------------------------|
| TASK OR ACTIVI   | TY: Snib Lock Mechanism Repai                                | r Or Replacement                               |                                     |
| Business Name:   |  | ABN:   | SWMS#                               |
| Business Address:  |  |  |                                     |
| Contact Person:  | Phone:   | E fil:   |                                     |
|  |  |  |                                     |
| THIS SAFE WORK METHOD  | STATEMENT IS APPROVED BY                                     | THE PCL OF THE ROJECT                          |                                     |
| Under the Work Health and Safety Regulation (WHS Regulation), a person conduct the proposed work starts.   | cting a business or under the (PC 1) is                      | required to en that a safe work method s       | statement (SWMS) is prepared before |
| Full Name:   |  |  |                                     |
| Signature:   |  | Title:   | Date:                               |
| Details of the person(s) responsible for ensuring implementation, monitoring   | apliance the VMS a well as review                            | s and modifications of the SWMS.               |                                     |
| Full Name:   |  | Title:   | Phone:                              |
| ALL PERSONNEL PARTICIPATING IN ANY ACTIVITY ON THIS S /MS M HAVE THE FOLLOWING COMMUNICATED  | NA, 2 OF ALL RELEVANT PERSONNI<br>EVELOPMENT AND APPROVAL OF | EL WHO HAVE BEEN CONSULTED AND CO<br>THIS SWMS | OMMUNICATED TO IN THE               |
| Safety meetings or toolbox talks will be sched and in account with a gislative requirements to first identify any site hazards, hazards and then to further take steps to either eliminate or continuous each hazard.  |  |  |                                     |
| If an incident or a near miss occurs, all work must sto, an atately. Depending on the severity of the incident, a meeting will be called with all workers to amend the SWMS if required. The meeting may also be an educational opportunity.   |  |  |                                     |
| Any changes made to the SWMS after an incident or a near miss must be approved by the Person Conducting Business or Undertaking and communicated to all relevant personnel.  |  |  |                                     |
| The SWMS must be kept and be available for inspection at least until the work is completed. Where a SWMS is revised, all versions should be kept. If a notifiable incident occurs in relation to which the SWMS relates, then the SWMS must be kept for at least two years from the occurrence of the notifiable incident. |  |  |                                     |





| CLIENT OR PRINCIPAL  | CONTRACTOR DETAILS  |
|--|---|
| Client:  | SCOPE OF WORKS  |
| Project Name:  |   |
| Project Address:   |   |
| Project Manager:   |   |
| Contact Phone:   |   |
| Date SWMS supplied to Project Manager:   |   |
| ANY HIGH BIOK CONSTRUCTOR  | NAME OF THE POLIT   |
| ANY HIGH-RISK CONSTRUCTOR  | N WC & BEIN C ARIED OUT   |
| ☐ involves a risk of a person falling more than 2 meters                                     | is carried out on or near pressurised gas mains or piping                                       |
| ☐ is carried out on a telecommunication tower  | carried out on or near chemical, fuel or refrigerant lines                                      |
| ☐ involves demolition of an element of a structure that is load-bearing                      | $\square$ is carried out on or near energised electrical installations or services              |
| ☐ involves demolition of an element related to the physical integral of a functure           | ☐ is carried out in an area that may have a contaminated or flammable atmosphere                |
| ☐ involves, or is likely to involve, disturbing asb  | ☐ involves tilt-up or precast concrete  |
| ☐ involves structural alteration or repair that —quires term — v sup —rt to prevent collapse | ☐ is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor |
| ☐ is carried out in or near a confined space   | ☐ is carried out in an area of a workplace where there is any movement of powered mobile plant  |
| ☐ is carried out in/near a shaft or trench deeper that. tunnel involving use of explosives   | ☐ is carried out in areas with artificial extremes of temperature.                              |
| $\square$ is carried out in or near water or other liquid that involves a risk of drowning.  | ☐ involves diving work.   |
| ANY HIGH-RISK MACHINER   | Y OR EQUIPMENT NEARBY   |
|  |   |
|  |   |
|  |   |



| RISK MATRIX       |  |                    |                 |                  |                    |                |   |         |                                      |  |
|-------------------|--|--------------------|-----------------|------------------|--------------------|----------------|---|---------|--------------------------------------|--|
| LIKELIHOOD        | INSIGNIFICANT  | MINOR              | MODERATE        | MAJOR            | CATASTROPHIC       | SCORE          | ACTION  | HEI     | RARCHY OF CONTROLS                   |  |
| ALMOST<br>CERTAIN | 3<br>HIGH  | 3<br>HIGH          | 4<br>ACUTE      | 4<br>ACUTE       | 4<br>ACUTE         | SCORE          | ACTION  |         | Elimination Remove the hazard.       |  |
| LIKELY            | 2<br>MODERATE  | 3<br>HIGH          | 3<br>HIGH       | 4<br>ACUTE       | 4<br>ACUTE         | 4A<br>ACUTE    | DO NOT<br>PROCE                                 |         | Substitution                         |  |
| POSSIBLE          | 1<br>LOW   | 2<br>MODERATE      | 3<br>HIGH       | 4<br>ACUTE       | 4<br>ACUTE         | 3H<br>HIGH     | Review before work starts.                      |         | Replace the hazard.                  |  |
| UNLIKELY          | 1<br>LOW   | 1<br>LOW           | 2<br>MODERATE   | 3<br>HIGH        | 4<br>ACUTE         | 2M<br>MODERATE | Ensure control measures in place.               | Isolate | e People from the hazard             |  |
| RARE              | 1<br>LOW   | 1<br>LOW           | 2<br>MODERATE   | 3<br>HIGH        | 3<br>HIGH          | 1L<br>LOW      | nitor and                                       |         | Engineering Isolate the hazard.      |  |
| is the second m   | rchy of Controls:<br>ost effective metho<br>nging the work is th | d of controlling a | hazard. Enginee | ering by isolati | on is the in ost e | en 'ive, while | rd. Substitution<br>Administrative<br>effective |         | Administrative Change the work.  PPE |  |

|                    |                    |                    |                  | PERS        |              | TIVE EQUIPM                           |                      |                        |                    |                   |                           |
|--------------------|--------------------|--------------------|------------------|-------------|--------------|---------------------------------------|----------------------|------------------------|--------------------|-------------------|---------------------------|
|                    |                    | Select the app     | ropriate PPŁ     | abo v uitab | cor the equi | pment used or                         | the job task         | being perforr          | ned (if applica    | ıble).            |                           |
| FOOT<br>PROTECTION | HAND<br>PROTECTION | HEAD<br>PROTECTION | HEARING<br>ETION | P ECTION    | PROTECTION   | FACE<br>PROTECTION                    | HIGH-VIS<br>CLOTHING | PROTECTIVE<br>CLOTHING | FALL<br>PROTECTION | SUN<br>PROTECTION | HAIR/JEWELLERY<br>SECURED |
|                    |                    |                    |                  |             |              |                                       |                      |                        |                    |                   |                           |
|                    |                    |                    |                  |             |              |                                       |                      |                        |                    |                   |                           |
| Other PPE R        | equired:           |                    |                  |             |              |                                       |                      |                        |                    |                   |                           |
|                    | Pe                 | ermit or Licen     | ses Requirem     | ents        |              | Mandatory Qualifications and Training |                      |                        |                    |                   |                           |
|                    |                    |                    |                  |             |              |                                       |                      |                        |                    |                   |                           |
|                    |                    |                    |                  |             |              |                                       |                      |                        |                    |                   |                           |
|                    |                    |                    |                  |             |              |                                       |                      |                        |                    |                   |                           |



| JOB STEP                     | POTENTIAL HAZARDS  | IR              | CONTROL MEASURES  | RR               |
|------------------------------|--|-----------------|---|------------------|
| SPECIFIC WORK STEPS          | HAZARDS THAT MAY ARISE   | INITIAL<br>RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS  | RESIDUAL<br>RISK |
| 1. Preparation               | Risk of injury from incorrect manual handling, Risks from electrical equipment | ЗН              | <ul> <li>Conduct a pre-work risk assessment to ideally potential bazards and establish appropriate controls.</li> <li>Ensure all personnel involved are trained in annual brading techniques and safe work practices related to lock mechanism repair or replacement.</li> <li>Use appropriate personal protective equipment (PE), including gloves, safety goggles, and steel-toed boots.</li> <li>Implement proper and children, such as bending the knees and keeping the load close to the body, to minimise strategraph in sual handling.</li> <li>Ensure all entirical tools and equipment at extested and tagged according to Australian standards before use.</li> <li>Isola in wer support to the snib lock by switching off at the main circuit breaker to prevent accidental activation.</li> <li>Avoid using alty or usuaged tools; inspect all tools visually before commencing work.</li> <li>trange or activate at lighting to ensure clear visibility of the working area and reduce the risk of errors.</li> <li>Keep to vorkspace tidy by organising tools and materials to avoid trips and falls.</li> <li>learly label and securely store any disassembled components to facilitate easy reassembly.</li> <li>Ensure that there is no unauthorised access to the work area by erecting barriers or signage.</li> <li>Instruct workers to maintain constant communication and adopt a buddy system when handling bulky or awkward items.</li> <li>Prepare an emergency response plan specific to the work being performed, ensuring prompt action in case of injuries or accidents.</li> </ul> | 2M               |
| 2. Perform<br>Lockout/Tagout | Electrical shock, Getting locked in or out                                     | 3H              | <ul> <li>Verify power is completely disconnected before starting work by using appropriate testing equipment, such as a multi-meter, to confirm zero voltage.</li> <li>Use lockout devices and tags that are durable, standardized, and clearly marked with specific warnings, including the name of the person responsible for placing the lock or tag.</li> <li>Ensure all power sources to the equipment are isolated and locked out, including electrical, hydraulic, and pneumatic energy sources.</li> <li>Use personal protective equipment, such as insulated gloves and safety glasses, to protect against electrical shock and potential flying debris.</li> <li>Train all workers involved in the procedure on lockout/tagout processes and the specific hazards associated with lock and electrical mechanism repairs.</li> <li>Assign a competent person to supervise the lockout/tagout procedure and ensure compliance with safety protocols throughout the task.</li> </ul>   | 1L               |



| JOB STEP                     | POTENTIAL HAZARDS                   | IR              | CONTROL MEASURES   | RR               |
|------------------------------|-------------------------------------|-----------------|--|------------------|
| SPECIFIC WORK STEPS          | HAZARDS THAT MAY ARISE              | INITIAL<br>RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS   | RESIDUAL<br>RISK |
|                              |                                     |                 | - Clearly communicate the lockout/tagout procedure to all personnel affected by the equipment shutdown, ensuring they understand their roles and responsibilities. |                  |
|                              |                                     |                 | - Install warning signs or barriers around the work lockout/tagout process.  |                  |
|                              |                                     |                 | - Ensure tools used for repairing or replacing snib lock methanisms are in good condition and appropriately insulated for electrical work.                         |                  |
|                              |                                     |                 | - Conduct a test to verify that the lock or mechan in will not operate once locked out, confirming energy isolation has been achieved fore proceeding with repairs |                  |
|                              |                                     |                 | - Establish an emergency proceure for safely address any potential issues during the lockout, such as misplaced keys or solver of re-ear gisation risks.           |                  |
|                              |                                     |                 | - Ensure all was ers involved are trained in the safe use of tools and equipment.  |                  |
|                              |                                     |                 | - Use conal processe equipment such as gloves and safety glasses to protect against cuts and eye injurie   |                  |
|                              |                                     |                 | - Select pper riate to set that are in good condition to minimise risk of mishandling.   |                  |
|                              |                                     |                 | Keep to work rea organised and free from clutter to reduce the chance of accidents.  |                  |
|                              |                                     |                 | - Death or caddy to keep tools within easy reach, reducing the need for awkward stretching or sending  |                  |
|                              |                                     |                 | - afore beginning, inspect tools for any damage or defects, and do not use damaged tools.  |                  |
| 3. Remove Existing           | Mishandling tools, Share s causing  |                 | - Clearly label and secure any sharp edges before disassembling to prevent accidental cuts.  | 2M               |
| _ock                         | cuts                                |                 | - Utilise proper lifting techniques when handling heavy door components to avoid strain or injury.   |                  |
|                              |                                     |                 | - Apply caution when using power tools by following manufacturer instructions and safety guidelines.   |                  |
|                              |                                     |                 | - Perform a risk assessment specific to the lock removal process to identify and mitigate potential hazards.   |                  |
|                              |                                     |                 | - Implement a buddy system where one person removes the lock and another assists, providing an extra set of hands and eyes.  |                  |
|                              |                                     |                 | - If work is conducted at height, ensure a stable and sturdy ladder or platform is used.   |                  |
|                              |                                     |                 | - Establish a communication plan in case immediate assistance is needed during the task.   |                  |
|                              |                                     |                 | - Conduct regular refresher training sessions to keep all workers updated on best safety practices.  |                  |
|                              |                                     |                 |  |                  |
|                              |                                     |                 |  |                  |
| 4. Inspect Door and<br>Frame | Splinters, Sharp edges causing cuts | 2M              | ,  | 1L               |
|                              |                                     |                 |  |                  |
|                              |                                     |                 |  |                  |



| JOB STEP                         | POTENTIAL HAZARDS                    | IR              | CONTROL MEASURES   | RR               |
|----------------------------------|--------------------------------------|-----------------|--|------------------|
| SPECIFIC WORK STEPS              | HAZARDS THAT MAY ARISE               | INITIAL<br>RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL<br>RISK |
|                                  |                                      |                 |  |                  |
| 5. Install New Lock<br>Mechanism | Incorrect use of tools, Pinch points | ЗН              |  | 2M               |



| JOB STEP                               | POTENTIAL HAZARDS                              | IR              | CONTROL MEASURES   | RR               |
|--|--|-----------------|--|------------------|
| SPECIFIC WORK STEPS                    | HAZARDS THAT MAY ARISE                         | INITIAL<br>RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL<br>RISK |
| 6. Testing Operation                   | Pinching fingers, Misalignment causing jamming | 2M              |  | 1L               |
| 7. Aligning and<br>Adjusting the Latch | Falling off ladder, Mishandling tools          | ЗН              |  | ]<br>2M          |



| JOB STEP               | POTENTIAL HAZARDS                           | IR              | CONTROL MEASURES   | RR               |
|------------------------|---|-----------------|--|------------------|
| SPECIFIC WORK STEPS    | HAZARDS THAT MAY ARISE                      | INITIAL<br>RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL<br>RISK |
|                        |   |                 |  |                  |
|                        |   |                 |  | I                |
|                        |   |                 |  | I                |
|                        |   |                 |  |                  |
|                        |   |                 |  |                  |
|                        | 7   |                 |  |                  |
|                        |   |                 |  |                  |
|                        | 5   |                 |  |                  |
| 8. Tighten all Fixings | Misusing tools, Hand/arm vibration syndrome | 2M              |  | I 1L             |
|                        |   |                 |  |                  |
|                        |   |                 |  |                  |
|                        |   |                 |  |                  |
|                        |   |                 |  |                  |



| JOB STEP                     | POTENTIAL HAZARDS                                     | IR              | CONTROL MEASURES   | RR               |
|------------------------------|---|-----------------|--|------------------|
| SPECIFIC WORK STEPS          | HAZARDS THAT MAY ARISE                                | INITIAL<br>RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL<br>RISK |
| 9. Installing Strike Plate   | Misusing power tools, Metal shards causing eye injury | 3H              |  | 2M               |
| 10. Testing Key<br>Operation | Key breakage, Lock mechanism failure                  | 2M              |  | ■ 1L             |



| JOB STEP            | POTENTIAL HAZARDS                                   | IR              | CONTROL MEASURES   | RR               |
|---------------------|---|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE                              | INITIAL<br>RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL<br>RISK |
| 11. Clean Up Area   | Slips, trips and falls, Disposal of hazardous waste | 3/              |  | 2M               |
| 12. Record Keeping  | Eye strain from computer use, Poor posture          | 2M              |  | 1L               |



| JOB STEP                         | POTENTIAL HAZARDS  | IR              | CONTROL MEASURES   | RR               |
|----------------------------------|--|-----------------|--|------------------|
| SPECIFIC WORK STEPS              | HAZARDS THAT MAY ARISE                                   | INITIAL<br>RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL<br>RISK |
|                                  |  |                 |  | 1                |
| 13. Training on New<br>Mechanism | Miscommunication, Incorrect usage leading to lock damage | ЗН              |  | 2M               |



| JOB STEP                             | POTENTIAL HAZARDS  | IR              | CONTROL MEASURES   | RR               |
|--------------------------------------|--|-----------------|--|------------------|
| SPECIFIC WORK STEPS                  | HAZARDS THAT MAY ARISE   | INITIAL<br>RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL<br>RISK |
| 14. Regular<br>Maintenance Checks    | Unexpected repairs, Failure to notice wear and tear                | 2M              |  | 1L               |
| 15. Emergency<br>Procedures Training | Inadequate knowledge of procedures,<br>Panic during real emergency | ЗН              |  | 2M               |



| POTENTIAL HAZARDS                                   | IR  | CONTROL MEASURES   | RR   |
|---|---|--|--|
| HAZARDS THAT MAY ARISE                              | INITIAL<br>RISK                           | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS         | RESIDUAL<br>RISK   |
|   |   |  | ı  |
|   |   |  |  |
|   |   |  |  |
|   |   |  |  |
|   |   |  | I  |
|   |   |  |  |
|   |   |  | 1  |
|   |   |  |  |
| Unresolved faults, Client dissatisfact with service | 2M  |  | 1L   |
|   |   |  |  |
|   |   |  |  |
|   |   |  |  |
|   |   |  |  |
|   | Unresolved faults, Client dissatisfact of | HAZARDS THAT MAY ARISE  INITIAL RISK  Unresolved faults, Client dissatisfactor | HAZARDS THAT MAY ARISE  INITIAL RISK  SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS  Unresolved faults, Client dissatisfag in |



| JOB STEP                                    | POTENTIAL HAZARDS                                | IR              | CONTROL MEASURES   | RR               |
|---|--|-----------------|--|------------------|
| SPECIFIC WORK STEPS                         | HAZARDS THAT MAY ARISE                           | INITIAL<br>RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL<br>RISK |
| 17. Disconnect<br>Lockout/Tagout<br>Devices | Electrical shock, Unexpected machinery operation | 4A              |  | 2M               |
| 18. Storage of Old Lock<br>Components       | Injury from sharp edges, Mishandling materials   | ЗН              |  | <b>1</b> 2M      |



| JOB STEP                            | POTENTIAL HAZARDS   | IR              | CONTROL MEASURES   | RR               |
|-------------------------------------|---|-----------------|--|------------------|
| SPECIFIC WORK STEPS                 | HAZARDS THAT MAY ARISE  | INITIAL<br>RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL<br>RISK |
| 19. Follow-up Service<br>Visit      | Road hazards during the sources of issues causing lock failure        | 2M              |  | 1L               |
| 20. Regular Reporting to Management | Missed documentation errors, Lack of feedback in improving procedures | 3H              |  | 2M               |



| JOB STEP            | POTENTIAL HAZARDS      | IR              | CONTROL MEASURES   | RR               |
|---------------------|------------------------|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL<br>RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL<br>RISK |
|                     |                        |                 |  |                  |
|                     |                        |                 |  |                  |



#### **EMERGENCY RESPONSE - CALL 000 FOR EMERGENCIES**

Ensure to have an Emergency Management Plan in place as well as adequate numbers of trained first aid staff with easy access to fully stocked first aid kits, rescue equipment, material safety data sheets, adequate access to emergency communication equipment and fire-fighting equipment suitable for all classes of fire and ignition sources.

#### LEGISLATIVE REFERENCES

RELEVANT LEGISLATION AND CODES OF PRACTICE. DELETE THE LEGISLATIVE REFERENCES. ANY STATE OF AT ARE NOT APPLICABLE.

#### **Queensland & Australian Capital Territory**

Work Health and Safety Act 2011

Work Health and Safety Regulations 2011

Legislation QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/work-health-and-safety-laws Codes of Practice QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/codes-of-practice

Legislation ACT: https://www.worksafe.act.gov.au/laws-and-compliance/acts-and-regulations

Codes of Practice ACT: https://www.worksafe.act.gov.au/laws-and-compliance/codes-of-practice

#### **New South Wales**

Work Health and Safety Act 2011

Work Health and Safety Regulations 2017

Legislation NSW: https://www.safework.nsw.gov.au/legal-obligations/legislatide

Codes of Practice NSW: https://www.safework.nsw.gov.au/resource-library/lis codes-of ractions of Practice NSW: https://www.safework.nsw.gov.au/resource-library/lis codes-of-ractions-of-racti

#### **Northern Territory**

Work Health and Safety (National Uniform Legislation) Act 2011

Work Health and Safety (National Uniform Legislation) Regulation 2011

Codes of Practice NT: https://worksafe.nt.gov.au/f

#### South Australia

Work Health and Safety Act 2012 (SA)

Work Health and Safety Regulations 2012 (SA)

Legislation for SA: https://www.safework.sa.gov.au/resources/le\_lation

Codes of Practice for SA: https://www.safework.sa.gov.au/work\_aces/codes-of-practice#COPs

#### Tasmania

Work Health and Safety Act 2012

Work Health and Safety (Transitional and Consequential Provisions) Act 2012

Work Health and Safety Regulations 2012

Work Health and Safety (Transitional) Regulations 2012

Legislation for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/acts-and-regulations

Codes of Practice for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/codes-of-practice

Details of permits, licenses or access required by regulatory bodies (add or delete as required):

- Permits from local council
- Authorisation to commence work
- Any required documents.

#### Victoria

Occupational Health al. Safety Act

Occupational Health and affety gulations 2017

Legis on VIC: https://www.wksafe.vic.gov.au/occupational-health-and-safety-act-and-

gulat

des on actice VI autros://www.worksafe.vic.gov.au/compliance-codes-and-codes-practice

#### Western Australia

Work Health and Safety Act 2020

Work Health and Safety Regulations 2022

Legislation Western Australia: <a href="https://www.commerce.wa.gov.au/worksafe/legislation">https://www.commerce.wa.gov.au/worksafe/legislation</a> Codes of Practice WA: <a href="https://www.commerce.wa.gov.au/worksafe/codes-practice">https://www.commerce.wa.gov.au/worksafe/codes-practice</a>

#### Safe Work Australia Links

Law and Regulation (All States): https://www.safeworkaustralia.gov.au/law-and-regulation Model Codes of Practice: https://www.safeworkaustralia.gov.au/resources-publications/model-codes-of-practice

#### **Model Codes of Practice**

- Managing noise and preventing hearing loss at work
- Confined spaces
- Labelling of workplace hazardous chemicals
- Managing risks of hazardous chemicals in the workplace
- Welding processes
- First aid in the workplace
- Managing the risk of falls at workplaces
- Hazardous manual tasks
- Managing the risk of falls in housing construction
- Managing electrical risks in the workplace
- Demolition work
- Excavation work
- Work health and safety consultation, cooperation and coordination
- Managing the work environment and facilities
- How to manage work health and safety risks
- Managing risks of plant in the workplace
- Construction work





#### SIGNATORIES OF THE SAFE WORK METHOD STATEMENT

The signed and dated personnel listed below have cooperated in the consultation and development of this Safe Work Method Statement which has been approved by the Person/s Conducting a Business or Undertaking (PCBU). In signing this Safe Work Method Statement each individual acknowledges and confirms that they have read this SWMS in full, having raised any questions for items on this Safe Work Method Statement that require clarification, and confirms that they are competent, skilled and knowledgeable for the task assigned to them. Every person acknowledges that they have received the relevant training and qualifications where required, before carrying out any work contained in this Safe Work Method Statement. By signing this Safe Work Method Statement each individual agrees to work safely, to follow any safe work instructions which are provided, and agrees to use all Personal Protective Equipment where appropriate.

| Worker Name | Signature | Date |
|-------------|-----------|------|
|             |           |      |
|             |           |      |
|             |           |      |
|             |           |      |
|             |           |      |

#### SAFE WORK IN THE STATEMENT MONITORING AND REVIEW

The SWMS must be reviewed regularly to make sure it remains a fective of must be reviewed (and revised if necessary) if relevant control measures are revised. The view process should be carried out in consultation with workers (including contractors of the SWMS and their health and safety representatives who represented that work group at the workplace.

When the SWMS has been revised the PCBU mast ensure that advised that a revision has been made and how they can access the revised SWMS, including all persons who will need to change a work procedure or system as a rest of the review are advised of the changes in a way that will enable them to implement their duties and the involved in the work must be provided with the relevant information and instruction that will assist them to understand and implement the revised SWMS.

The SWMS must be monitored regularly for the effectiveness of ensuring hazard controls are effective in reducing the risk of incidents, keeping the workplace safe for all personnel. The person responsible for monitoring the effectiveness of the Safe Work Method Statement should employ a multi-faceted approach which includes but is not limited to:

- Spot Checks.
- 2. Consultation with workers, contractors and sub-contractors.
- 3. Internal audits on a continual basis.

An approach of continuous improvement, promptly recording inconsistencies or deficiencies, followed up by immediate corrective action and consultation with all relevant personnel ensures that the PCBU is consistently developing ever-improving systems of safe work principles.

| REVIEW NUMBER | 1 | 2 | 3 | 4 | 5 | 6 | 7 |
|---------------|---|---|---|---|---|---|---|
| NAME          |   |   |   |   |   |   |   |
| INITIALS      |   |   |   |   |   |   |   |
| DATE          |   |   |   |   |   |   |   |





### SAFE WORK METHOD STATEMENT REVIEW CHECKLIST

This Safe Work Method Statement Review Checklist is to be followed and used upon initial development of the SWMS to help ensure that all steps have been adequately taken before work commences. Think of this document as an internal audit review checklist before commencing work, and may form part of a Toolbox Talk (safety meeting) and may be used as an opportunity for education and training.

| ITEMS WHICH MUST BE INCLUDED IN THE SWMS  | COMPLETED    | COMMENTS |
|---|--------------|----------|
|   |              |          |
| The company details have been entered, including the project name and address.                  |              |          |
| All relevant personnel consulted during the development of the SWMS.                            |              |          |
| Name, signature, position and date signed of the person approving the SWMS.                     |              |          |
| Specific personnel and qualifications, experience is noted in the SWMS.                         | 7            |          |
| Provides a step-by-step process of tasks required to carry out the activity or task.            |              |          |
| Adequate risk assessment of any identified hazards has been completed.                          |              |          |
| Foreseeable hazards are identified and documented for each step.                                |              |          |
| Any hazards listed in any site risk assessments have been added to the SWMS                     |              |          |
| SWMS initial risk (IR) column as well as residual risk (RR) column pleted.                      |              |          |
| Check control measures added to the SWMS are the most effective selections                      |              |          |
| Responsible person is assigned and listed on the part the important control measures.           |              |          |
| Permit or licenses requirements specified, sur as Hot Work, Electric Work, Work at Heights etc. |              |          |
| SWMS identifies plant and equipment to be us  |              |          |
| Details of inspection checks required for any equipment listed an inoted on the SWMS.           |              |          |
| Describes any mandatory qualifications, experience, and or skills required to perform the work. |              |          |
| Applicable personal protective equipment is selected on the SWMS.                               |              |          |
| Reflects and documents any legislative references and/or Australian Standards.                  |              |          |
| Identifies any hazardous substances used with specific control measures in line with any SDS.   |              |          |
|   |              |          |
| REVIEWED BY   | DATE REVIEWE | D        |
| SIGNATURE   | DATE COMPLET | ED       |