



Tower Crane Assembly - Dis	mantling SAFE WORK MI	ETHOD STATEMENT (SWMS)	
TASK OR AC	CTIVITY: Tower Crane Assembly	- Dismantling	
Business Name:		ABN:	SWMS#
Business Address:			
Contact Person:	Phone:	E il:	
THIS SAFE WORK METHOD	STATEMENT IS APPROVED BY	THE PCL OF THE ROJECT	
Under the Work Health and Safety Regulation (WHS Regulation), a person conduct the proposed work starts.	cting a business or undo	required to er. sthat a safe work method s	statement (SWMS) is prepared before
Full Name:			
Signature:		Title:	Date:
Details of the person(s) responsible for ensuring implementation, monitoring	roliance the VMS a vell as review	s and modifications of the SWMS.	
Full Name:		Title:	Phone:
ALL PERSONNEL PARTICIPATING IN ANY ACTIVITY ON THIS 5 MS M HAVE THE FOLLOWING COMMUNICATED	NAL 2 OF ALL RELEVANT PERSONNI EVELOPMENT AND APPROVAL OF	EL WHO HAVE BEEN CONSULTED AND CO THIS SWMS	OMMUNICATED TO IN THE
Safety meetings or toolbox talks will be sched and in account with gislative requirements to first identify any site hazards, and then to further take steps to either eliminate or continuous each hazard.			
If an incident or a near miss occurs, all work must sto, quately. Depending on the severity of the incident, a meeting will be called with all workers to amend the SWMS if required. The meeting may also be an educational opportunity.			
Any changes made to the SWMS after an incident or a near miss must be approved by the Person Conducting Business or Undertaking and communicated to all relevant personnel.			
The SWMS must be kept and be available for inspection at least until the work is completed. Where a SWMS is revised, all versions should be kept. If a notifiable incident occurs in relation to which the SWMS relates, then the SWMS must be kept for at least two years from the occurrence of the notifiable incident.			

Version 2.5 Authorised by Review # Date of Issue: Review Date: 1





CLIENT OR PRINCIPAL	CONTRACTOR DETAILS
Client:	SCOPE OF WORKS
Project Name:	
Project Address:	
Project Manager:	
Contact Phone:	
Date SWMS supplied to Project Manager:	
ANY HIGH-RISK CONSTRUCTO	ON WO K BEIN O KRIED OUT
☐ involves a risk of a person falling more than 2 meters	☐ is carried out on or near pressurised gas mains or piping
☐ is carried out on a telecommunication tower	carried out on or near chemical, fuel or refrigerant lines
☐ involves demolition of an element of a structure that is load-bearing	☐ is carried out on or near energised electrical installations or services
☐ involves demolition of an element related to the physical integration of a ructure	☐ is carried out in an area that may have a contaminated or flammable atmosphere
☐ involves, or is likely to involve, disturbing asb	☐ involves tilt-up or precast concrete
☐ involves structural alteration or repair that — quires term — ov sup — rt to prevent collapse	☐ is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor
is carried out in or near a confined space	☐ is carried out in an area of a workplace where there is any movement of powered mobile plant
☐ is carried out in/near a shaft or trench deeper tha tunnel involving use of explosives	☐ is carried out in areas with artificial extremes of temperature.
☐ is carried out in or near water or other liquid that involves a risk of drowning.	☐ involves diving work.
ANY HIGH-RISK MACHINER	RY OR EQUIPMENT NEARBY

Version 2.5 Authorised by Review # Date of Issue: Review Date: 2



	RISK MATRIX										
LIKELIHOOD	INSIGNIFICANT	MINOR	MODERATE	MAJOR	CATASTROPHIC	SCOBE	ACTION		HEIRARCHY OF CONTROLS		
ALMOST CERTAIN	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4 ACUTE	SCORE ACTION		Elimination Remove the hazard.			
LIKELY	2 MODERATE	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4A ACUTE	DO NOT PROCE		Substitution		
POSSIBLE	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	4 ACUTE	3H HIGH	Review befor work starts.		Replace the hazard.		
UNLIKELY	1 LOW	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	2M MODERATE	Ensure control measures in place.		Isolate People from the hazard		
RARE	1 LOW	1 LOW	2 MODERATE	3 HIGH	3 HIGH	1L LOW	nitor and		Engineering Isolate the hazard.		
is the second m	rchy of Controls: ost effective metho nging the work is th	d of controlling a	hazard. Enginee	ring by isolati		et. 'ive, while	rd. Substitution Administrative effective		Administrative Change the work. PPE		

				PERS		TIVE EQUIPM					
		Select the app	ropriate PPL	abo. ~uitab	le or the equip	oment used or	the job task	being perform	ned (if applica	able).	
FOOT PROTECTION	HAND PROTECTION	HEAD PROTECTION	ARING STION	F' CTIO	RL PIRATORY PROTECTION	FACE PROTECTION	HIGH-VIS CLOTHING	PROTECTIVE CLOTHING	FALL PROTECTION	SUN PROTECTION	HAIR/JEWELLERY SECURED
Other PPE R	equired:										
	Pe	ermit or Licen	ses Requirem	ents			Ma	indatory Qual	ifications and	Training	



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
Pre-start planning and permits	Incomplete SWMS coverage Unclear roles and responsibilities Inadequate traffic and exclusion zoning Conflicting site activities Unverified underground and overhead services	4A	 Review project scope and confirm that this LVMS specifically covers tower crane assembly, dismantling, self-erecting operations, high hash lifting as working at heights from crane booms Consult with principal contractor, crane supply and grant principal contractor, crane supply and communication methods before work starts Obtain and display necessary work permits include the crane operation permits, high risk work licences and any council road and any council road and self-ere using the rent Dial Before You Dig plans and site service plans before locatic crane pads and slew hius Identify and move undergound self-ere using the rent Dial Before You Dig plans and site service plans before locatic crane pads and slew hius Identify and move undergound self-ere using the rent Dial Before You Dig plans and site service plans before locatic crane pads and slew hius Identify and move undergound self-ere using the rent Dial Before You Dig plans and site service plans before locatic crane pads and slew hius Identify and move undergound self-ere using the rent Dial Before You Dig plans and site service plans before locatic crane pads and slew hius Identify and move undergound self-ere using the rent Dial Before You Dig plans and site service plans before locatic crane pads and slew hius Identify and move undergound his service using rent Dial Before You Dig plans and site service plans before locatic crane and service plans and structures and map minimum approach distance in accordance with service plans and service pla	2M
Deliveries and site access	Unplanned vehicle movement Collision with pedestrians Falling components during unloading Tipping of semi-trailers Restricted access and poor visibility	ЗН	 Establish and signpost a dedicated delivery route and loading zone separated from pedestrian walkways with barriers and bunting Appoint a trained traffic controller to manage all crane component deliveries in accordance with the site traffic management plan Inspect delivery vehicles on arrival for load stability, correct restraining and evidence of load shift before authorising unloading Chock wheels of semi-trailers and engage park brakes before releasing any load restraints Use only rated lifting points, certified spreader beams and lifting lugs supplied or approved by the crane manufacturer DO NOT stand in line of fire when removing chains, dogs or straps from compressed or leaning loads 	2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS Use spotters with radios and agreed hand signals to guide vehicle reversing and positioning within the crane assembly area Maintain exclusion zones around unloading operatus using rigid barriers where practicable to keep unauthorised persons clear Confirm ground bearing capacity at unloage and laydean areas is adequate for vehicle axle loads and use bog mats where required Stack mast sections, counterweights and jibs at able, level country during dunnage and chocks to prevent rolling or sliding	RESIDUAL RISK
Ground conditions and crane base	Ground subsidence under crane Inadequate crane base design Unstable outrigger footing Collapse of temporary 'ations'		Obtain and review or site soil to dition. Verify crane as edimentors, anchorocations and holding-down bolt sizes match the crane manufacturer's wind pefore erection. Inspirit, and for off spots, voids, recent excavations, underground services and evidence of water saturation wind the one base area. Use en linear concert concert foundations, compacted fill and grillages designed by a suitably qualified princer DO No crely on uncontrolled fill. Instruction level crane base or rails using calibrated survey equipment and record final levels as required with example. Torque anchor bolts, cast-in plates and base frame welds for damage, corrosion or deformation before use. Torque anchor bolts to manufacturer or engineer-specified values using calibrated torque equipment and record results. Provide adequate drainage away from base or outrigger pads to prevent ponding and erosion during wet weather. Use hardwood mats or engineered pads under mobile crane outriggers and verify ground bearing pressure is within allowable limits. Barricade base area and display 'No Entry — Crane Foundation' signage to prevent unauthorised interference with anchors or base components.	2M
Assembly of self- erecting crane	 Uncontrolled boom unfolding Pinch points at hinge joints Component instability during self-erection Crane overturning during luffing Contact with overhead services 	4A		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
Mobile crane set-up for assembly	Mobile crane over uning Outrigger failure Boom collapse or overleading Collision with structures.	1A		2M
Mast and tower section erection	Falling tower sectionsDropped tools and hardwareCrush injuries at connection points	4A		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
	Uncontrolled mast movement			
	Working at heights on tower			
				-
Slewing unit and jib installation	High reach lifting instability Slewing unit misalignment Falling jib or counterjib Wind-induced load swing	4A		2M
	Working at heights from crane booms			
				I



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
Mechanical, electrical and safety systems	Electrical shock from controls Unintended crane movement Failure of limit switches Suspension failure at high reach Hydraulic leaks under pressure	3H		1L
Commissioning, load testing and handover	Crane overload during testing Falling test weights Uncontrolled slewing or luffing Inadequate operator training	ЗН		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
Routine operations and high reach lifting	Load collision with structures Load drop during high reach Exceeding crane rated capacity Weather impacts on stability Public exposure to crane operations	ЗН		2M
Working at heights on crane booms	Falls from jib or counterjib Slip on wet or oily surfaces Dropped tools from boom Limited emergency access and rescue	4A		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
Dismantling planning and preparation	Unplanned crane movement Component instability during dismantle Loss of structural integrity Change in counterweight balance	4A		2M
Dismantling jib, counterjib and mast	 Falling crane components High reach dismantling instability Crush injuries at joints Loss of balance for riggers at height 	4A		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
Pack-up, transport and demobilisation	Manual handling injuries Load shift during transport Unsecured loose items Residual energy in components	ЗН		2M



EMERGENCY RESPONSE - CALL 000 FOR EMERGENCIES

Ensure to have an Emergency Management Plan in place as well as adequate numbers of trained first aid staff with easy access to fully stocked first aid kits, rescue equipment, material safety data sheets, adequate access to emergency communication equipment and fire-fighting equipment suitable for all classes of fire and ignition sources.

LEGISLATIVE REFERENCES

RELEVANT LEGISLATION AND CODES OF PRACTICE. DELETE THE LEGISLATIVE REFERENCES. ANY STATE AT ARE NOT APPLICABLE.

Queensland & Australian Capital Territory

Work Health and Safety Act 2011

Work Health and Safety Regulations 2011

Legislation QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/work-health-and-safety-laws Codes of Practice QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/codes-of-practice

Legislation ACT: https://www.worksafe.act.gov.au/laws-and-compliance/acts-and-regulations

Codes of Practice ACT: https://www.worksafe.act.gov.au/laws-and-compliance/codes-of-practice

New South Wales

Work Health and Safety Act 2011

Work Health and Safety Regulations 2025

Legislation NSW: https://www.safework.nsw.gov.au/legal-obligations/legislati

Codes of Practice NSW: https://www.safework.nsw.gov.au/resource-library/lis

Northern Territory

Work Health and Safety (National Uniform Legislation) Act 2011

Work Health and Safety (National Uniform Legislation) Regulation 201

Codes of Practice NT: https://worksafe.nt.gov.au/f

South Australia

Work Health and Safety Act 2012 (SA)

Work Health and Safety Regulations 2012 (SA)

Legislation for SA: https://www.safework.sa.gov.au/resources/le_lation

Codes of Practice for SA: https://www.safework.sa.gov.au/wor/ aces/codes-of-practice#COPs

Tasmania

Work Health and Safety Act 2012

Work Health and Safety (Transitional and Consequential Provisions) Act 2012

Work Health and Safety Regulations 2012

Work Health and Safety (Transitional) Regulations 2012

Legislation for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/acts-and-regulations

Codes of Practice for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/codes-of-practice

Details of permits, licenses or access required by regulatory bodies (add or delete as required):

- Permits from local council
- Authorisation to commence work
- Any required documents.

Victoria

Or pational Health a. Safety Act J4

Occational Health and afety gulations 2017

Legis on VIC: https://www.sksafe.vic.gov.au/occupational-health-and-safety-act-and-

gulat

tes of actice VIC attps://www.worksafe.vic.gov.au/compliance-codes-and-codes-practice

Western Australia

Work Health and Safety Act 2020

Work Health and Safety Regulations 2022

Legislation Western Australia: https://www.commerce.wa.gov.au/worksafe/legislation

Codes of Practice WA: https://www.commerce.wa.gov.au/worksafe/codes-practice

Safe Work Australia Links

Law and Regulation (All States): https://www.safeworkaustralia.gov.au/law-and-regulation Model Codes of Practice: https://www.safeworkaustralia.gov.au/resources-publications/model-codes-of-practice

Model Codes of Practice

- Managing noise and preventing hearing loss at work
- Confined spaces
- Labelling of workplace hazardous chemicals
- Managing risks of hazardous chemicals in the workplace
- Welding processes
- First aid in the workplace
- Managing the risk of falls at workplaces
- Hazardous manual tasks
- Managing the risk of falls in housing construction
- Managing electrical risks in the workplace
- Demolition work
- Excavation work
- Work health and safety consultation, cooperation and coordination
- Managing the work environment and facilities
- How to manage work health and safety risks
- Managing risks of plant in the workplace
- Construction work





SIGNATORIES OF THE SAFE WORK METHOD STATEMENT

The signed and dated personnel listed below have cooperated in the consultation and development of this Safe Work Method Statement which has been approved by the Person/s Conducting a Business or Undertaking (PCBU). In signing this Safe Work Method Statement each individual acknowledges and confirms that they have read this SWMS in full, having raised any questions for items on this Safe Work Method Statement that require clarification, and confirms that they are competent, skilled and knowledgeable for the task assigned to them. Every person acknowledges that they have received the relevant training and qualifications where required, before carrying out any work contained in this Safe Work Method Statement. By signing this Safe Work Method Statement each individual agrees to work safely, to follow any safe work instructions which are provided, and agrees to use all Personal Protective Equipment where appropriate.

Worker Name	Signature

SAFE WORK IN THE STATEMENT MONITORING AND REVIEW

The SWMS must be reviewed regularly to make sure it remains fective of must be reviewed (and revised if necessary) if relevant control measures are rovised. The view respectively should be carried out in consultation with workers (including contractors as a sub-intractors of the SWMS and their health and safety representatives who represented that work group at the workplace.

When the SWMS has been revised the PCBU must ensure that advised that a revision has been made and how they can acces he revised SWMS, including all persons who will need to change a work procedure or system as a region of the review are advised of the changes in a way that will enable them to implement their duties and the revised SWMS. All workers that will be involved in the work must be provided with the relevant information and instruction that will assist them to understand and implement the revised SWMS.

The SWMS must be monitored regularly for the effectiveness of ensuring hazard controls are effective in reducing the risk of incidents, keeping the workplace safe for all personnel. The person responsible for monitoring the effectiveness of the Safe Work Method Statement should employ a multi-faceted approach which includes but is not limited to:

- Spot Checks.
- 2. Consultation with workers, contractors and sub-contractors.
- Internal audits on a continual basis.

An approach of continuous improvement, promptly recording inconsistencies or deficiencies, followed up by immediate corrective action and consultation with all relevant personnel ensures that the PCBU is consistently developing ever-improving systems of safe work principles.

REVIEW NUMBER	1	2	3	4	5	6	7
NAME							
INITIALS							
DATE							

Version 2.5 Authorised by Review # Date of Issue: Review Date: 13





SAFE WORK METHOD STATEMENT REVIEW CHECKLIST

This Safe Work Method Statement Review Checklist is to be followed and used upon initial development of the SWMS to help ensure that all steps have been adequately taken before work commences. Think of this document as an internal audit review checklist before commencing work, and may form part of a Toolbox Talk (safety meeting) and may be used as an opportunity for education and training.

ITEMS WHICH MUST BE INCLUDED IN THE SWMS	COMPLETED	COMMENTS
The company details have been entered, including the project name and address.		
All relevant personnel consulted during the development of the SWMS.		
Name, signature, position and date signed of the person approving the SWMS.		
Specific personnel and qualifications, experience is noted in the SWMS.	7	
Provides a step-by-step process of tasks required to carry out the activity or task.	k	
Adequate risk assessment of any identified hazards has been completed.	\boxtimes	
Foreseeable hazards are identified and documented for each step.	\boxtimes	
Any hazards listed in any site risk assessments have been added to the SWMS		
SWMS initial risk (IR) column as well as residual risk (RR) colum mpleted.	\boxtimes	
Check control measures added to the SWMS are the most effective selections.	\boxtimes	
Responsible person is assigned and listed on the part of the important of	\boxtimes	
Permit or licenses requirements specified, sur as Hot Work, Electric Work, Work at Heights etc.	\boxtimes	
SWMS identifies plant and equipment to be use	\boxtimes	
Details of inspection checks required for any equipment listed an onthe SWMS.	\boxtimes	
Describes any mandatory qualifications, experience, use or skills required to perform the work.	\boxtimes	
Applicable personal protective equipment is selected on the SWMS.		
Reflects and documents any legislative references and/or Australian Standards.	\boxtimes	
Identifies any hazardous substances used with specific control measures in line with any SDS.	\boxtimes	
REVIEWED BY	DATE REVIEWED	
SIGNATURE	DATE COMPLETED	