



| Transformer Oil | SAFE WORK METHOD STA | ATEMENT (SWMS) | |
|--|--|--|-------------------------------------|
| TA | ASK OR ACTIVITY: Transformer | Oil | |
| Business Name: | | ABN: | SWMS# |
| Business Address: | | | |
| Contact Person: | Phone: | E il: | |
| THIS SAFE WORK METHOD | STATEMENT IS APPRO\\\O\D BY | THE PC. OF THE ROJECT | |
| | | | |
| Under the Work Health and Safety Regulation (WHS Regulation), a person conduct the proposed work starts. | eting a business or under a (PC 1) is | required to en that a safe work method s | statement (SWMS) is prepared before |
| Full Name: | | | |
| Signature: | NY | Title: | Date: |
| Details of the person(s) responsible for ensuring implementation, monitoring a | ppliance the VMS a well as review | s and modifications of the SWMS. | |
| Full Name: | | Title: | Phone: |
| ALL PERSONNEL PARTICIPATING IN ANY ACTIVITY ON THIS & VMS IN HAVE THE FOLLOWING COMMUNICATED | NA. 2 OF ALL RELEVANT PERSONNI EVELOPMENT AND APPROVAL OF | EL WHO HAVE BEEN CONSULTED AND COTHIS SWMS | OMMUNICATED TO IN THE |
| Safety meetings or toolbox talks will be sched ed in account with gislative requirements to first identify any site hazards, comparing those hazards and then to further take steps to either eliminate or continuous each hazard. | | | |
| If an incident or a near miss occurs, all work must sto, an attely. Depending on the severity of the incident, a meeting will be called with all workers to amend the SWMS if required. The meeting may also be an educational opportunity. | | | |
| Any changes made to the SWMS after an incident or a near miss must be approved by the Person Conducting Business or Undertaking and communicated to all relevant personnel. | | | |
| The SWMS must be kept and be available for inspection at least until the work is completed. Where a SWMS is revised, all versions should be kept. If a notifiable incident occurs in relation to which the SWMS relates, then the SWMS must be kept for at least two years from the occurrence of the notifiable incident. | | | |

Version 2.5 Authorised by Review # Date of Issue: Review Date: 1





| CLIENT OR PRINCIPAL | CONTRACTOR DETAILS |
|--|---|
| Client: | SCOPE OF WORKS |
| Project Name: | |
| Project Address: | |
| Project Manager: | |
| Contact Phone: | |
| Date SWMS supplied to Project Manager: | |
| ANY HIGH BIOK CONSTRUCTOR | NAME OF THE POLIT |
| ANY HIGH-RISK CONSTRUCTOR | N WC & BEIN C ARIED OUT |
| ☐ involves a risk of a person falling more than 2 meters | is carried out on or near pressurised gas mains or piping |
| ☐ is carried out on a telecommunication tower | carried out on or near chemical, fuel or refrigerant lines |
| ☐ involves demolition of an element of a structure that is load-bearing | \square is carried out on or near energised electrical installations or services |
| ☐ involves demolition of an element related to the physical integral of a functure | ☐ is carried out in an area that may have a contaminated or flammable atmosphere |
| ☐ involves, or is likely to involve, disturbing asb | ☐ involves tilt-up or precast concrete |
| ☐ involves structural alteration or repair that —quires term — v sup —rt to prevent collapse | ☐ is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor |
| ☐ is carried out in or near a confined space | ☐ is carried out in an area of a workplace where there is any movement of powered mobile plant |
| ☐ is carried out in/near a shaft or trench deeper that. tunnel involving use of explosives | ☐ is carried out in areas with artificial extremes of temperature. |
| \square is carried out in or near water or other liquid that involves a risk of drowning. | ☐ involves diving work. |
| ANY HIGH-RISK MACHINER | Y OR EQUIPMENT NEARBY |
| | |
| | |
| | |

Version 2.5 Authorised by Review # Date of Issue: Review Date: 2



| RISK MATRIX | | | | | | | | | | |
|-------------------|--|--------------------|-----------------|------------------|--------------------|----------------|---|---------|--------------------------------------|--|
| LIKELIHOOD | INSIGNIFICANT | MINOR | MODERATE | MAJOR | CATASTROPHIC | SCORE | ACTION | HEI | RARCHY OF CONTROLS | |
| ALMOST CERTAIN | 3 HIGH | 3 HIGH | 4 ACUTE | 4 ACUTE | 4 ACUTE | SCORE | ACTION | | Elimination Remove the hazard. | |
| LIKELY | 2 MODERATE | 3 HIGH | 3 HIGH | 4 ACUTE | 4 ACUTE | 4A ACUTE | DO NOT PROCE | | Substitution | |
| POSSIBLE | 1 LOW | 2 MODERATE | 3 HIGH | 4 ACUTE | 4 ACUTE | 3H HIGH | Review before work starts. | | Replace the hazard. | |
| UNLIKELY | 1 LOW | 1 LOW | 2 MODERATE | 3 HIGH | 4 ACUTE | 2M MODERATE | Ensure control measures in place. | Isolate | e People from the hazard | |
| RARE | 1 LOW | 1 LOW | 2 MODERATE | 3 HIGH | 3 HIGH | 1L LOW | nitor and | | Engineering Isolate the hazard. | |
| is the second m | rchy of Controls: ost effective metho nging the work is th | d of controlling a | hazard. Enginee | ering by isolati | on is the in ost e | en 'ive, while | rd. Substitution Administrative effective | | Administrative Change the work. PPE | |

| | | | | PERS | | TIVE EQUIPM | | | | | |
|--------------------|--------------------|--------------------|------------------|-------------|--------------|--------------------|----------------------|------------------------|--------------------|-------------------|---------------------------|
| | | Select the app | ropriate PPŁ | abo v uitab | cor the equi | pment used or | the job task | being perforr | ned (if applica | ıble). | |
| FOOT PROTECTION | HAND PROTECTION | HEAD PROTECTION | HEARING ETION | P ECTION | PROTECTION | FACE PROTECTION | HIGH-VIS CLOTHING | PROTECTIVE CLOTHING | FALL PROTECTION | SUN PROTECTION | HAIR/JEWELLERY SECURED |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| Other PPE R | equired: | | | | | | | | | | |
| | Pe | ermit or Licen | ses Requirem | ents | | | Ma | andatory Qual | ifications and | Training | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|-------------------------|--|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| 1. Preparation | Unexpected energization, Slips and falls | 2M | Ensure proper lockout/tagout procedures. It vollowed before the commencement of any work to avoid unexpected energization. Conduct a thorough risk assessment for all point a mazards, including slips and falls, and devise appropriate control measures beforehand. Have workers trained in first in available on site, and entire they have access to emergency response equipment. Provide person protecting equipment (PPE) such as non-slip footwear, gloves, hard hats, and safety glasses to accorders involved in the recipient of make sure they use them as required. Instructurariers in warm as signs around not transformer and work area to clearly demarcate restricted zone, and prevent authorised access. Ensult the the word pace is cleared of any debris or obstacles that could lead to slips, trips, or falls. Make that at words adhere to industry-standard guidelines when handling and transporting ansformer oil, bluding proper storage, labeling, and disposal procedures. Conside gullar inspections of the work site by a skilled Workplace Health and Safety Officer to monitor ompila, with policies and regulations and to identify and mitigate risks promptly. Is sure that transformers are de-energised and safety grounded before conducting any work involving transformer oils, and confirm the absence of any residual energy using appropriate testing equipment. Implement a buddy system where workers check each other's PPE and compliance with safety procedures throughout the day to maintain high safety standards. Schedule daily toolbox talks or briefings to discuss ongoing safety concerns, remind workers of hazards, and reinforce best practices. Use spill containment measures like drip pans and spill kits to minimise environmental impact and potential slip hazards due to oil leaks or spills. Develop a clear communication protocol for both routine updates and emergencies, including a predefined chain of command and the use | 1L |
| 2. Equipment Inspection | Electrical shock, Faulty equipment | 3Н | Regular equipment inspection: Conduct routine inspections to ensure all equipment is free from visible defects, and confirm its suitability for the work being carried out. De-energise electrical components: Before inspecting any equipment, ensure that all components are de-energised to mitigate the risk of electrical shock. Lockout/tagout procedures: Implement strict lockout/tagout procedures to prevent the accidental activation of equipment during inspection. | 2M |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|--------------------------|----------------------------|-------------------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | Use of insulated tools and equipment: Inspectors and workers should use only insulated tools and equipment when working with transformer oil to reduce the risk of electrical shock. | |
| | | | - Work within a restricted access area: Establish a pricted access area around the equipment to minimise the number of individuals exposed to the entirely hazards. | |
| | | | - Wear appropriate personal protective equation (PPE) assure that all personnel involved in equipment inspection wear the necessary PPE, including loves unety glasses, and steel-toe shoes. | |
| | | | - Continuous safety training: Provide ongoing say training to workers and inspectors to ensure everyone is aware of potential pazards, proper having techniques, and necessary precautions when working with transformer oil. | |
| | | | - Proper document and recon reeping: Maintain accurate records of equipment inspections, including date aspection sults, any activate taken to address identified issues. | |
| | | | - Communication between the members regard any concern assues relate to equipment condition or safety protocols. | |
| | | | - Imm the report of hazardous conditions: Encourage workers and inspectors to immediately report any unificendition or faulty equipment so that corrective actions can be taken promptly. | |
| | | | - Emergancy is ponse un: Develop an emergency response plan outlining the necessary steps to take case can electical shock or other unexpected hazard during equipment inspection. | |
| | | | - Many in quipment according to manufacturer guidelines: Follow manufacturer guidelines for paintain servicing, and cleaning the equipment to ensure it remains in optimal working condition. | |
| | | $\backslash \backslash$ | - pper disposal of contaminated materials: Dispose of any contaminated materials, such as rags or closes used during inspection, in accordance with local waste disposal regulations. | |
| | 5 | | - Regularly review safety procedures: Periodically review and update safety procedures to ensure they remain comprehensive and up-to-date with evolving industry standards and best practices. | |
| | | | - Proper signage: Ensure the work area is clearly marked with appropriate warning signs indicating "high voltage" and "flammables" to alert personnel of the potential hazards. | |
| | | | - Avoid overcrowding: Limit the number of people in the work area to only those essential for the task, reducing the risk of accidents and improving visibility. | |
| | | | - Fire extinguishers: Equip the work area with suitable fire extinguishers for Transformer Oil fires, such as Class BC or BE powder type extinguishers, ensuring they are readily accessible and staff are trained in their use. | |
| Setting Up Work Area | Fire risk, Poor visibility | 2M | - Good housekeeping: Keep the work area clean and free from debris, specifically oily rags and other flammable materials, to minimise the possibility of a fire starting or spreading. | 1L |
| | | | - Ventilation: Ensure proper ventilation within the work area to dissipate any fumes produced during the handling of Transformer Oil, improving air quality and visibility. | |
| | | | - Spill containment: Utilise spill containment equipment such as drip trays, bunding or oil absorbent pads to prevent oil spills from spreading and causing additional hazards, including slip-and-fall accidents. | |
| | | | - Personal Protective Equipment (PPE): Ensure all workers are provided with and trained in the use of appropriate PPE, such as safety goggles, chemical-resistant gloves, and flame-resistant clothing. | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|--------------------------|--------------------------|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | - Task lighting: Provide adequate task-specific lighting in the work area to improve visibility, reduce eye strain and identify potential hazards. | |
| | | | - Electrical safety: Turn off power to the transformer and properly lockout-tagout (LOTO) electrical circuits prior to performing work, minimising the risk of petrical shock or electrocution. | |
| | | | - Training and supervision: Ensure that all the skers involved in the task have been adequately trained and supervised on safe work procedures, including handlist nazardous substances and working with high voltage systems. | |
| 4. Transformer Isolation | Electric shock, Arthrash | ЗН | | 1L |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------|-------------------------|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | | |
| 5. Draining Oil | Skin irritation, Spills | | | 1L |
| | | | | I |
| | | | | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------|------------------------|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | INITIAL | | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|----------------------------|--------------------------------------|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| 7. Cleaning Internal Parts | Toxic fumes, Inhalation of particles | | | 2M |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|-------------------------|---|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| 8. Replacing Components | Incorrect assembly, Damaging components | 211 | | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------------------|-------------------------------------|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | | |
| 9. Filling with Oil | Overfilling, Spillage | 2M | | 1L |
| | | | | |
| 10. Reassembling Transformer | Pinching injuries, Misaligned parts | 2M | | 1L |







| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|-----------------------------------|---|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | | |
| 12. Cleanup and Waste Disposal | Exposure to hazardous materials, Trip hazards | 2M | | 1L |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------|------------------------|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | | |
| | | | | |



EMERGENCY RESPONSE - CALL 000 FOR EMERGENCIES

Ensure to have an Emergency Management Plan in place as well as adequate numbers of trained first aid staff with easy access to fully stocked first aid kits, rescue equipment, material safety data sheets, adequate access to emergency communication equipment and fire-fighting equipment suitable for all classes of fire and ignition sources.

LEGISLATIVE REFERENCES

RELEVANT LEGISLATION AND CODES OF PRACTICE. DELETE THE LEGISLATIVE REFERENCES. ANY STATE OF AT ARE NOT APPLICABLE.

Queensland & Australian Capital Territory

Work Health and Safety Act 2011

Work Health and Safety Regulations 2011

Legislation QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/work-health-and-safety-laws Codes of Practice QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/codes-of-practice

Legislation ACT: https://www.worksafe.act.gov.au/laws-and-compliance/acts-and-regulations

Codes of Practice ACT: https://www.worksafe.act.gov.au/laws-and-compliance/codes-of-practice

New South Wales

Work Health and Safety Act 2011

Work Health and Safety Regulations 2017

Legislation NSW: https://www.safework.nsw.gov.au/legal-obligations/legislatide

Codes of Practice NSW: https://www.safework.nsw.gov.au/resource-library/lis

Northern Territory

Work Health and Safety (National Uniform Legislation) Act 2011

Work Health and Safety (National Uniform Legislation) Regulation 201

Legislation NT: https://worksafe.nt.gov.au/laws-and-compliance/wo_place-

Codes of Practice NT: https://worksafe.nt.gov.au/f

South Australia

Work Health and Safety Act 2012 (SA)

Work Health and Safety Regulations 2012 (SA)

Legislation for SA: https://www.safework.sa.gov.au/resources/legislation

Codes of Practice for SA: https://www.safework.sa.gov.au/work_aces/codes-of-practice#COPs

Tasmania

Work Health and Safety Act 2012

Work Health and Safety (Transitional and Consequential Provisions) Act 2012

Work Health and Safety Regulations 2012

Work Health and Safety (Transitional) Regulations 2012

Legislation for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/acts-and-regulations

Codes of Practice for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/codes-of-practice

Details of permits, licenses or access required by regulatory bodies (add or delete as required):

- Permits from local council
- Authorisation to commence work
- Any required documents.

Victoria

Occupational Health al. Safety Act

Occupational Health and afety gulations 2017

Legis on VIC: https://www.csafe.vic.gov.au/occupational-health-and-safety-act-and-

gulat

les on actice VI atps://www.worksafe.vic.gov.au/compliance-codes-and-codes-practice

Western Australia

Work Health and Safety Act 2020

Work Health and Safety Regulations 2022

Legislation Western Australia: https://www.commerce.wa.gov.au/worksafe/legislation

Codes of Practice WA: https://www.commerce.wa.gov.au/worksafe/codes-practice

Safe Work Australia Links

Law and Regulation (All States): https://www.safeworkaustralia.gov.au/law-and-regulation Model Codes of Practice: https://www.safeworkaustralia.gov.au/resources-publications/model-codes-of-practice

Model Codes of Practice

- Managing noise and preventing hearing loss at work
- Confined spaces
- Labelling of workplace hazardous chemicals
- Managing risks of hazardous chemicals in the workplace
- Welding processes
- First aid in the workplace
- Managing the risk of falls at workplaces
- Hazardous manual tasks
- Managing the risk of falls in housing construction
- Managing electrical risks in the workplace
- Demolition work
- Excavation work
- Work health and safety consultation, cooperation and coordination
- Managing the work environment and facilities
- How to manage work health and safety risks
- Managing risks of plant in the workplace
- Construction work





SIGNATORIES OF THE SAFE WORK METHOD STATEMENT

The signed and dated personnel listed below have cooperated in the consultation and development of this Safe Work Method Statement which has been approved by the Person/s Conducting a Business or Undertaking (PCBU). In signing this Safe Work Method Statement each individual acknowledges and confirms that they have read this SWMS in full, having raised any questions for items on this Safe Work Method Statement that require clarification, and confirms that they are competent, skilled and knowledgeable for the task assigned to them. Every person acknowledges that they have received the relevant training and qualifications where required, before carrying out any work contained in this Safe Work Method Statement. By signing this Safe Work Method Statement each individual agrees to work safely, to follow any safe work instructions which are provided, and agrees to use all Personal Protective Equipment where appropriate.

| Worker Name | Signature | Date |
|-------------|-----------|------|
| | | |
| | | |
| | | |
| | | |
| | | |

SAFE WORK IN THE STATEMENT MONITORING AND REVIEW

The SWMS must be reviewed regularly to make sure it remains a fective of must be reviewed (and revised if necessary) if relevant control measures are revised. The view process should be carried out in consultation with workers (including contractors of the SWMS and their health and safety representatives who represented that work group at the workplace.

When the SWMS has been revised the PCBU mast ensure that advised that a revision has been made and how they can access the revised SWMS, including all persons who will need to change a work procedure or system as a rest of the review are advised of the changes in a way that will enable them to implement their duties and the involved in the work must be provided with the relevant information and instruction that will assist them to understand and implement the revised SWMS.

The SWMS must be monitored regularly for the effectiveness of ensuring hazard controls are effective in reducing the risk of incidents, keeping the workplace safe for all personnel. The person responsible for monitoring the effectiveness of the Safe Work Method Statement should employ a multi-faceted approach which includes but is not limited to:

- Spot Checks.
- 2. Consultation with workers, contractors and sub-contractors.
- 3. Internal audits on a continual basis.

An approach of continuous improvement, promptly recording inconsistencies or deficiencies, followed up by immediate corrective action and consultation with all relevant personnel ensures that the PCBU is consistently developing ever-improving systems of safe work principles.

| REVIEW NUMBER | 1 | 2 | 3 | 4 | 5 | 6 | 7 |
|---------------|---|---|---|---|---|---|---|
| NAME | | | | | | | |
| INITIALS | | | | | | | |
| DATE | | | | | | | |

Version 2.5 Authorised by Review # Date of Issue: Review Date: 16





SAFE WORK METHOD STATEMENT REVIEW CHECKLIST

This Safe Work Method Statement Review Checklist is to be followed and used upon initial development of the SWMS to help ensure that all steps have been adequately taken before work commences. Think of this document as an internal audit review checklist before commencing work, and may form part of a Toolbox Talk (safety meeting) and may be used as an opportunity for education and training.

| ITEMS WHICH MUST BE INCLUDED IN THE SWMS | COMPLETED | COMMENTS |
|---|---------------|----------|
| | | |
| The company details have been entered, including the project name and address. | | |
| All relevant personnel consulted during the development of the SWMS. | | |
| Name, signature, position and date signed of the person approving the SWMS. | | |
| Specific personnel and qualifications, experience is noted in the SWMS. | 7 | |
| Provides a step-by-step process of tasks required to carry out the activity or task. | | |
| adequate risk assessment of any identified hazards has been completed. | | |
| Foreseeable hazards are identified and documented for each step. | | |
| Any hazards listed in any site risk assessments have been added to the SWMS | | |
| SWMS initial risk (IR) column as well as residual risk (RR) column pleted. | | |
| Check control measures added to the SWMS are the most effective selective selectives | \boxtimes | |
| Responsible person is assigned and listed on the part the improved the measures. | | |
| Permit or licenses requirements specified, sur as Hot Work, Electric Work, Work at Heights etc. | \boxtimes | |
| SWMS identifies plant and equipment to be us | \boxtimes | |
| Details of inspection checks required for any equipment listed noted on the SWMS. | \boxtimes | |
| Describes any mandatory qualifications, experience, use or skills required to perform the work. | | |
| Applicable personal protective equipment is selected on the SWMS. | \boxtimes | |
| Reflects and documents any legislative references and/or Australian Standards. | | |
| dentifies any hazardous substances used with specific control measures in line with any SDS. | | |
| | | |
| REVIEWED BY | DATE REVIEWE | D |
| SIGNATURE | DATE COMPLETI | ED |