



| Using Safety Lines And A | nchors SAFE WORK MET | HOD STATEMENT (SWMS) | |
|--|--|--|-------------------------------------|
| TASK OR | ACTIVITY: Using Safety Lines Ar | nd Anchors | |
| Business Name: | | ABN: | SWMS# |
| Business Address: | | | |
| Contact Person: | Phone: | E 111: | |
| | | | |
| THIS SAFE WORK METHOD | STATEMENT IS APPROTO BY | THE PCL OF THE ROJECT | |
| Under the Work Health and Safety Regulation (WHS Regulation), a person conduct the proposed work starts. | eting a business or under o (PC 1) is | required to en that a safe work method s | statement (SWMS) is prepared before |
| Full Name: | | | |
| Signature: | NY | Title: | Date: |
| Details of the person(s) responsible for ensuring implementation, monitoring | opliance the VMS a vell as review | s and modifications of the SWMS. | |
| Full Name: | | Title: | Phone: |
| ALL PERSONNEL PARTICIPATING IN ANY ACTIVITY ON THIS MIS MIS MIS MIS MIS MIS MIS MIS MIS M | NA, 2 OF ALL RELEVANT PERSONNI EVELOPMENT AND APPROVAL OF | EL WHO HAVE BEEN CONSULTED AND CO | OMMUNICATED TO IN THE |
| Safety meetings or toolbox talks will be sched ed in accomply with gislative requirements to first identify any site hazards, hazards and then to further take steps to either eliminate or continuate hazard. | | | |
| If an incident or a near miss occurs, all work must sto, an atalety. Depending on the severity of the incident, a meeting will be called with all workers to amend the SWMS if required. The meeting may also be an educational opportunity. | | | |
| Any changes made to the SWMS after an incident or a near miss must be approved by the Person Conducting Business or Undertaking and communicated to all relevant personnel. | | | |
| The SWMS must be kept and be available for inspection at least until the work is completed. Where a SWMS is revised, all versions should be kept. If a notifiable incident occurs in relation to which the SWMS relates, then the SWMS must be kept for at least two years from the occurrence of the notifiable incident. | | | |

Version 2.5 Authorised by Review # Date of Issue: Review Date: 1





| CLIENT OR PRINCIPAL | CONTRACTOR DETAILS |
|--|---|
| Client: | SCOPE OF WORKS |
| Project Name: | |
| Project Address: | |
| Project Manager: | |
| Contact Phone: | |
| Date SWMS supplied to Project Manager: | |
| ANY HIGH BIOK CONSTRUCTOR | NAME OF THE POLIT |
| ANY HIGH-RISK CONSTRUCTOR | N WC & BEIN C ARIED OUT |
| ☐ involves a risk of a person falling more than 2 meters | is carried out on or near pressurised gas mains or piping |
| ☐ is carried out on a telecommunication tower | carried out on or near chemical, fuel or refrigerant lines |
| ☐ involves demolition of an element of a structure that is load-bearing | \square is carried out on or near energised electrical installations or services |
| ☐ involves demolition of an element related to the physical integral of a functure | ☐ is carried out in an area that may have a contaminated or flammable atmosphere |
| ☐ involves, or is likely to involve, disturbing asb | ☐ involves tilt-up or precast concrete |
| ☐ involves structural alteration or repair that —quires term — v sup —rt to prevent collapse | ☐ is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor |
| ☐ is carried out in or near a confined space | ☐ is carried out in an area of a workplace where there is any movement of powered mobile plant |
| ☐ is carried out in/near a shaft or trench deeper that. tunnel involving use of explosives | ☐ is carried out in areas with artificial extremes of temperature. |
| \square is carried out in or near water or other liquid that involves a risk of drowning. | ☐ involves diving work. |
| ANY HIGH-RISK MACHINER | Y OR EQUIPMENT NEARBY |
| | |
| | |
| | |

Version 2.5 Authorised by Review # Date of Issue: Review Date: 2



| RISK MATRIX | | | | | | | | | | |
|-------------------|--|--------------------|-----------------|------------------|--------------------|----------------|---|---------|--------------------------------------|--|
| LIKELIHOOD | INSIGNIFICANT | MINOR | MODERATE | MAJOR | CATASTROPHIC | SCORE | ACTION | HEI | RARCHY OF CONTROLS | |
| ALMOST CERTAIN | 3 HIGH | 3 HIGH | 4 ACUTE | 4 ACUTE | 4 ACUTE | SCORE | ACTION | | Elimination Remove the hazard. | |
| LIKELY | 2 MODERATE | 3 HIGH | 3 HIGH | 4 ACUTE | 4 ACUTE | 4A ACUTE | DO NOT PROCE | | Substitution | |
| POSSIBLE | 1 LOW | 2 MODERATE | 3 HIGH | 4 ACUTE | 4 ACUTE | 3H HIGH | Review before work starts. | | Replace the hazard. | |
| UNLIKELY | 1 LOW | 1 LOW | 2 MODERATE | 3 HIGH | 4 ACUTE | 2M MODERATE | Ensure control measures in place. | Isolate | e People from the hazard | |
| RARE | 1 LOW | 1 LOW | 2 MODERATE | 3 HIGH | 3 HIGH | 1L LOW | nitor and | | Engineering Isolate the hazard. | |
| is the second m | rchy of Controls: ost effective metho nging the work is th | d of controlling a | hazard. Enginee | ering by isolati | on is the in ost e | en 'ive, while | rd. Substitution Administrative effective | | Administrative Change the work. PPE | |

| | | | | PERS | | TIVE EQUIPM | | | | | |
|--------------------|--------------------|--------------------|------------------|-------------|--------------|---------------------------------------|----------------------|------------------------|--------------------|-------------------|---------------------------|
| | | Select the app | ropriate PPŁ | abo v uitab | cor the equi | pment used or | the job task | being perforr | ned (if applica | ıble). | |
| FOOT PROTECTION | HAND PROTECTION | HEAD PROTECTION | HEARING ETION | P ECTION | PROTECTION | FACE PROTECTION | HIGH-VIS CLOTHING | PROTECTIVE CLOTHING | FALL PROTECTION | SUN PROTECTION | HAIR/JEWELLERY SECURED |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| Other PPE R | equired: | | | | | | | | | | |
| | Pe | ermit or Licen | ses Requirem | ents | | Mandatory Qualifications and Training | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|----------------------|---|-----------------|---|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| 1. Preparation | Unsecured equipment, untrained personnel | 2M | - Conduct a comprehensive risk assessment errore commencing any work to identify potential hazards related to unsecured equipment and untrain to personno. - Ensure all safety lines and anchors are inspecting of damage or wear prior to use, with regular maintenance schedules in place. - Verify that all equipment is progrety secured and materials want Australian safety standards and regulations. - Provide thore or training assions or all personal involved in the use of safety lines and anchors, ensuring the ore knowled able abordore procedures and emergency protocols. - Implement a landy switch where explored workers supervise and guide less experienced personnel during a trations or lang safety lines and anchors. - Displored or signal caround the work area indicating the presence of safety lines and anchors, along with an lass lated in. - Ensure that an ersonnel have access to and wear appropriate personal protective equipment (PPE), immigenests and harmesses, while working near or using safety lines and anchors. - Estable or communication plan among team members to coordinate activities and respond promptly to vissues or emergencies. - Unit access to the work area to authorised personnel only to prevent unauthorised individuals from tampering with or misusing safety equipment. - Develop and rehearse emergency rescue plans specifically tailored to situations involving safety lines and anchors, ensuring readiness in case of an incident. - Position anchors according to manufacturers' specifications to ensure maximum stability and load distribution. - Use redundant systems by having backup safety lines available to provide additional protection in case of anchor point failure. - Maintain a clean and organised worksite to prevent trip hazards and ensure that all tools and equipment are stored securely when not in use. - Regularly review and update safety procedures and training materials based on feedback from personnel and any changes in regulations or equipment used. | 1L |
| 2. Anchor Inspection | Failure of anchor points, improper inspection | 3H | Ensure all anchor points are installed by a qualified and competent person in accordance with manufacturer instructions and Australian standards. Conduct pre-use inspection of all anchor points by a trained and competent individual. Maintain a record of inspections, including date, inspector name, and any findings or actions required. | 1L |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------|--|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | - Tag any faulty or suspicious anchor points as out of service immediately and arrange for repair or replacement by a certified professional. | |
| | | | - Use only anchors made from materials that are constitution with the specific environment and conditions, such as corrosion-resistant materials for outdonesse. | |
| | | | - Verify that anchor points have appropriate and ratings the intended use and are suitable for the maximum potential force they may encounted | |
| | | | - Implement regular training sessions for worken of proper inspection techniques and identifying potential defects in anchor points. | |
| | | | - Ensure a secondary system of ackup is available possible to provide additional safety in case of primary anchor possible to provide additional safety in case of primary anchor possible to provide additional safety in case of primary anchor possible to provide additional safety in case of primary anchor possible to provide additional safety in case of primary anchor possible to provide additional safety in case of primary anchor possible to provide additional safety in case of primary anchor possible to provide additional safety in case of primary anchor possible to provide additional safety in case of primary anchor possible to provide additional safety in case of primary anchor possible to provide additional safety in case of primary anchor possible to provide additional safety in case of primary anchor possible to provide additional safety in case of primary anchor possible to provide additional safety in case of primary anchor possible to provide additional safety in case of primary anchor possible to provide additional possible to primary anchor possible to provide additional possibl | |
| | | | - Use visual s, such as i ruction signs diagrams at the site, to remind workers of correct inspection processors. | |
| | | | - Mol and operational conditions regularly, such as weather changes, which might affect a tegrity anchor points. | |
| | | | - Avoid look ations unapproved alterations to anchor points without thorough assessment and recertification by qualific engineer. | |
| | | | - sure at any imporary anchor systems comply with the same level of inspection as permanent systems to fore every use. | |
| | | | ncorporate checks into daily site safety briefings to reinforce the importance of thorough and accurate in ections. | |
| | | | Regularly review and update inspection procedures and criteria to ensure they meet current industry standards and best practices. | |
| | 5 | | - Conduct a thorough inspection of the area where the safety line will be installed to ensure structural integrity and suitability. | |
| | | | - Use only manufacturer-approved anchors and equipment for specific rooftop or elevated areas. | |
| | | | - Follow the manufacturer's guidelines and installation procedures exactly as specified in the installation manual. | |
| 3. Safety Line | | | - Engage qualified personnel with appropriate training and competency in installing safety lines and anchor systems. | |
| Installation | Incorrect installation, failure of safety line | 4A | - Verify that all components of the safety system, including lines and anchors, are free of defects and in good working condition. | 2M |
| | | | - Conduct pre-installation briefing sessions to make workers aware of the specifics of the safety line system being used. | |
| | | | - Ensure that the length and type of the safety line match the task requirements and the specific site conditions. | |
| | | | - Use proper tools and equipment for installation; avoid using makeshift or incorrect tools that could compromise safety. | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|--------------------------|--|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | - Initial test load the safety system under supervision after installation to confirm it can bear potential loads. | |
| | | | - Clearly label and document all installed safety line and anchors, including the date of installation and the installer's details. | |
| | | | - Include routine inspections and maintenant of safety lines and anchors in workplace safety programmes. | |
| | | | - Install signage to warn workers of potential having related to the safety line system when in use. - Provide clear and accessible mergency procedule in configuration of system failure or other incidents. | |
| ł. Safety Check | Overlooking defect inaccurate checks | ЗН | | 1L |
| 5. Briefing and Training | Inadequate training, lack of communication | 3H | | 1L |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|-----------------------|---|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | | |
| 6. Harness Attachment | Faulty attachment, poor equipment condition | 4A | | 2M |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------|--------------------------------|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | • |
| | | | | |
| | | | | |
| | | | | |
| . Edge Protection | Unsafe edge prote on the estup | ЗН | | 2M |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------------------------|---|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| 8. Usage of Safety Lines & Anchors | Incorrect usage, disregarding procedures | 4A | | 2M |
| 9. Work at Height | Falls from height, human error, loose equipment | 4A | | 2M |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|-----------------------------------|--|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | | |
| 10. Retraction of Safety Lines | Snagging hazard, wid ret | 3H | | 2M |
| 1. Dismantling of Anchors | Anchor point failure, dropping objects | 3H | | l 1L |







| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------------------|--------------------------------------|-----------------|--|----------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL |
| 13. Periodic Equipment Check | Overlooking defects, inaccurate cher | ЗН | | 2M |
| 14. Incident Reporting | Miscommunication, delayed reporting | 2M | | 1L |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------------|---|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | | |
| 15. Emergency Response | Poor response time, inadequate procedures | 3Н | | ■ 1L |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|------------------------|--|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | | |
| 6. Post-job Evaluation | Non-evaluation risks, over pokent sues | 2M | | 1L |
| 7. Maintenance | Missed faults, delayed correction | 3H | | 2M |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------|---|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | | |
| | | | | |
| | | | | • |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | 1 | \ | | I |
| | | | | • |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| 18. Anchor Removal | Infrastructure damage, anchor point failure | 3H | | 1L |
| | | | | |
| | | | | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---------------------------------------|---|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | ı |
| | | | | |
| | | | | |
| 19. Debriefing and Training Review | Incomplete debriefing, inadequate follow-up on training | 2M | | 1L |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |



| JOB STEP | POTENTIAL HAZARDS | IR | CONTROL MEASURES | RR |
|---|---|-----------------|--|------------------|
| SPECIFIC WORK STEPS | HAZARDS THAT MAY ARISE | INITIAL RISK | SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS | RESIDUAL RISK |
| 20. Safety line and Anchors Disposal | Faulty disposal procedures, Environment contamination | 2M | | 1L |
| | | | | |



EMERGENCY RESPONSE - CALL 000 FOR EMERGENCIES

Ensure to have an Emergency Management Plan in place as well as adequate numbers of trained first aid staff with easy access to fully stocked first aid kits, rescue equipment, material safety data sheets, adequate access to emergency communication equipment and fire-fighting equipment suitable for all classes of fire and ignition sources.

LEGISLATIVE REFERENCES

RELEVANT LEGISLATION AND CODES OF PRACTICE. DELETE THE LEGISLATIVE REFERENCES. ANY STATE OF AT ARE NOT APPLICABLE.

Queensland & Australian Capital Territory

Work Health and Safety Act 2011

Work Health and Safety Regulations 2011

Legislation QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/work-health-and-safety-laws Codes of Practice QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/codes-of-practice

Legislation ACT: https://www.worksafe.act.gov.au/laws-and-compliance/acts-and-regulations

Codes of Practice ACT: https://www.worksafe.act.gov.au/laws-and-compliance/codes-of-practice

New South Wales

Work Health and Safety Act 2011

Work Health and Safety Regulations 2017

Legislation NSW: https://www.safework.nsw.gov.au/legal-obligations/legislati

Codes of Practice NSW: https://www.safework.nsw.gov.au/resource-library/lis > odes-oi racti

Northern Territory

Work Health and Safety (National Uniform Legislation) Act 2011

Work Health and Safety (National Uniform Legislation) Regulation 201

Legislation NT: https://worksafe.nt.gov.au/laws-and-compliance/wo_place-

Codes of Practice NT: https://worksafe.nt.gov.au/f

South Australia

Work Health and Safety Act 2012 (SA)

Work Health and Safety Regulations 2012 (SA)

Legislation for SA: https://www.safework.sa.gov.au/resources/le_lation

Codes of Practice for SA: https://www.safework.sa.gov.au/work_aces/codes-of-practice#COPs

Tasmania

Work Health and Safety Act 2012

Work Health and Safety (Transitional and Consequential Provisions) Act 2012

Work Health and Safety Regulations 2012

Work Health and Safety (Transitional) Regulations 2012

Legislation for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/acts-and-regulations

Codes of Practice for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/codes-of-practice

Details of permits, licenses or access required by regulatory bodies (add or delete as required):

- Permits from local council
- Authorisation to commence work
- Any required documents.

Victoria

Occupational Health al. Safety Act

Occupational Health and Infety gulations 2017

Legis on VIC: https://www.cksafe.vic.gov.au/occupational-health-and-safety-act-and-

gulat

des on actice VI autros://www.worksafe.vic.gov.au/compliance-codes-and-codes-practice

Western Australia

Work Health and Safety Act 2020

Work Health and Safety Regulations 2022

Legislation Western Australia: https://www.commerce.wa.gov.au/worksafe/legislation Codes of Practice WA: https://www.commerce.wa.gov.au/worksafe/codes-practice

Safe Work Australia Links

Law and Regulation (All States): https://www.safeworkaustralia.gov.au/law-and-regulation Model Codes of Practice: https://www.safeworkaustralia.gov.au/resources-publications/model-codes-of-practice

Model Codes of Practice

- Managing noise and preventing hearing loss at work
- Confined spaces
- Labelling of workplace hazardous chemicals
- Managing risks of hazardous chemicals in the workplace
- Welding processes
- First aid in the workplace
- Managing the risk of falls at workplaces
- Hazardous manual tasks
- Managing the risk of falls in housing construction
- Managing electrical risks in the workplace
- Demolition work
- Excavation work
- Work health and safety consultation, cooperation and coordination
- Managing the work environment and facilities
- How to manage work health and safety risks
- Managing risks of plant in the workplace
- Construction work





SIGNATORIES OF THE SAFE WORK METHOD STATEMENT

The signed and dated personnel listed below have cooperated in the consultation and development of this Safe Work Method Statement which has been approved by the Person/s Conducting a Business or Undertaking (PCBU). In signing this Safe Work Method Statement each individual acknowledges and confirms that they have read this SWMS in full, having raised any questions for items on this Safe Work Method Statement that require clarification, and confirms that they are competent, skilled and knowledgeable for the task assigned to them. Every person acknowledges that they have received the relevant training and qualifications where required, before carrying out any work contained in this Safe Work Method Statement. By signing this Safe Work Method Statement each individual agrees to work safely, to follow any safe work instructions which are provided, and agrees to use all Personal Protective Equipment where appropriate.

| Worker Name | Signature | Date |
|-------------|-----------|------|
| | | |
| | | |
| | | |
| | | |
| | | |

SAFE WORK IN THE STATEMENT MONITORING AND REVIEW

The SWMS must be reviewed regularly to make sure it remains a fective of must be reviewed (and revised if necessary) if relevant control measures are revised. The view process should be carried out in consultation with workers (including contractors of the SWMS and their health and safety representatives who represented that work group at the workplace.

When the SWMS has been revised the PCBU mast ensure that advised that a revision has been made and how they can access the revised SWMS, including all persons who will need to change a work procedure or system as a rest of the review are advised of the changes in a way that will enable them to implement their duties and the involved in the work must be provided with the relevant information and instruction that will assist them to understand and implement the revised SWMS.

The SWMS must be monitored regularly for the effectiveness of ensuring hazard controls are effective in reducing the risk of incidents, keeping the workplace safe for all personnel. The person responsible for monitoring the effectiveness of the Safe Work Method Statement should employ a multi-faceted approach which includes but is not limited to:

- Spot Checks.
- 2. Consultation with workers, contractors and sub-contractors.
- 3. Internal audits on a continual basis.

An approach of continuous improvement, promptly recording inconsistencies or deficiencies, followed up by immediate corrective action and consultation with all relevant personnel ensures that the PCBU is consistently developing ever-improving systems of safe work principles.

| REVIEW NUMBER | 1 | 2 | 3 | 4 | 5 | 6 | 7 |
|---------------|---|---|---|---|---|---|---|
| NAME | | | | | | | |
| INITIALS | | | | | | | |
| DATE | | | | | | | |

Version 2.5 Authorised by Review # Date of Issue: Review Date: 19





SAFE WORK METHOD STATEMENT REVIEW CHECKLIST

This Safe Work Method Statement Review Checklist is to be followed and used upon initial development of the SWMS to help ensure that all steps have been adequately taken before work commences. Think of this document as an internal audit review checklist before commencing work, and may form part of a Toolbox Talk (safety meeting) and may be used as an opportunity for education and training.

| ITEMS WHICH MUST BE INCLUDED IN THE SWMS | COMPLETED | COMMENTS |
|---|--------------|----------|
| | | |
| The company details have been entered, including the project name and address. | | |
| All relevant personnel consulted during the development of the SWMS. | | |
| Name, signature, position and date signed of the person approving the SWMS. | | |
| Specific personnel and qualifications, experience is noted in the SWMS. | 7 | |
| Provides a step-by-step process of tasks required to carry out the activity or task. | | |
| Adequate risk assessment of any identified hazards has been completed. | | |
| Foreseeable hazards are identified and documented for each step. | | |
| Any hazards listed in any site risk assessments have been added to the SWMS | | |
| SWMS initial risk (IR) column as well as residual risk (RR) column pleted. | | |
| Check control measures added to the SWMS are the most effective selections | | |
| Responsible person is assigned and listed on the part the important control measures. | | |
| Permit or licenses requirements specified, sur as Hot Work, Electric Work, Work at Heights etc. | | |
| SWMS identifies plant and equipment to be us | | |
| Details of inspection checks required for any equipment listed an inoted on the SWMS. | | |
| Describes any mandatory qualifications, experience, and or skills required to perform the work. | | |
| Applicable personal protective equipment is selected on the SWMS. | | |
| Reflects and documents any legislative references and/or Australian Standards. | | |
| Identifies any hazardous substances used with specific control measures in line with any SDS. | | |
| | | |
| REVIEWED BY | DATE REVIEWE | D |
| SIGNATURE | DATE COMPLET | ED |