

Applying Fresh Coats Of I	Paint SAFE WORK METH	OD STATEMENT (SWMS)	
TASK OR	ACTIVITY: Applying Fresh Coat	s Of Paint	
Business Name:		ABN:	SWMS#
Business Address:			
Contact Person:	Phone:	E ail:	
THIS SAFE WORK METHOD	STATEMENT IS APPROV D BY	THE PC. OF THE ROJECT	
Under the Work Health and Safety Regulation (WHS Regulation), a person conduct the proposed work starts.	cting a business or und thing (Pc V) is	required to en that a safe work method	statement (SWMS) is prepared before
Full Name:			
Signature:	NY	Title:	Date:
Details of the person(s) responsible for ensuring implementation, monitoring	compliant e of the SWIL as well as re	eviews and modifications of the SWMS.	
Full Name:		Title:	Phone:
ALL PERSONNEL PARTICIPATING IN ANY ACTIVITY ON THIS VMS HAVE THE FOLLOWING COMMUNICATED	NA. 2 OF ALL RELEVANT PERSONN EVELOPMENT AND APPROVAL OF	IEL WHO HAVE BEEN CONSULTED AND (THIS SWMS	COMMUNICATED TO IN THE
Safety meetings or toolbox talks will be sched ed in accorde with regislative requirements to first identify any site hazards, to construct the those hazards and then to further take steps to either eliminate or conclude ach hazard.			
If an incident or a near miss occurs, all work must stead dately. Depending on the severity of the incident, a meeting will be called with all workers to amend the SWMS if required. The meeting may also be an educational opportunity.			
Any changes made to the SWMS after an incident or a near miss must be approved by the Person Conducting Business or Undertaking and communicated to all relevant personnel.			
The SWMS must be kept and be available for inspection at least until the work is completed. Where a SWMS is revised, all versions should be kept. If a notifiable incident occurs in relation to which the SWMS relates, then the SWMS must be kept for at least two years from the occurrence of the notifiable incident.			



CLIENT OR PRINCIPAL	CONTRACTOR DETAILS
Client:	SCOPE OF WORKS
Project Name:	
Project Address:	
Project Manager:	
Contact Phone:	
Date SWMS supplied to Project Manager:	
ANY HIGH-RISK CONSTRUCTOR	ON WC & BEIN C & RIED OUT
involves a risk of a person falling more than 2 meters	is carried out on or near pressurised gas mains or piping
☐ is carried out on a telecommunication tower	carried out on or near chemical, fuel or refrigerant lines
☐ involves demolition of an element of a structure that is load-hearing	☐ is carried out on or near energised electrical installations or services
☐ involves demolition of an element related to the physical interrity structure	☐ is carried out in an area that may have a contaminated or flammable atmosphere
☐ involves, or is likely to involve, disturbing as	☐ involves tilt-up or precast concrete
involves structural alteration or repair the requires to rary so port to prevent collapse	☐ is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor
☐ is carried out in or near a confined space	☐ is carried out in an area of a workplace where there is any movement of powered mobile plant
is carried out in/near a shaft or trench deeper an or tunnel involving use of explosives	☐ is carried out in areas with artificial extremes of temperature.
is carried out in or near water or other liquid that involves a risk of drowning.	involves diving work.
ANY HIGH-RISK MACHINER	Y OR EQUIPMENT NEARBY



RISK MATRIX										
LIKELIHOOD	INSIGNIFICANT	MINOR	MODERATE	MAJOR	CATASTROPHIC	SCORE	ACTION		HEIRARCHY OF CONTROLS	
ALMOST CERTAIN	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4 ACUTE	SCORE	ACTION		Elimination Remoy e the hazard.	
LIKELY	2 MODERATE	3 HIGH	3 HIGH	4 ACUTE	4 ACUTE	4A ACUTE	DO NOT PROCE		Substitution	
POSSIBLE	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	4 ACUTE	3H HIGH	Review before work starts.		Replace the hazard.	
UNLIKELY	1 LOW	1 LOW	2 MODERATE	3 HIGH	4 ACUTE	2M MODERATE	Ensure control measures in place.		Isolation Isolate People from the hazard	
RARE	1 LOW	1 LOW	2 MODERATE	3 HIGH	3 HIGH	1L LOW	nitor and records		Engineering Isolate the hazard.	
is the second m	archy of Controls: nost effective methologing the work is	od of controlling a	a hazard. Engine	ering by isolat	ion is the nost of	e. tive, while	ard. Substitution e Administrative least effective		Administrative Change the work.	

						TIVE EQUIPM					
		Select the app	propriate PPL	abo suitak	ok for the equip	oment used or	the job task	being perfori	med (if applica	able).	
FOOT PROTECTION	HAND PROTECTION	HEAD PROTECTION	THE ARING STION	P _cCTION	PROTECTION	FACE PROTECTION	HIGH-VIS CLOTHING	PROTECTIVE CLOTHING	FALL PROTECTION	SUN PROTECTION	HAIR/JEWELLERY SECURED
Other PPE R	equired:										
	Permit or Licenses Requirements						Mandatory Qualifications and Training				



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
1. Preparation	Tripping hazards, Chemical exposure to cleaning solutions	2M	- Conduct a walk-through of the area to jd any potential tripping hazards such as uneven surfaces, debris, or clutter, and remove them prior to commencion work. - Clearly mark and isolate any areas with now of prior inperfections using warning signs or barriers until they can be repaired. - Use non-slip mats or secure overings on wet do lipper priors to prevent trips and falls. - Ensure all cords are paring, propriat personal protective equipment (PPE), including chemical-resistant gloregogales and mask who mandling any cleaning solutions. - Profess Materias are their safe use. - Utilise the angle process with less hazardous chemicals where possible, ensuring compliance with Australia to chanical safe use to reduce fume accumulation when using chemical cleaning ages. - Schedus regular breaks for workers exposed to cleaning chemicals to minimise prolonged exposure as allow fresh air intake. - Ensure all containers for cleaning solutions are properly labelled and stored in designated areas when not in use. - Immediately clean up any spills of cleaning solutions and dispose of waste materials according to regulatory guidelines to prevent slipping and environmental contamination. - Appoint a safety officer to monitor the preparation area to ensure all control measures are effectively implemented and followed by workers.	1L
2. Sanding Surface	Risk of Dust Inhalation, Noise Exposure	3Н	 Use a dust extraction system to collect and minimise airborne dust. Equip workers with P2 or N95 rated respirators for adequate respiratory protection. Ensure sanding equipment has built-in dust collection bags or shrouds. Conduct sanding in well-ventilated areas, using exhaust fans if necessary. Rotate tasks between workers to limit prolonged exposure to dust and noise. Provide training on the health risks associated with dust inhalation and proper protective measures. Use earmuffs or earplugs with appropriate Noise Reduction Rating (NRR) for noise protection. Maintain sanding equipment to ensure it operates efficiently and reduces unnecessary noise. Implement scheduled breaks to decrease continuous exposure to noise and dust. 	2M



	JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
Regularly monitor air quality to ensure dust levels remain within safe limits according to workplace standards. - Encourage wet sanding techniques where uplicable to suppress dust production Display clear signage indicating high-non, and dust oducing work zones. - Ensure all workers are equified with appropria, presonal as rective equipment (PPE) such as gloves, goggles, and masks to preve, chemical exposu Conduct a toolbod — for to immensing work to sorm the team about potential hazards associated with applying as ex Use only the volvation from the working area by keeping windows and doors open or using exhaust fans to dis visuable and the work area Stord aim, bute mit, data and chemicals in well-ventilated areas away from heat sources and ignition points Imprises a no-smoking policy within and around the areas where primers and other flammable staterials, a stored and used I immediately accessible within the work area Immediat	SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE		SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
standards. - Encourage wet sanding techniques when pipilicable to suppress dust production Display clear signage indicating high-note and dust adducing work zones. - Ensure all workers are equivined with appropria, porsonal or active equipment (PPE) such as gloves, goggles, and masks to previ such emical exposur Conduct a toolboor in nor to homenicing work to yorm the team about potential hazards associated with applying project Use only Warchased or wivelenting area by keeping windows and doors open or using exhaust fans to dis it, hazard as furnes Ensure all workers are equivined with appropria, porsonal (VOC) primers to minimise harmful furnes Les only Warchased or wivelenting area by keeping windows and doors open or using exhaust fans to dis it, hazard as furnes Store arm, pole minimise Store arm, pole minimise and first aid kits easily accessible within the work area Improve a no-smoking policy within and around the areas where primers and other flammable points In workers in emergency procedures, including how to respond to chemical spills or fires Use only intrinsically safe tools and equipment that do not produce sparks when used near flammable materials Regularly inspect and maintain all painting equipment to ensure it is in good condition and does not pose a safety risk Clearly label all containers of primers and flammable materials for easy identification and awareness Allocate specific storage areas for flammable materials, ensuring they are compliant with Australian Safety Standards Dispose of waste materials, empty containers, and rags used with primers promptly and in accordance with environmental regulations.				- Limit the number of workers in sanding areas to reduce overall exposure levels.	
- Display clear signage indicating high-nots and due solducing work zones. - Ensure all workers are equipped with appropriate personal as sective equipment (PPE) such as gloves, goggles, and masks to preven schemical exposit. - Conduct a toolboor bloor to homenicing work to both the team about potential hazards associated with applying potent. - Use only with vibased of the volking area by keeping windows and doors open or using exhaust fans to dis it is hazard as furnes. - Store farm ble minimise hamful furnes Enchotope high art in the working area by keeping windows and doors open or using exhaust fans to dis it is hazard as furnes Store farm ble minimise and chemicals in well-ventilated areas away from heat sources and ignition points. - Store farm ble minimises and first aid kits easily accessible within the work area Imprised a no-smoking policy within and around the areas where primers and other flammable sterials as stored and used In workers in emergency procedures, including how to respond to chemical spills or fires. - Use only intrinsically safe tools and equipment that do not produce sparks when used near flammable materials Regularly inspect and maintain all painting equipment to ensure it is in good condition and does not pose a safety risk Clearly label all containers of primers and flammable materials for easy identification and awareness Allocate specific storage areas for flammable materials for easy identification and awareness Allocate specific storage areas for flammable materials, ensuring they are compliant with Australian Safety Standards Dispose of waste materials, empty containers, and rags used with primers promptly and in accordance with environmental regulations.					
- Ensure all workers are equined with approphs, personal metrice equipment (PPE) such as gloves, goggles, and masks to preven chemical exposu. - Conduct a toolbox or for to remencing work to some the team about potential hazards associated with applying policy. - Use only we rebased on we volation from the working area by keeping windows and doors open or using exhaustfans to dis it. hazar, as furnes. - Enth stropes whild on in the working area by keeping windows and doors open or using exhaustfans to dis it. hazar, as furnes. - Store arm belief my draids and chemicals in well-ventilated areas away from heat sources and ignition points. - Store arm belief my draids and chemicals in well-ventilated areas away from heat sources and ignition points. - Store arm belief my draids and chemicals in well-ventilated areas away from heat sources and ignition points. - Store arm belief my draids and chemicals in well-ventilated areas away from heat sources and ignition points. - Store arm belief my draids and chemicals in well-ventilated areas away from heat sources and ignition points. - Store arm belief my draids and chemicals in well-ventilated areas away from heat sources and ignition points. - Store arm belief my draids and chemicals in well-ventilated areas away from heat sources and ignition points. - Improved and used. - Improved and used. - Improved and an advanced and used. - Improved and an advanced areas are primers and other flammable materials for easy identification and does not pose a safety fisk. - Clearly label all containers of primers and flammable materials, ensuring they are compliant with Australian Safety Standards. - Dispose of waste materials, empty containers, and rags used with primers promptly and in accordance with environmental regulations.				- Encourage wet sanding techniques wher policable to suppress dust production.	
goggles, and masks to preven chemical exposu. - Conduct a toolbos of Norto in mencing work to sorm the team about potential hazards associated with applying prior. - Use only We rebased or we volation trade of compound (VOC) primers to minimise harmful fumes. - Ensign proper in this or in the working area by keeping windows and doors open or using exhaustfans to dis it in hazard is fumes. - Store any tobe minimise. - Store any tobe minimise.				- Display clear signage indicating high-not, and due tooducing work zones.	
- Enstance of the working area by keeping windows and doors open or using exhaust fans to dis it hazar as furmes. - Store are believed. - Improved a no-smoking policy within and around the areas where primers and other flammable atterials, a stored and used. - Improved a no-smoking policy within and around the areas where primers and other flammable atterials. - Improved a no-smoking policy within and around the areas where primers and other flammable atterials, a stereous policy. - In workers in emergency procedures, including how to respond to chemical spills or fires. - Use only intrinsically safe tools and equipment that do not produce sparks when used near flammable materials. - Regularly risk. - Clearly label all containers of primers and flammable materials for easy identification and awareness. - Allocate specific storage areas for flammable materials, ensuring they are compliant with Australian Safety Standards. - Dispose of waste materials, empty containers, and rags used with primers promptly and in accordance with environmental regulations.				goggles, and masks to preven chemical exposition. - Conduct a toolbox and for to a mencing work to come the team about potential hazards associated with applying proper.	
2M Chemical Exposure, Fire from Flammable Materials 2M Improve a no-smoking policy within and around the areas where primers and other flammable aterials or stored and used. 2 Improvers a no-smoking policy within and around the areas where primers and other flammable aterials or stored and used. 3. Applying Primer 2 Improvers a no-smoking policy within and around the areas where primers and other flammable aterials or stored and used. 3. Applying Primer 2 Improvers a no-smoking policy within and around the areas where primers and other flammable aterials or stored and used. 4 Improvers a no-smoking policy within and around the areas where primers and other flammable policy within and around the areas where primers and other flammable aterials or improved and used. 4 Improvers a no-smoking policy within and around the areas where primers and other flammable policy within and around the areas where primers and other flammable aterials or improved and used. 4 Improvers a no-smoking policy within and around the areas where primers and other flammable aterials or improved and used. 5 Improvers a no-smoking policy within and around the areas where primers and other flammable aterials aterials and used. 6 Improvers and used. 6 Improvers and used. 6 Improvers and outer flammable aterials and used in the work area. 7 Improvers a no-smoking policy within and around the areas where primers and other flammable aterials, including how to respond to chemical spills or fires. 7 Improvers a no-smoking policy within and around the areas where primers and other flammable aterials and used. 8 Improvers and used. 9 Improvers and used. 9 Improvers and used. 9 Improvers and used. 9 Improvers and used. 1 Improvers and u				- En: proper ntil n in the working area by keeping windows and doors open or using exhaustfans	
Chemical Exposure, Fire from Flammable Materials 2M Improve a a no-smoking policy within and around the areas where primers and other flammable aterials, se stored and used. Improve a a no-smoking policy within and around the areas where primers and other flammable aterials, se stored and used. Improve a a no-smoking policy within and around the areas where primers and other flammable materials, in workers in emergency procedures, including how to respond to chemical spills or fires. Use only intrinsically safe tools and equipment that do not produce sparks when used near flammable materials. Regularly inspect and maintain all painting equipment to ensure it is in good condition and does not pose a safety risk. Clearly label all containers of primers and flammable materials for easy identification and awareness. Allocate specific storage areas for flammable materials, ensuring they are compliant with Australian Safety Standards. Dispose of waste materials, empty containers, and rags used with primers promptly and in accordance with environmental regulations.		Flammable Materials			
Flammable Materials Implicate a no-smoking policy within and around the areas where primers and other flammable atterials be stored and used. Implicate a no-smoking policy within and around the areas where primers and other flammable atterials be stored and used. Implicate a no-smoking policy within and around the areas where primers and other flammable atterials be stored and used. Implicate a no-smoking policy within and around the areas where primers and other flammable atterials or its pills or fires. In primer a no-smoking policy within and around the areas where primers and other flammable atterials or its pills or fires. In primer a no-smoking policy within and around the areas where primers and other flammable atterials or its pills or fires. In primer a no-smoking policy within and around the areas where primers and other flammable atterials or its pills or fires. In primer a no-smoking policy within and around the areas where primers and other flammable atterials or its pills or fires. In primer and no-smoking policy within and around the areas where primers and other flammable atterials or its pills or fires. In primer and no-smoking policy within and and used. In primer and no-smoking policy within and and used. In primer and no-smoking policy within a				eep firextine ishers and first aid kits easily accessible within the work area.	
Use only intrinsically safe tools and equipment that do not produce sparks when used near flammable materials. - Regularly inspect and maintain all painting equipment to ensure it is in good condition and does not pose a safety risk. - Clearly label all containers of primers and flammable materials for easy identification and awareness. - Allocate specific storage areas for flammable materials, ensuring they are compliant with Australian Safety Standards. - Dispose of waste materials, empty containers, and rags used with primers promptly and in accordance with environmental regulations.	3. Applying Primer				1L
materials. - Regularly inspect and maintain all painting equipment to ensure it is in good condition and does not pose a safety risk. - Clearly label all containers of primers and flammable materials for easy identification and awareness. - Allocate specific storage areas for flammable materials, ensuring they are compliant with Australian Safety Standards. - Dispose of waste materials, empty containers, and rags used with primers promptly and in accordance with environmental regulations. Inhalation of Fumes, Skin Irritation from 2M					
- Clearly label all containers of primers and flammable materials for easy identification and awareness. - Allocate specific storage areas for flammable materials, ensuring they are compliant with Australian Safety Standards. - Dispose of waste materials, empty containers, and rags used with primers promptly and in accordance with environmental regulations.					
- Clearly label all containers of primers and flammable materials for easy identification and awareness. - Allocate specific storage areas for flammable materials, ensuring they are compliant with Australian Safety Standards. - Dispose of waste materials, empty containers, and rags used with primers promptly and in accordance with environmental regulations.					
Safety Standards. - Dispose of waste materials, empty containers, and rags used with primers promptly and in accordance with environmental regulations. Inhalation of Fumes, Skin Irritation from 2M				- Clearly label all containers of primers and flammable materials for easy identification and awareness.	
with environmental regulations. Inhalation of Fumes, Skin Irritation from 2M					
	4 Curing Primer				
Unreacted Primer Living			2M		11
	4. Culling Fillilet	Unreacted Primer	ZIVI		I L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
				I
				_
5. Mixing Paint	Chemical exposure, Fire from flam tole	4A		■ 2M
o. Wilhing I aiit	materials	7/		ZIVI
				I



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
6. Applying First Coat	Falling from Height, Musculoskeletal strain	3H		1 1L 1L 1
7. Curing First Coat	Exposure to harmful fumes, skin contact with curing paint	2M		1 1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
8. Sanding First Coat	Dust Inhalation, Noise exposure, E Damage from Debris	3H		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
9. Cleaning Surface	Slips and Falls due to Wet Surface, Chemical Exposure to Cleaning Solutions	ЗН		1
10. Applying Second Coat	Falling from Height, Musculoskeletal Strain, Chemical Exposure	3Н		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
11. Curing Second Coat	Exposure to Harmful Fumes, Skin Contact with Curing Paint	2M-		1L
12. Sanding Second Coat	Dust Inhalation, Noise exposure, Eye Damage from Debris	ЗН		2M



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
13. Applying Final Coat	Falling from height, Must book all Strain, Chemical Exposure	ЗН		1L



JOB STEP	POTENTIAL HAZARDS	IR	CONTROL MEASURES	RR
SPECIFIC WORK STEPS	HAZARDS THAT MAY ARISE	INITIAL RISK	SPECIFIC MEASURES TO BE PUT IN PLACE TO ELIMINATE OR CONTROL THE RISKS	RESIDUAL RISK
14. Curing Final Coat	Exposure to Harmful Fumes, Skin Contact with Curing Paint	2M		1L
15. Clean Up and Waste Disposal	Exposure to Harmful Chemicals, Sharp objects leading to cuts or punctures	2M		 1L









EMERGENCY RESPONSE - CALL 000 FOR EMERGENCIES

Ensure to have an Emergency Management Plan in place as well as adequate numbers of trained first aid staff with easy access to fully stocked first aid kits, rescue equipment, material safety data sheets, adequate access to emergency communication equipment and fire-fighting equipment suitable for all classes of fire and ignition sources.

LEGISLATIVE REFERENCES

RELEVANT LEGISLATION AND CODES OF PRACTICE. DELETE THE LEGISLATIVE REFERENCE. N ANY STATEMENT ARE NOT APPLICABLE

Queensland & Australian Capital Territory

Work Health and Safety Act 2011

Work Health and Safety Regulations 2011

Legislation QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/work-health-and-safety-laws Codes of Practice QLD: https://www.worksafe.qld.gov.au/laws-and-compliance/codes-of-practice

Legislation ACT: https://www.worksafe.act.gov.au/laws-and-compliance/acts-and-regulations

Codes of Practice ACT: https://www.worksafe.act.gov.au/laws-and-compliance/codes-of-practice

New South Wales

Work Health and Safety Act 2011

Work Health and Safety Regulations 2017

Legislation NSW: https://www.safework.nsw.gov.au/legal-obligations/legis

Codes of Practice NSW: https://www.safework.nsw.gov.au/resource-library.

Northern Territory

Work Health and Safety (National Uniform Legislation) Act 201

Work Health and Safety (National Uniform Legislation) Regulations 26

Legislation NT: https://worksafe.nt.gov.au/laws-and-compliance/prkplate fety-lay

Codes of Practice NT: https://worksafe.nt.gov.a/

South Australia

Work Health and Safety Act 2012 (SA)

Work Health and Safety Regulations 2012 (S

Legislation for SA: https://www.safework.sa.gov.au/resources gislation

Codes of Practice for SA: https://www.safework.sa.gov.au/w/cplaces/codes-of-practice#COPs

Tasmania

Work Health and Safety Act 2012

Work Health and Safety (Transitional and Consequential Provisions) Act 2012

Work Health and Safety Regulations 2012

Work Health and Safety (Transitional) Regulations 2012

Legislation for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/acts-and-regulations

Codes of Practice for TAS: https://worksafe.tas.gov.au/topics/laws-and-compliance/codes-of-practice

Details of permits, licenses or access required by regulatory bodies (add or delete as required):

- Permits from local council
- Authorisation to commence work
- Any required documents.

Victoria

Ocupational Health Safety A 2004

Oct ational Health an Safet regulations 2017

Legis ion VIC: https://www.orksafe.vic.gov.au/occupational-health-and-safety-act-and-

gula

des of actice V/ attps://www.worksafe.vic.gov.au/compliance-codes-and-codes-practice

Western Australia

Work Health and Safety Act 2020

Work Health and Safety Regulations 2022

Legislation Western Australia: https://www.commerce.wa.gov.au/worksafe/legislation

Codes of Practice WA: https://www.commerce.wa.gov.au/worksafe/codes-practice

Safe Work Australia Links

Law and Regulation (All States): https://www.safeworkaustralia.gov.au/law-and-regulation Model Codes of Practice: https://www.safeworkaustralia.gov.au/resources-publications/model-codes-of-practice

Model Codes of Practice

- Managing noise and preventing hearing loss at work
- Confined spaces
- Labelling of workplace hazardous chemicals
- Managing risks of hazardous chemicals in the workplace
- Welding processes
- First aid in the workplace
- Managing the risk of falls at workplaces
- Hazardous manual tasks
- Managing the risk of falls in housing construction
- Managing electrical risks in the workplace
- Demolition work
- Excavation work
- Work health and safety consultation, cooperation and coordination
- Managing the work environment and facilities
- How to manage work health and safety risks
- Managing risks of plant in the workplace
- Construction work



SIGNATORIES OF THE SAFE WORK METHOD STATEMENT

The signed and dated personnel listed below have cooperated in the consultation and development of this Safe Work Method Statement which has been approved by the Person/s Conducting a Business or Undertaking (PCBU). In signing this Safe Work Method Statement each individual acknowledges and confirms that they have read this SWMS in full, having raised any questions for items on this Safe Work Method Statement that require clarification, and confirms that they are competent, skilled and knowledgeable for the task assigned to them. Every person acknowledges that they have received the relevant training and qualifications where required, before carrying out any work contained in this Safe Work Method Statement. By signing this Safe Work Method Statement each individual agrees to work safely, to follow any safe work instructions which are provided, and agrees to use all Personal Protective Equipment where appropriate.

Worker Name	Signature	Date

SAFE WORK IN 'THE 'S' NTEMANT MONITORING AND REVIEW

The SWMS must be reviewed regularly to make sure it remain effect, and must be reviewed (and revised if necessary) if relevant control measures are revised. The view should be carried out in consultation with workers (including contractors as an intractors of the SWMS and their health and safety representatives who represented that work group at the workplace.

When the SWMS has been revised the PCBD mest ensure the advised that a revision has been made and how they can accept the revised SWMS, including all persons who will need to change a work procedure or system as a remotified the review are advised of the changes in a way that will enable them to implement their duties the thing with the revised SWMS. All workers that will be involved in the work must be provided with the relevant information and instruction that will assist them to understand and implement the revised SWMS.

The SWMS must be monitored regularly for the effectiveness of ensuring hazard controls are effective in reducing the risk of incidents, keeping the workplace safe for all personnel. The person responsible for monitoring the effectiveness of the Safe Work Method Statement should employ a multi-faceted approach which includes but is not limited to:

- Spot Checks.
- Consultation with workers, contractors and sub-contractors.
- 3. Internal audits on a continual basis

An approach of continuous improvement, promptly recording inconsistencies or deficiencies, followed up by immediate corrective action and consultation with all relevant personnel ensures that the PCBU is consistently developing ever-improving systems of safe work principles.

REVIEW NUMBER	1	2	3	4	5	6	7
NAME							
INITIALS							
DATE							



SAFE WORK METHOD STATEMENT REVIEW CHECKLIST

This Safe Work Method Statement Review Checklist is to be followed and used upon initial development of the SWMS to help ensure that all steps have been adequately taken before work commences. Think of this document as an internal audit review checklist before commencing work, and may form part of a Toolbox Talk (safety meeting) and may be used as an opportunity for education and training.

ITEMS WHICH MUST BE INCLUDED IN THE SWMS	COMPLETED	COMMENTS	
The company details have been entered, including the project name and address.			
All relevant personnel consulted during the development of the SWMS.			
Name, signature, position and date signed of the person approving the SWMS.			
Specific personnel and qualifications, experience is noted in the SWMS.	7		
Provides a step-by-step process of tasks required to carry out the activity or task.			
Adequate risk assessment of any identified hazards has been completed.			
Foreseeable hazards are identified and documented for each step.	\boxtimes		
Any hazards listed in any site risk assessments have been added to the SW. S.			
SWMS initial risk (IR) column as well as residual risk (RR) column sympleted.			
Check control measures added to the SWMS are the most effective sections.			
Responsible person is assigned and listed on the placenta. Of control measures.			
Permit or licenses requirements specified, so in as Hot Work, Electrical Work, Work at Heights etc.			
SWMS identifies plant and equipment to be			
Details of inspection checks required for any equipment lister are noted on the SWMS.			
Describes any mandatory qualifications, experience, ang or skills required to perform the work.			
Applicable personal protective equipment is selected on the SWMS.			
Reflects and documents any legislative references and/or Australian Standards.			
Identifies any hazardous substances used with specific control measures in line with any SDS.			
REVIEWED BY	DATE REVIEWE	D	
SIGNATURE	DATE COMPLETED		